



Effective From 21st April, 2026

Product	Product Model	Product Description	DPP	MRP
Hikvision Logo WD Purple HDD				
	2 TB Surveillance HDD (HIKVISION)	Buffer Size - 128MB, Rotation Speed - 5400 RPM, Transfer rate - 176.4MB/s, 128 MB cache, SATA 6GB/S	Call For Price	Call For Price
	4 TB Surveillance HDD (Hikvision)	BufferAmount-64MB, RoHScompatible, Transfer Rate-145MB/s, 64MB Cache, SATA 6Gb/s, 23dBA, 300,000 unload cycles, 5400RPM	Call For Price	Call For Price
	6 TB Surveillance HDD (Hikvision)	Buffer Size - 256 MB, Rotation Speed - 5400 RPM, Transfer rate - 176.4MB/s, 128 MB cache, SATA 6GB/S	Call For Price	Call For Price
	8 TB Surveillance HDD (Hikvision)	BufferAmount-64MB, RoHScompatible, Transfer Rate-145MB/s, 64MB Cache, SATA 6Gb/s, 23dBA, 300,000 unload cycles, 5400RPM	Call For Price	Call For Price
	10 TB Surveillance HDD (Seagate)	CaheBuffer- 256MB, Internal data transfer rate-2169 Mb/s, I/O data-transfer rate- 600 MB/s max, 7200 RPM	Call For Price	Call For Price
Hikvision Analog and Network Cable				
	DS-1LN6U-W/CCA (UTP CAT6 CCA)	CAT. 6 CCAU/UTP 4x2x23AWG, 1 PVC, ISO/IEC11801, HDPE, 305m CCA,Coppercontent:27% Material-Solid-Bare Copper	Rs. 10,035	Rs. 12,544
	DS-1LN6UU/CCA (CAT6 U/UTP CCA)	CCA, 0.57±0.01mm 23AWG, Cat 6, U/UTP, CPR Eca,1.02 ± 0.05 mm, PVC, Grey, 305±1.5m, Rip Cord,Separator, Copper content:22% Material-Solid- Bare Copper	Rs. 8,887	Rs. 11,109
	DS-1LN6U-SCO (UTP CAT6)	U/UTP CAT6-6P- PVC-CMX category ISO/IEC11801, ANSI/TIA-568- C.2, RoHS2.0 TIA-568-C.2 YD/T1019 Standard, Material-Solid-Bare Copper	Rs. 24,654	Rs. 30817
	DS-1LN5EO-UU/E (CAT 5E)	U/UTP CAT5E-4P- PE, Solid-Bare Copper material,0.500 (24AWG), HDPE insulation, ≤60V,DCResistance(Ω/100m) max, 305 m CAT5E UTP Outdoor Network Cable, Full diameter and fulllength, Quality verified by Fluke test, Guaranteed long PoE transmission distance.	Rs. 19,781	Rs. 24,726
	DS-1LN6UZC0 (U/UTP Cat6 PVC 24AWG Cable)	Cat.6, ISO/IEC 11801, ANSI/TIA-568.2-D, RoHS 2.0, Solid Bare Copper (99.95%), 0.515 ± 0.005 mm 24AWG diameter conductor, h strong mechanical properties, and high tensile and compressive strength, reducing damage during the project.	Rs. 21,215	Rs. 26,519
	DS-1LH1SCAR1742C RG174+Power cable)	BareCopper26AWG0.385+0.005mmSPE,1.45+0.05mm,Aluminum foil bonded Copper Clad Aluminum Magnesium 0.115 + 0.005 mm 55%,55 +6 ohms,Stranded CCAM 20*0.15±0.004 mm,PVC , 1.50 ±0.10 mm 20.35 mm,100 m,4.5 + 0.30 mm,Black,-25-70-C	Rs.2,365	Rs.2,956
	DS-1LH1SCAM592C (Mini RG59 Siamese Cable) (2+1 Cable)	90/180m mini RG59 Siamese cable, Bare Copper material, 26AWG wire gauge, PVC, Compliant with RoHS 2.0, Compliant with RoHS 2.0, Braiding material is Copper Clad Aluminium Magnesium, Excellent anti-interference performance	Rs. 4,014	Rs. 5,017
	DS-1LN6OUTPE (U/UTP Cat6 PE 24AWG Cable)	Cat 6, Solid-Bare Copper, ISO/IEC11801, ANSI/TIA- 568.2-D, RoHS 2.0, HDPE, 0.515±0.01 mm, 24AWG, Tensile strength ≥ 75% of before aging, Elongation ≥ 75% of before aging	Rs. 23,221	Rs. 29,026