




Effective From 21st April 2026				
Product Image	Product Model	Product Description	DPP	MRP
Value Series				
	5 Port Fast Ethernet Switch (DS-3E0105D-O)	Support MDI/MIDX, 10/100 Mbps adaptive Ethernet ports, 5 V DC, 0.6 A, 1 Gbps switching capacity	Rs. 785	Rs. 981
	8 Port Fast Ethernet Switch (DS-3E0108D-O)	Support MDI/MIDX, 10/100 Mbps adaptive Ethernet ports, Support ADI/ADIX, 5 V DC, 0.6 A, Support desktop and wall-mounting, Plug & play, and easy to use	Rs. 1,047	Rs. 1,309
Hikvision Unmanaged Gigabit Switch				
	DS-3E0505D-O (5-Port Gigabit Switch)	Supports MDI/MIDX, Unmanaged Gigabit Switch, 5 Ports x1000Mbps IEEE802.3, IEEE802.3u standard, 2k MAC Support 5 VDC, Plug and play, Store-and-forward switching, 0.6A, 10Gbps Backplane bandwidth	Rs. 1,309	Rs. 1,636
	DS-3E0508D-O (8-Port Gigabit Switch) 510	Unmanaged Gigabit Switch, 8 Ports x1000Mbps IEEE802.3, IEEE802.3u standard, 4k MAC Support 9VDC, 1 A, 16Gbps Backplane bandwidth	Rs. 2,618	Rs. 3,272
	DS-3E0516-E(C) (16 port Gigabit switch)	32Gbps Exchange Capacity, 16 Ports, 16x 1000Mbps 220VAC, 0.3A, 23.808Mbps packet forward rate IEEE802.3u standard, 4.1Mbits internal cache	Rs. 7,195	Rs. 8,993
	DS-3E0524-E(C) (24 port Gigabit switch)	48Gbps Exchange Capacity, 24 Ports, 24x 1000Mbps 220VAC, 0.7A, 35.712Mbps packet forward rate IEEE802.3u standard, 4.1Mbits internal cache	Rs. 8,769	Rs. 10,961
Hikvision Smart Managed Switch				
	DS-3E1105P-EI (Smart Managed)	1Gbps Switching Capacity, 5 Ports, 4x 100Mbps 48 VDC, 1.35 A, 300m when extend IEEE802.3at/af standard, 6KV Surge Protection	Rs. 4,019	Rs. 5,024
Hikvision Unmanaged POE Switch				
	DS-XS06-P (4 Port)	4 x 10/100 Mbps PoE RJ45 port and 2 x 10/100 Mbps RJ45 port, Whole-device PoE power of 35 W, Long-range transmission supported, High-priority ports supported.	Rs. 2,350	Rs. 3,000
	DS-XS10-P (8 Port)	8 x 10/100 Mbps PoE RJ45 port and 2 x 10/100 Mbps RJ45 port, Whole-device PoE power of 60 W, Long-range transmission supported, High-priority ports supported	Rs. 3,500	Rs. 4,500
Hikvision POE Switch				
	DS-3E0105P-E/M (4-Port PoE Switch)	L2, Unmanaged, 5Ports, 4x100m, 48VDC, 0.8A, 250m when extend IEEE802.3, IEEE802.3u standard	Rs. 3,403	Rs. 4,253
	DS-3E0109P-E/M (8-Port PoE Switch)	L2, Unmanaged, 9 Ports IE51 VDC, 1.25 A, 250m when extend IEEE802.3af, 8x100m standard	Rs. 5,549	Rs. 6,936
	DS-3E0318P-E/M (16-Port PoE Switch)	L2, Unmanaged, 16Ports, 100m(N), 100~240VAC 50/60Hz IEEE802.3at standard, 250m when extend	Rs. 18,139	Rs. 22,673
	DS-3E0326P-E/M (24-Port PoE Switch)	L2, Unmanaged, 24Ports IEEE802.3af, 24x100m, 250m when extend 100~240 VAC, 50/60Hz	Rs. 23,113	Rs. 28,891
Hikvision Dual Uplink POE Switch				
	DS-3E0106P-E/M (4 port Dual Up Link)	Unmanaged, 1.6 Gbps Switching Capacity, 4 Ports, IEEE 802.3, IEEE802.3u, IEEE802.3x, 48VDC, 0.8A, 300 m long-range transmission.	Rs. 3,926	Rs. 4,907
	DS-3E0310P-E/M (8 Port Fast Ethernet Unmanaged POE Switch)	8 x 10/100Mbps PoE ports and 2 x Gigabit RJ45 port, 6 KV surge protection for PoE ports, up to 300 m long-range transmission, Wire-speed forwarding.	Rs. 6,596	Rs. 8,245
Gigabit Unmanaged POE				
	DS-3E0505P-E/M (4 PORT POE GIGA SWITCH)	Unmanaged, IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE 802.3ab, and IEEE 802.3z standard, Switching Capacity 10 Gbps, Power Supply 48 VDC, 0.8 A	Rs. 4,188	Rs. 5,235



Effective From 21st April 2026				
Product Image	Product Model	Product Description	DPP	MRP
	DS-3E0510P-E/M (8 PORT POE GIGA SWITCH)	Unmanaged, Standard IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z, Switching capacity 20 Gbps, Power supply 48 VDC, 1.35 A	Rs. 7,853	Rs. 9,816
	DS-3E0518P-E/M (16 port POE switch)	16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports, IEEE 802.3at/af standard, IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard, 6 KV surge, protection for PoE ports, PoE power management, Gigabit network access	Rs. 21,830	Rs. 27,288
	DS-3E0526P-E/M (24 Port POE switch)	24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports, IEEE 802.3at/af standard, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z standard, 6 KV surge protection for PoE ports PoE power management	Rs. 29,840	Rs. 37,300
Hikvision Router				
	DS-3WR3N	2.4 GHz: 300 Mbps, IEEE 802.11b/g/n @2.4 GHz, 5-dBi external antennas, Dual antennas for maximum coverage, Supports IPTV, 4 × RJ45, 10/100 Mbps auto-negotiation, ≤ 5.4 W max power consumption, 134 g (0.295 lb.) weight, Wireless Router × 1, Ethernet cable × 1, Quick installation guide × 1	Rs. 1,750	Rs. 2,188
	DS-3WR12C	Four 5-dBi external antennas, ≤ 1167 Mbps data rate, 2.4 GHz, 5 GHz working frequency band, IEEE 802.11/a/n/ac wave 2 @5GHz, IEEE 802.11b/g/n @2.4GHz wireless standard, Broadband account synchronization	Rs. 2,618	Rs. 3,273
SFP Fiber Port Switch				
	HK-SFP-1.25G-20-1310 / HK-SFP-1.25G-20-1550 (SFP Modules)	Single Power Supply 3.3V, Support 1.25G Ethernet, 1250 Mbps data rate, 0~20km distance, 1 connector quality, -9~-1dBm Tx power Note: HK-SFP-1.25G-20-1310 has to work with HK-SFP-1.25G-20-1550 as a pair.	Rs. 6,200	Rs. 7,750
	DS-3T1306P-SI/HS (4 Port Ethernet Unmanaged POE Switch)	3 × 100M PoE ports, 1 × Hi-PoE port, 1 × gigabit RJ45 port and 1 × gigabit SFP Fiber Optical Port, up to 300m long-range transmission, (-30 to 65 °C) design wider temperature, 3.5712 Mpps forwarding rate, 4.8 Gbps switching capacity	Rs. 9,685	Rs. 10,944
	DS-3T0506HP-E/HS (4 Port Unmanaged POE Switch)	3 × gigabit PoE ports, 1 × gigabit Hi-PoE port, 2 × gigabit SFP fiber optical ports, up to 300m long-range transmission, (-30 to 65 °C) design wider temperature, 8.928 Mpps forwarding rate, 12 Gbps switching capacity	Rs. 9,685	Rs. 10,944
	DS-3T0510HP-E/HS (8 Port Unmanaged Industrial POE Switch)	6 × gigabit PoE ports, 2 × gigabit Hi-PoE port, 2 × gigabit SFP fiber optical ports, up to 300m long-range transmission, (-30 to 65 °C) design wider temperature, 14.88 Mbps forwarding rate, 20 Gbps switching capacity	Rs. 15,051	Rs. 18,814
	DS-3E0524TF (24 port Unmanaged Giga Switch)	10/100/1000M Base T(X) (RJ45 ports), IEEE802.3, IEEE802.3u and IEEE802.3x network standards, 48 Gbps switching bandwidth, 35.7 Mpps packet forwarding rate, 2.5 kg weight, 220 VAC power supply	Rs. 27,196	Rs. 33,995
Switching Power Supply				
	DS-2FA1205-DW-IN (5 Ampere)	Input: 200-240 VAC, 50-60Hz, 2A Max Output: 12VDC, 5A Max, Metal Housing	Rs. 1,147	Rs. 1,434
	DS-2FA120A-DW-IN (10 Ampere)	Input: 200-240 VAC, 50-60Hz, 2A Max Output: 12VDC, 10A, Metal Housing	Rs. 1,605	Rs. 2,006
	DS-2FA120K-DW-IN (20 Ampere)	Input: 200-240 VAC, 50-60Hz, 3.5A Max Output: 12VDC, 20A, Metal Housing	Rs. 2,523	Rs. 3,154
Networking Gear				
	DS-1M5EUA-ISU	AX Current,1.5A @25 °C,MAX Voltage≤150VAC Insulation Resistance,≥1000MΩ @100V DC Withstand voltage,1KV AC RMS ContactResistance≤20 mΩ,Tensile Strength 50N for 60s±5s,Insert/Extraction life≥750 cycles	Rs. 7	Rs. 9



Effective From 21st April 2026				
Product Image	Product Model	Product Description	DPP	MRP
	DS-1M6UA-ISU	1.5A @25°C,≤150VAC≥1000MΩ @100V DC,1KV AC RMS,≤20 mΩ 50N for 60s+5s,≥750 cycles,-25~55°C	Rs. 12	Rs. 15
	DS-1FPA1 (1-port Faceplate)	Height86.0mm,Width86.0mm,Depth14.5mm,ColorWhite,Integrated Dust Cover Type Sliding,Outlet OrientationFire resistance UL 94 V-0,FlatTotal Ports, quantity1,Material Type Acrylonitrile butadiene styrene (ABS)	Rs. 110	Rs.138
	DS-1FPA2 (2-port Faceplate)	Height86.0mm,Width86.0mm,Depth14.5mm,ColorWhite,Integrated Dust Cover TypeSliding,Outlet Orientation,Fire resistanceUL 94 V-0,FlatTotal Ports, quantity2,MaterialType Acrylonitrile butadiene styrene (ABS)	Rs. 125	Rs. 156
	DS-1CM1U241U, 24-slot CableManagement	Packaging Type,Box80gPackage dimension,500 x 105 x 58 mm,Packaging quantity 1Height 44.4 mm,Width,483 mmDepth74 mm	Rs. 870	Rs. 1,088
	DS-1CP6U24-1U Cat6 Unshielded 24- port Patch Panel, 1U	DC resistance≤ 20 mΩ,Current Rating1.5 A @ 20 °C,Dielectric Withstand Voltage, RMS, conductive surface,1,000 Vac @ 60s Dielectric Withstand Voltage, RMS, contact-to-contact 1,000 Vac @ 60 s Insulation Resistance, minimum 500 MΩ	Rs. 4,005	Rs.5,006
	DS-1CK6U90T Cat6 Unshielded 90° Punch Down Keystone Jack	Electrical performance guaranteed to meet or exceed the channel specifications to ISO/IEC 11801 Class E and ANSI/TIA-568.2-D Category 6.High performance supports Category 6 performance specification up to 250MHz.	Rs. 145	Rs.181
	DS-1CK6U180T Cat6 Unshielded 180° Punch Down Keystone Jack	White,ANSI/TIACategory,6CableType,Unshielded,Conductor Type,Solid, Stranded,termination Type,IDC,Wiring,TIA 568A, TIA 568B.DC resistance,≤ 20 mΩ,Current Rating,1.5 A @ 20 °C Dielectric Withstand Voltage, RMS, conductive surface,1,000 Vac @ 60s	Rs. 115	Rs.144
	DS-1NP6UECO (0.5m Gray)	Conductor Material,Bare Copper (99.95%)Conductor Diameter 7*0.2mm 24AWGSheath Material PVC,Sheath Thickness,0.50 ± 0.05mm,Sheath Diameter,5.8±0.20 mmSheath Color	Rs.150	Rs.187
	DS-1NP6UECO (0.5m Orange)	Conductor Material,Bare Copper (99.95%)Conductor Diameter 7*0.2mm 24AWGSheath Material PVC,Sheath Thickness,0.50 ± 0.05mm,Sheath Diameter,5.8±0.20 mmSheath Color	Rs.150	Rs.187
	DS-1NP6UECO (1m Orange)	Conductor Material,Bare Copper (99.95%)Conductor Diameter 7*0.2mm 24AWGSheath Material PVC,Sheath Thickness,0.50 ± 0.05mm,Sheath Diameter,5.8±0.20 mmSheath Color	Rs.180	Rs.225
	DS-1NP6UECO (2m Blue)	Conductor Material,Bare Copper (99.95%)Conductor Diameter 7*0.2mm 24AWGSheath Material PVC,Sheath Thickness,0.50 ± 0.05mm,Sheath Diameter,5.8±0.20 mmSheath Color	Rs. 275	Rs.345
	DS-1NP6UECO (3m Grey)	Conductor Material,Bare Copper (99.95%)Conductor Diameter 7*0.2mm 24AWGSheath Material PVC,Sheath Thickness,0.50 ± 0.05mm,Sheath Diameter,5.8±0.20 mmSheath Color	Rs. 355	Rs.444
	DS-1NP6ADLO (5m Blue)	OFC core,stable,reliable and anti interference,Ultra high transmission rate,less latency,wear-resistant and tensile-resistant without breaking	Rs. 625	Rs.782