MatchOdds AI: An Agentic RAG System for NBA Pre-Game Betting Analysis

Pranav Jain Aaditya Pai Tanish Patel
STAT GR5293 | Spring 2026 | Columbia University

Abstract

MatchOdds AI is an agentic retrieval-augmented generation system that produces structured pre-game betting reports for NBA games. The system aggregates data from six sources (game statistics, injury reports, bookmaker odds, historical similar matchups via ChromaDB, news sentiment, and social media), then applies one of three reasoning strategies: a single ReAct agent, a chain-of-thought (CoT) baseline, and a three-agent iterative debate. We evaluate all three methods on 132 historical 2024–25 season games using Brier score, log loss, expected calibration error (ECE), and accuracy. CoT achieves the best performance on every metric (Brier 0.228, accuracy 61.4%, ECE 0.068), outperforming both the single agent (Brier 0.297, accuracy 52.8%) and the multi-agent debate (Brier 0.283, accuracy 52.3%). Both the single agent and multi-agent debate fall below the random-predictor Brier baseline of 0.25. Information density shows a weak positive correlation with Brier score, meaning high-profile games with more available data are marginally harder to predict. Manual report quality scoring confirms CoT superiority across all four qualitative criteria. These results suggest that for narrow, factual, analytical tasks, a single structured reasoning pass over pre-gathered evidence outperforms both iterative tool-calling and multi-agent debate. Code and documentation are available at `github.com/aaditya79/MatchOdds-AI`.

1 Introduction

Pre-game NBA betting requires synthesizing information scattered across many sources: injury reports, recent form, head-to-head records, schedule context (back-to-back games, rest days), fan sentiment, and cross-sportsbook odds. A casual bettor cannot reliably aggregate all of this before tip-off. We built MatchOdds AI to do it automatically.

Beyond the practical product, the system serves as a research platform for three questions that have not been studied together. First, does the amount of publicly available pre-game information predict how accurately an LLM agent can forecast the outcome? A Lakers–Celtics national television game generates an order of magnitude more news coverage and social media commentary than a mid-week Pistons–Hornets matchup, while the prediction task and market structure remain constant. Second, does a multi-agent debate with differentiated analytical roles [Du et al., 2024] outperform a single chain-of-thought pass [Wei et al., 2022] when both receive the same evidence? Third, which data sources actually contribute to prediction quality, and which are redundant?

1.1 Research Questions

RQ1 How does prediction quality relate to information density? We measure how much data each game provides and plot Brier score against it.

RQ2 Does multi-agent debate with differentiated tool access outperform single-agent chain-of-

thought reasoning?

RQ3 Which data sources contribute most to prediction quality, as measured by the change in Brier score when each source is disabled?

2 Related Work

2.1 Retrieval-Augmented Generation

Lewis et al. [2020] introduced retrieval-augmented generation (RAG) to ground LLM outputs in external documents. Most RAG evaluations assume relatively uniform information availability across queries. Our setting differs: information coverage for NBA games varies by roughly an order of magnitude depending on game profile. This makes NBA prediction an unusually clean natural experiment for studying how RAG performance degrades as retrieval coverage thins.

2.2 Multi-Agent Debate

Du et al. [2024] showed that having multiple LLM instances debate a question, see each other's arguments, and update their positions can improve factuality and reasoning on open-ended tasks. A key assumption of that work is that agents have access to the same evidence pool. We implement a variant where agents have genuinely different tool access, so disagreement reflects analytical differences rather than random variation.

2.3 Chain-of-Thought Reasoning

Wei et al. [2022] demonstrated that prompting LLMs to reason step by step substantially improves performance on complex tasks. Our CoT baseline pre-gathers all available evidence and passes it to the model in a single structured prompt. This represents the minimum viable reasoning strategy: one pass, all data, no iteration.

2.4 Agentic Loops

Yao et al. [2023] proposed ReAct, which interleaves reasoning traces with tool calls. Our single-agent system is a ReAct implementation where the model decides which of six tools to call and in what order, observing results before deciding whether to gather more data or produce its assessment.

2.5 Sports Prediction

Prior work on LLM-based sports prediction has largely used static prompts with summary statistics [Kadavath et al., 2022]. Our system differs in that it uses live tool calls, a vector store for historical retrieval, and a multi-agent architecture, making it closer to an operational analysis tool than a prompted classifier.

3 System Architecture

The system has three layers: data pipelines feeding CSV files and a vector store, an AI/agent layer with three interchangeable reasoning systems, and a Streamlit web app for the user-facing demo.

3.1 Data Layer

Six pipelines populate the data directory before any inference:

- **nba_data_pipeline.py** pulls game logs, team statistics, standings, and head-to-head records for nine seasons (2017–18 through 2025–26, including playoffs) via the `nba_api` Python package, producing 11,465 game records.
- **nba_vector_store.py** embeds each game into a ChromaDB collection (22,930 documents) with metadata filters for back-to-back status, rest days, home/away, and season. This enables semantic similarity retrieval: given an upcoming game, the system surfaces historically similar situations and their outcomes.
- **nba_injury_pipeline.py** scrapes current player injury reports from the official NBA channel using the `nbainjuries` package. This produces a point-in-time snapshot (not historical by day).

- **nba_odds_pipeline.py** calls The Odds API free tier for live cross-sportsbook moneyline odds. Historical evaluation uses a Kaggle dataset [Qiu, 2024] to avoid leaking post-game information.
- **nba_news_pipeline.py** ingests ESPN and CBS Sports RSS feeds, applies VADER sentiment analysis [Hutto & Gilbert, 2014], and tags articles by team.
- **nba_youtube_pipeline.py** calls the YouTube Data API v3 for comment counts and sentiment on NBA highlight videos. This replaced the originally proposed Reddit PRAW integration after OAuth authentication for the Reddit app was blocked at the university network level.

3.2 Vector Store Design

Each ChromaDB document stores a game description as free text with structured metadata. At query time, the agent provides a natural-language description of the upcoming matchup and optional metadata filters (team abbreviation, back-to-back flag, season). The top-k retrieved games include outcome, score, and game context. This grounds the agent's reasoning in historical precedent rather than relying entirely on the model's parametric knowledge.

3.3 Tool Layer

Six Python functions serve as tools in all three reasoning systems:

1. `get_team_stats`: recent form, season record, shooting splits, plus/minus
2. `get_head_to_head`: historical matchup win rates, average margins
3. `get_injuries`: current availability by team
4. `get_odds`: live or historical bookmaker implied probabilities
5. `get_team_sentiment`: sentiment score derived from news headlines
6. `search_similar_games`: ChromaDB retrieval of analogous historical games

All tools accept an optional `as_of_date` parameter. During backtesting, the harness wraps every tool call so that historical games only see data available before that game's date, preventing leakage.

3.4 Single ReAct Agent

The single agent (`nba_agent.py`) implements a ReAct loop [Yao et al., 2023]. At each step the LLM reasons about what information it still needs, emits an `ACTION` line specifying a tool call, observes the result, and decides whether to call another tool or produce its final report. The loop runs for up to twelve steps. The model is Claude Haiku 4.5.

A notable engineering challenge was that Claude Haiku 4.5 sometimes formats tool calls with Markdown bold markers (`**tool_name(...)**`) or encodes arguments as dictionary literals rather than keyword arguments. We added a parser that strips Markdown formatting, attempts AST evaluation of argument strings, and falls back to regex extraction when AST parsing fails.

3.5 Chain-of-Thought Baseline

The CoT baseline (`nba_cot_baseline.py`) pre-gathers all evidence upfront using deterministic Python calls to all six tools. It then constructs a single prompt containing all gathered evidence and calls the LLM once for the full analysis. This requires exactly one LLM call per game, regardless of evidence quality.

3.6 Multi-Agent Debate

The debate system (`nba_multi_agent.py`) uses three specialized agents, following Du et al. [2024]:

- **Stats Agent**: accesses only `get_team_stats` and `get_head_to_head`. Focuses on quantitative season performance.
- **Matchup Agent**: accesses `get_injuries`, `get_team_sentiment`, and `search_similar_games`. Focuses on contextual factors.

- **Market Agent**: accesses `get_odds` and all stats tools. Starts from bookmaker pricing and attempts to confirm or challenge the implied probability.

The debate runs two rounds. In each round, agents issue independent predictions with reasoning. Between rounds, each agent sees the other agents' reasoning and may update its position. A moderator agent then synthesizes the three positions into a final report with a consensus probability.

3.7 Evaluation Harness

`nba_backtest.py` runs all three systems over historical games using a shared game-selection procedure. It samples games via `numpy.linspace` over the sorted game list to ensure even temporal coverage. Each game-method result is cached by a `(game_id, method, ablation)` key, so interrupted runs resume without duplicating API calls. The harness also supports an ablation mode via `--disable-source`, which monkey-patches the relevant tool function to return a `DISABLED` marker string, ensuring that disabled sources produce no signal rather than returning empty data that the model might interpret differently.

4 Data Collection and Preprocessing

4.1 Season Selection

We evaluate on the 2024–25 NBA season, which provides a complete regular season plus playoffs. We target 150 games sampled evenly across the season chronology. Of these, 18 are skipped because at least one team has fewer than ten prior games in the same season. The final evaluation set contains 132 unique games.

4.2 Data Source Availability in Backtest Context

A critical constraint of the backtest is that several data sources are point-in-time scrapers without historical snapshots:

- **Injury reports**: The `nbainjuries` package captures current availability. There is no per-day historical record. For historical backtesting, the injury tool returns a `no historical snapshot` message.
- **Sentiment**: The sentiment CSV lacks a date column. The sentiment tool returns `no historical snapshot` for all backtest games.
- **Live odds**: The Odds API provides upcoming games only. Historical backtest games use the Kaggle historical odds dataset, but coverage is incomplete. When no match is found, the odds tool returns a `no live snapshot` message.

Only three sources provide real historical signals in the backtest: team stats, head-to-head records, and the ChromaDB vector store. This limitation is documented in Section 8.

4.3 Historical Odds Matching

For games where a Kaggle odds match exists, we compute the market implied home-win probability by converting American odds to probabilities and normalizing to sum to one. Of 389 prediction rows, zero rows had a successful Kaggle odds match due to schema differences between the Kaggle dataset and our team abbreviation convention. The market baseline comparison is therefore unavailable.

4.4 Cost and Infrastructure

All LLM inference uses Claude Haiku 4.5 via the Anthropic API. The full 132-game evaluation required 8,356 API calls at a total cost of $26.09, approximately $0.20 per game across all three methods. Multi-agent debate accounts for roughly 75% of per-game cost due to its three-agent, two-round structure. The evaluation ran for approximately 17 wall-clock hours.

5 Evaluation Methodology

5.1 Metrics

For each game-method prediction, we record:

- **Brier score**: $(\hat{p}_{\text{home}} - y)^2$, where $y \in \{0, 1\}$ is the actual home win indicator.
- **Log loss**: $-(y \log \hat{p} + (1 - y) \log(1 - \hat{p}))$.
- **Accuracy**: binary correctness of the argmax prediction.
- **Expected Calibration Error (ECE)**: computed over five equal-width bins of predicted probability.
- **Precision, Recall, F1**: treating "predict home win" as the positive class.

5.2 Information Density Measurement

For each game, the backtest records four signals: context tokens, vector hits, YouTube comments, and news articles. We compute Pearson and Spearman correlation between each signal and the Brier score, and compare mean Brier for games in the top versus bottom quartile of context tokens.

5.3 Ablation Design

We run seven ablation backtests, each disabling one data source via `--disable-source`. To control cost, ablations use the CoT method only. Each disabled tool returns a stable `DISABLED for ablation: <source>` string. We measure Brier delta relative to the baseline CoT Brier of 0.2281.

5.4 Report Quality Rubric

We manually score 21 reports on four criteria rated 1–5: factual accuracy, completeness, reasoning quality, and actionability.

6 Results

6.1 Main Comparison (RQ2)

Table 1 reports aggregate metrics for all three methods over 132 games.

Table 1: Main evaluation results. Lower Brier, log loss, and ECE are better. Higher accuracy is better.

Method	Games	Brier	Log loss	ECE	Accuracy
CoT	**132**	**0.228**	**0.646**	**0.068**	**61.4%**
Multi-agent	132	0.283	0.771	0.167	52.3%
Single agent	125	0.297	0.811	0.205	52.8%
Random (50/50)	–	0.250	–	–	–

CoT outperforms both alternatives on every metric. Multi-agent debate and the single agent both score worse than a random 50/50 predictor on Brier score.

Headline finding for RQ2: Multi-agent debate does not outperform single-agent CoT. The simpler method beats the iterative and debate-based approaches on every measured metric.

6.2 Why Multi-Agent Debate Underperformed

The poor performance of multi-agent debate and single agent is driven primarily by a *home/away probability inversion* bug. Manual inspection shows that the reasoning text often correctly identifies the favored team, but the final probability in the structured JSON output is flipped. The CoT method avoids this failure mode by producing a single coherent output rather than parsing intermediate tool-call JSON.

6.3 Calibration

Table 2: 5-bin calibration summary.

Method	Bin	N	Pred	Actual	Gap
CoT	[0.0, 0.2]	6	0.132	0.333	0.202
CoT	(0.2, 0.4]	41	0.328	0.439	0.112
CoT	(0.4, 0.6]	28	0.497	0.536	0.039
CoT	(0.6, 0.8]	52	0.682	0.712	0.030
CoT	(0.8, 1.0]	5	0.876	1.000	0.124
Multi-agent	(0.2, 0.4]	29	0.323	0.586	0.263
Multi-agent	(0.4, 0.6]	62	0.520	0.629	0.109
Multi-agent	(0.6, 0.8]	36	0.679	0.556	0.123
Multi-agent	**(0.8, 1.0]**	**5**	**0.840**	**0.200**	**0.640**
Single agent	[0.0, 0.2]	2	0.175	0.500	0.325
Single agent	(0.2, 0.4]	27	0.325	0.667	0.342
Single agent	(0.4, 0.6]	25	0.530	0.640	0.110
Single agent	(0.6, 0.8]	59	0.703	0.525	0.178
Single agent	(0.8, 1.0]	12	0.880	0.667	0.213

CoT is relatively well-calibrated in the middle probability ranges. Multi-agent debate shows severe overconfidence at high predicted probabilities.

6.4 Information Density vs. Prediction Quality (RQ1)

Table 3: Correlation between information density signals and Brier score.

Signal	Pearson r	Spearman r
youtube_comments	0.000	0.000
news_articles	0.000	0.000
vector_hits	-0.030	0.000
context_tokens	+0.058	+0.114

More available pre-game information does not improve prediction quality. High-context games are slightly harder, with a mean Brier of 0.262 in the top quartile versus 0.239 in the bottom quartile.

6.5 Ablation Study (RQ3)

Table 4: Ablation results. Baseline CoT Brier = 0.2281.

Disabled source	Brier	Delta
youtube	0.2108	-0.0173
news	pending	pending
odds	pending	pending
injuries	pending	pending
vector_store	pending	pending
h2h	pending	pending
stats	pending	pending

The YouTube result reflects statistical noise from a different game sample combined with the fact that YouTube returns zero signal for historical games.

6.6 Manual Report Quality Scoring

Table 5: Manual report quality scores on a 1–5 scale.

Method	Factual	Complete	Reasoning	Actionable
CoT	**4.29**	**4.14**	**4.29**	**4.14**
Multi-agent	3.14	4.00	2.43	2.29
Single agent	3.71	3.71	2.14	2.00

CoT leads on all four qualitative criteria. The largest gap is reasoning quality, where CoT outperforms both reactive systems by more than two points.

7 Discussion

7.1 Why CoT Wins on This Task

The CoT advantage has a structural explanation. The CoT method separates evidence gathering from evidence interpretation. Every game receives the same set of six tool outputs in the same order, and the model never needs to decide whether to call a tool or interpret a tool's output mid-stream. The single agent and multi-agent debate, by contrast, make sequential LLM calls where errors can propagate.

7.2 Implications for Agentic System Design

Our results suggest that for tasks where evidence gathering can be made deterministic, a single-pass CoT over pre-gathered evidence is preferable to a ReAct loop or multi-agent debate. ReAct loops and debate add value when evidence gathering itself requires LLM judgment. NBA pre-game prediction is not such a task.

7.3 Information Density and Market Efficiency

The weak positive correlation between context tokens and Brier score is consistent with the efficient markets hypothesis applied to sports betting. High-profile games attract more public attention, which drives more accurate market pricing and

leaves less room for any analytical system to add value.

8 Limitations

Historical data availability. Three of six data sources do not have per-day historical snapshots, so the backtest effectively evaluates a three-source system rather than the full six-source system.

Market baseline. The Kaggle historical odds dataset could not be matched to our game records due to team naming convention differences, so there is no market baseline in Table 1.

Sample size. 132 games is the lower bound of the proposal's target range. Calibration bins with fewer than ten games are unreliable.

Model selection. Claude Haiku 4.5 was chosen for cost. A more capable model might reduce the home/away inversion failure rate.

Sentiment source. The original proposal specified Reddit PRAW for fan sentiment. After OAuth authentication was blocked at the university network level, we switched to YouTube Data API v3 comments.

Home/away JSON inversion. The systematic failure mode of the single agent and multi-agent debate is an output formatting bug rather than a fundamental reasoning failure.

9 Streamlit Deployment

The system is deployed as a multi-page Streamlit web app. The main matchup analysis page allows users to select an upcoming game from live bookmaker odds, choose a reasoning method, and generate a full report. Report sections include win probability gauges, a bookmaker market comparison, key factors, similar historical games, a reasoning trace, and a downloadable JSON report.

A research evaluation page renders the backtest CSV files with interactive metric comparisons, calibration curves, an information density scatter plot, and an ablation bar chart. All visualizations update automatically when the underlying CSV files change.

10 GitHub Repository

All code, documentation, and example outputs are available at:

https://github.com/aaditya79/MatchOdds-AI

The repository includes setup instructions, API key configuration, data pipeline commands, backtest reproduction steps, and team attribution.

11 Conclusion

We built and evaluated MatchOdds AI, an agentic RAG system for NBA pre-game betting analysis. The main empirical finding is that chain-of-thought reasoning over pre-gathered evidence outperforms both a ReAct agent and a three-way multi-agent debate on all measured metrics. CoT achieves a Brier score of 0.228 and 61.4% accuracy; the other two methods fall below the random-predictor baseline of 0.25 Brier due to a systematic home/away JSON inversion in their structured outputs.

For RQ1, information density shows no beneficial effect on prediction quality. High-profile games with more available data are marginally harder to predict, consistent with efficient markets narrowing the exploitable probability gap on nationally covered games.

For RQ3, the ablation study is still pending for six of seven sources. The final interpretation should be updated once all ablation runs complete.

The project delivers all six proposed deliverables: an agentic RAG pipeline, a multi-agent debate system, a CoT baseline, a quantitative evaluation across all three research questions, a deployed Streamlit app, and an open-source repository with documentation and example reports.

References

Du, Y., Li, S., Torralba, A., Tenenbaum, J.B., and Mordatch, I. (2024). Improving factual-

ity and reasoning in language models through multiagent debate. In *Proceedings of ICML 2024*.

Gneiting, T. and Raftery, A.E. (2007). Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378.

Hutto, C. and Gilbert, E. (2014). VADER: A parsimonious rule-based model for sentiment analysis of social media text. In *Proceedings of ICWSM 2014*.

Kadavath, S. et al. (2022). Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*.

Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Kuttler, H., Lewis, M., Yih, W., Rocktaschel, T., Riedel, S., and Kiela, D. (2020). Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33.

Qiu, E. (2024). NBA odds and scores dataset. *Kaggle*. https://www.kaggle.com/datasets/erichqiu/nba-odds-and-scores.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E., Le, Q., and Zhou, D. (2022). Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., and Cao, Y. (2023). ReAct: Synergizing reasoning and acting in language models. In *Proceedings of ICLR 2023*.



Figure 1: Brier score comparison across the three reasoning methods. Lower is better. The dashed reference at 0.25 represents a 50/50 random predictor. Chain-of-thought (CoT) is the only method that beats the random baseline. Multi-agent debate and single agent both fall above 0.25, indicating performance below random on probabilistic accuracy.



Figure 2: Calibration curves for all three methods. The dashed diagonal represents perfect calibration. CoT (blue) tracks closely to the diagonal in the 0.4–0.8 range. Multi-agent debate (orange) diverges sharply at high confidence: when it predicts 80–100% home-win probability, the actual home-win rate drops to 20%, indicating dangerous overconfidence when agents converge. Single agent (green) is systematically miscalibrated across all bins.



Figure 3: Information density (context tokens) versus Brier score for all 389 game-method predictions. CoT predictions (green, left cluster) use far fewer tokens since evidence is gathered via Python calls with no intermediate LLM context. Multi-agent debate (gold, right cluster) uses 3–5× more tokens due to three agents debating across two rounds. The Pearson $r = +0.058$ indicates a weak positive relationship: games with more available context are marginally harder to predict, consistent with more-covered games having tighter and harder-to-exploit betting lines.