Chapter 1
Introduction

1.1 Background of the Project

India has one of the largest livestock populations in the world, and cattle play a vital role in the agricultural economy. Indigenous cow breeds such as Gir, Kangayam, Ongole, Tharparkar, and others are known for their adaptability, disease resistance, and milk productivity. Accurate identification of these breeds is essential for breeding programs, dairy management, conservation of native genetic resources, and agricultural research.

Traditionally, breed identification is performed manually by experts based on physical characteristics such as body structure, horn shape, coat color, and size. However, manual identification requires domain expertise and can sometimes be inaccurate due to visual similarity between certain breeds. Many indigenous breeds share similar morphological features, making differentiation difficult for non-experts.

With the advancement of Artificial Intelligence and Deep Learning, image-based classification systems have gained significant importance in agriculture. Convolutional Neural Networks (CNNs) have proven highly effective in image recognition tasks by automatically learning discriminative features from images. Transfer Learning techniques further enhance performance by leveraging pretrained models for domain-specific classification problems.

In this project, an AI-based system is developed to classify Indian indigenous cow breeds using image data. The system utilizes the DenseNet121 deep learning architecture with transfer learning to recognize 17 different cow breeds. A web-based interface is developed using Streamlit, allowing users to upload cow images and obtain breed predictions along with confidence scores.

This project aims to bridge the gap between traditional livestock management and modern AI technology by providing a user-friendly, automated breed recognition system. The solution can assist farmers, researchers, and livestock authorities in improving breed identification accuracy and supporting data-driven decision-making in the agricultural sector.

1.2 Statistics of the Project

The proposed project focuses on the development of an Artificial Intelligence-based livestock breed classification system using deep learning techniques. The system is designed to identify indigenous Indian cow breeds from image data using a Convolutional Neural Network (CNN) model with transfer learning.

The following statistical details summarize the technical and structural components of the project:

Dataset Statistics

- Total Number of Classes: **16 Indigenous Indian Cow Breeds**

- Dataset Structure: Image-based dataset organized into breed-wise folders
- Image Format: JPG / JPEG / PNG
- Image Input Size: **224 × 224 pixels**
- Training-Validation Split: **80% Training, 20% Validation**
- Data Augmentation Techniques Used:
    - Rotation
    - Zoom
    - Horizontal Flipping
    - Rescaling

The 16 recognized cow breeds include:
Bargur, Deoni, Gaolao, Gir, Hallikar, Hariana, Kandhari, Kangayam, Kankrej, Krishna, Nagori, Nimari, Ongole, Ponwar, Punganur and Rathi

1.3 Objectives of the Project

The primary objective of this project is to design and develop an intelligent image-based livestock breed classification system using deep learning techniques. The system aims to automate the identification of indigenous Indian cow breeds through a user-friendly web application.

The specific objectives of the project are as follows:

1. To Develop an Automated Breed Classification System

To build a deep learning model capable of accurately classifying 17 indigenous Indian cow breeds based on image input, thereby reducing dependency on manual identification methods.

2. To Implement Transfer Learning Using DenseNet121

To utilize the DenseNet121 pre-trained convolutional neural network architecture and apply transfer learning techniques for efficient feature extraction and improved classification accuracy.

3. To Perform Data Preprocessing and Augmentation

To enhance model performance by applying image preprocessing techniques such as resizing, normalization, rotation, zooming, and horizontal flipping.

4. To Design a Web-Based User Interface

To develop an interactive web application using Streamlit that allows users to upload cow images and receive breed predictions with confidence scores.

5. To Improve Accuracy and Reduce Misclassification

To optimize model parameters, apply regularization techniques, and use early stopping mechanisms to achieve stable and reliable classification performance.

6. To Provide Real-Time Prediction Capability

To enable real-time breed prediction through a locally deployed web application using the command:

streamlit run app.py

7. To Ensure Scalability for Future Expansion

To design the system in a way that allows future integration of additional cattle and buffalo breeds for comparative analysis and extended livestock research.

1.6 Alignment with the Sustainable Development Goals (SDGs)

The proposed Image-Based Indian Cow Breed Classification System aligns with the Sustainable Development Goals (SDGs) established by the United Nations. The alignment is presented in the table below:

SDG Number & Title	Relevance to the Project	Contribution of the System
Sustainable Development Goal 2 – Zero Hunger	Focuses on sustainable agriculture and food security.	Accurate breed identification improves dairy productivity, supports sustainable livestock management, and enhances food security.
Sustainable Development Goal 9 – Industry, Innovation and Infrastructure	Encourages technological advancement and innovation.	Integration of Deep Learning and AI in livestock management promotes digital transformation in agriculture.
Sustainable Development Goal 12 – Responsible Consumption and Production	Promotes sustainable use of natural resources.	Helps preserve indigenous cattle breeds and supports responsible breeding practices.
Sustainable Development Goal 8 – Decent Work and Economic Growth	Supports economic growth and employment opportunities.	Enhances farmer productivity and improves economic outcomes in rural dairy sectors.

1.7 Overview of the Project Report

This report is structured into nine comprehensive chapters, each detailing a specific component of the project lifecycle:

- Chapter 1 – Introduction: Provides background, motivation, objectives of the project and the project overview.
- Chapter 2 – Literature Review: Highlights the existing studies, methods and technologies related to federated search, recommendation systems, and educational resource discovery.
- Chapter 3 – Methodology: Describes the design approach, workflow, and architecture of the system.
- Chapter 4 – Project Timeline: Presents development milestones and review stages.
- Chapter 5 – Analysis and Design: Details the system analysis, requirement specifications, and design diagrams.
- Chapter 6 – Software and Implementation: Explains the front-end, back-end, and database modules with code structure and integration details.
- Chapter 7 – Evaluation: Provides testing results, performance metrics, and usability assessments.
- Chapter 8 – Social, Legal, Ethical, Sustainability, and Safety Aspects: Discusses compliance and societal implications of the project.
- Chapter 9 – Conclusion and Future Work: Summary of the key findings, conclusions of the project and the future work that has been planned.

Every section explains how the evolution of the Study Search Engine from ideas to the implementation as a unified educational resource platform supporting the education of the learners, developers and researchers with personalized, secure and sustainable learning with ranked results.

Chapter 2
Literature Review

2.1 Graph Synthesis for Pig Breed Classification From Muzzle Images

[1] S. Chakraborty, K. Karthik and S. Banik (2021). Chakraborty et al. proposed a graph synthesis-based deep learning framework for pig breed classification using muzzle images. Their approach extracted structural patterns from muzzle regions and transformed them into graph representations for classification. The study demonstrated improved recognition accuracy by combining graph-based feature modeling with convolutional neural networks. However, the system relied heavily on controlled image acquisition and focused only on muzzle-based recognition, limiting its adaptability to full-body classification. This work supports the importance of structured feature extraction in livestock recognition but highlights the need for a more generalized and scalable image-based breed classification system, which our project addresses using full-image transfer learning.

2.2 A Vision-Based Cattle Recognition System Using TensorFlow

[2] A. Biglari and W. Tang (2022). Biglari and Tang developed a TensorFlow-based vision system for cattle recognition aimed at livestock water intake monitoring. Their method employed convolutional neural networks to identify individual cattle in farm environments, enabling automated behavioral tracking. The system demonstrated effective monitoring performance under real-time conditions. However, the research primarily focused on individual cattle recognition rather than breed classification. Additionally, the system was application-specific and did not emphasize multi-class fine-grained breed categorization. Their work demonstrates the practical use of deep learning in livestock management but reveals a research gap in indigenous breed identification, which our project attempts to address.

2.3 Contour Extraction of Individual Cattle Using Enhanced Mask R-CNN

[3] R.-W. Bello, A. S. A. Mohamed and A. Z. Talib (2021). Bello et al. introduced an enhanced Mask R-CNN-based instance segmentation model for extracting cattle contours from images. The proposed approach improved object segmentation accuracy, enabling precise cattle identification even in complex backgrounds. While segmentation enhances object isolation, it increases computational complexity and training requirements. Furthermore, the focus remained on contour detection rather than breed-level classification. This study highlights the importance of accurate feature extraction but also emphasizes the need for lightweight classification systems suitable for real-time web deployment, as implemented in our project using DenseNet121.

2.4 A Comprehensive Analysis of Classic Machine Learning and Deep Learning Modeling for Breed Recognition

[4] M. A. Rahman et al. (2025). Rahman et al. presented a comparative study between classical machine learning algorithms and deep learning models for breed recognition tasks. Their research evaluated methods such as Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), and

Random Forest alongside Convolutional Neural Networks (CNNs). The study demonstrated that deep learning models significantly outperform traditional machine learning approaches in terms of accuracy, robustness, and generalization capability. The authors emphasized the importance of automated feature extraction in CNN architectures compared to handcrafted features required in classical methods. However, the research required extensive computational resources and large datasets to achieve optimal performance. Additionally, the study did not focus specifically on indigenous cattle breeds or real-time deployment. This comparative analysis supports the decision in our project to adopt transfer learning using DenseNet121, as deep learning provides superior feature extraction and classification accuracy. It also reinforces the need for optimized architectures that balance performance and computational efficiency for practical web-based implementation.

2.5 Cattle Breed Detection and Categorization Using Image Processing and Machine Learning

[5] N. R. Duraiswami et al. (2022). Duraiswami et al. proposed a cattle breed detection system based on traditional image processing techniques combined with machine learning classifiers. Their methodology involved preprocessing steps such as edge detection, color histogram analysis, and texture feature extraction, followed by classification using supervised learning algorithms. The study achieved moderate accuracy levels and demonstrated the feasibility of automated cattle breed detection. However, the reliance on manual feature extraction limited scalability and adaptability to diverse environmental conditions. Variations in lighting, background noise, and animal pose significantly affected performance. Furthermore, the system required feature engineering expertise, making it less flexible compared to deep learning-based approaches. This research highlights the limitations of conventional machine learning techniques in handling complex visual patterns. In contrast, our proposed system leverages transfer learning with DenseNet121, which automatically extracts hierarchical features from images and improves classification robustness, thereby overcoming the challenges associated with handcrafted feature dependency.

2.6 Identification of Cattle's Breed Type Using Deep Learning Models

[6] C. Bhanuprakash and V. N. V. (2024). Bhanuprakash and V. N. V. developed a deep learning-based approach for identifying cattle breed types using convolutional neural network models. Their study evaluated different CNN architectures and demonstrated that transfer learning significantly improves classification accuracy, especially when working with limited datasets. The authors emphasized preprocessing techniques such as resizing, normalization, and augmentation to enhance generalization capability. While the proposed method achieved promising results, the study lacked deployment considerations and focused primarily on model accuracy evaluation. Additionally, computational requirements were relatively high due to model complexity. Their findings strongly support the methodological foundation of our project, particularly the use of transfer learning for fine-grained breed classification. However, our system extends beyond model development by incorporating a Streamlit-based web interface, enabling real-time breed prediction and practical usability for farmers and researchers.

2.7 Dog Breed Detection Using YOLOv7 and WOA-CNN

[7] R. Singh, R. Kothari and V. Arulalan (2024). Singh et al. proposed a hybrid approach combining YOLOv7 object detection with Whale Optimization Algorithm-based CNN (WOA-CNN) for dog breed detection. Their system first detected the dog region using YOLOv7 and then classified the detected object using an optimized CNN model. The integration of evolutionary optimization improved classification accuracy and convergence speed. The study demonstrated strong performance in object localization and multi-class classification under varied backgrounds. However, YOLO-based frameworks primarily focus on detection rather than fine-grained breed classification. Additionally, optimization algorithms increase computational overhead and complexity. The work emphasizes the importance of combining detection and classification pipelines but may not be suitable for lightweight web deployment. In comparison, our project focuses directly on image-level breed classification using transfer learning without requiring separate detection stages, thereby reducing computational load while maintaining high accuracy.

2.8 Cow Face Recognition with Vision Transformer

[8] H. Zhao et al. (2023). Zhao et al. introduced a Vision Transformer-based model for cow face recognition under noisy labeling conditions. Their research leveraged self-attention mechanisms to capture global contextual features across images, improving recognition accuracy even with imperfect training data. The model demonstrated robustness in handling variations in pose and lighting. However, Vision Transformers require large-scale datasets and high computational resources for optimal performance. The system was primarily designed for individual cow identification rather than breed classification. Moreover, transformer architectures are resource-intensive, making real-time deployment challenging in low-resource agricultural settings. This study highlights the effectiveness of advanced attention-based models but also reinforces the need for computationally efficient alternatives. Our project adopts DenseNet121, which balances performance and efficiency, making it suitable for deployment via Streamlit in real-world farm environments.

2.9 Multi-View Cattle Facial Recognition Based on Feature Matching

[9] Z. Zheng et al. (2025). Zheng et al. proposed a multi-view cattle facial recognition algorithm based on feature matching techniques. Their approach extracted discriminative features from multiple camera angles to enhance recognition reliability. The multi-view strategy improved robustness against pose variations and occlusions. While effective, the system required multiple camera inputs and complex feature alignment processes. This increases infrastructure cost and implementation complexity. Furthermore, the method focused on facial identification rather than breed-level classification. The study demonstrates that multi-view analysis enhances recognition accuracy but may not be practical for small-scale farmers lacking advanced imaging setups. In contrast, our system requires only a single image input and performs classification efficiently using transfer learning, making it more accessible and scalable.

2.10 Video-Based Analysis of Cattle Behaviors Using FlowEQ Transform

[10] J.-W. Chae et al. (2024). Chae et al. developed a video-based cattle behavior analysis system using FlowEQ Transform for improved classification. Their approach analyzed motion patterns and behavioral cues from video sequences to classify cattle activities. The system demonstrated high temporal analysis capability and improved accuracy compared to static image methods. However, video-based systems demand large storage capacity, higher computational power, and continuous monitoring infrastructure. The research primarily focused on behavior analysis rather than breed identification. Although dynamic analysis provides richer information, it may not be necessary for static breed classification tasks. Our project simplifies implementation by utilizing still image classification, reducing system complexity while maintaining effectiveness in breed recognition.

2.11 Automatic Cattle Identification Based on Texture Feature Fusion

[11] W. Kusakunniran et al. (2018). Kusakunniran et al. proposed an automatic cattle identification system using fusion of texture features extracted from muzzle images. Their method combined Local Binary Patterns (LBP) and other handcrafted descriptors for recognition. The approach achieved efficient performance with lower computational requirements compared to deep learning methods. However, texture-based handcrafted features are sensitive to illumination changes and image noise. Additionally, manual feature engineering limits adaptability across diverse datasets. The study highlights early advancements in cattle recognition but demonstrates limitations compared to modern deep CNN architectures. Our system improves upon this by employing DenseNet121 for automatic hierarchical feature extraction, eliminating dependence on manual texture descriptors.

2.12 Automatic Cattle Identification Using Multi-Channel LBP

[12] W. Kusakunniran and T. Chaiviroonjaroe (2018). This study introduced a multi-channel Local Binary Pattern approach for cattle identification using muzzle images. The authors aimed to enhance recognition accuracy by analyzing texture information across different channels. While computationally efficient, the approach struggled under variations in lighting and occlusion. The research emphasized cost-effective implementation but lacked scalability for multi-breed classification. Compared to deep learning models, LBP-based techniques provide limited discriminative power. This supports the transition toward CNN-based architectures in modern livestock recognition systems, as implemented in our project.

2.13 Identification of Different Types of Buffalo Using YOLO

[13] J. R. Butu et al. (2023). Butu et al. proposed a YOLO-based computer vision system for buffalo type identification. The system demonstrated strong detection accuracy and real-time performance. However, YOLO primarily focuses on object detection rather than fine-grained classification. Additionally, breed-level differentiation may require deeper feature extraction than bounding-box detection provides. This study supports future integration of buffalo classification in our system but highlights the need for specialized classification networks like DenseNet121.

2.14 Hybrid Deep Learning Framework for Cattle Identification

[14] V. S. P. Gunda et al. (2022). Gunda et al. introduced a hybrid deep learning framework combining multiple CNN architectures for robust cattle identification. Their ensemble approach improved classification accuracy but increased model complexity and computational cost. The research emphasized robustness but lacked lightweight deployment considerations. Our project balances accuracy and efficiency by using a single optimized DenseNet121 model

2.15 Identifying the Optimal Deep Learning Based Image Recognition Technique for Dog Breed Detection

[15] S. C. Iyer and N. M. Shekokar (2023). Iyer and Shekokar conducted a comparative analysis to determine the most effective deep learning architecture for dog breed detection. Their study evaluated multiple convolutional neural network models, including VGG, ResNet, and Inception architectures, analyzing performance metrics such as accuracy, precision, recall, and computational efficiency. The authors demonstrated that transfer learning significantly enhances classification performance, especially when working with limited training datasets. Their results indicated that deeper architectures generally yield higher accuracy but require greater computational resources. The study emphasized the importance of selecting an optimal architecture that balances accuracy and efficiency. However, the research was limited to dog breeds and did not explore livestock-specific challenges such as environmental variability or indigenous breed similarity. Additionally, deployment aspects were not addressed. This comparative evaluation strongly supports our methodological choice of DenseNet121, as it provides high accuracy with efficient feature reuse while maintaining manageable computational requirements suitable for real-time Streamlit-based deployment.

2.16 Literature survey of all the papers

Table 2.1 Literature Survey of all Papers

Author(s) & Year	Title / Focus	Key Contributions	Limitations
Chakraborty et al. (2021)	Pig Breed Classification using Graph Synthesis	Introduced graph-based feature modeling for muzzle images; improved structured representation of livestock features	Limited to muzzle images; requires controlled environment
Biglari & Tang (2022)	Vision-Based Cattle Recognition	Applied CNN for livestock monitoring using TensorFlow; real-time cattle tracking	Focused on individual recognition, not breed classification
Bello et al. (2021)	Enhanced Mask R-CNN for Cattle Contour Extraction	Improved instance segmentation accuracy in complex backgrounds	High computational complexity; not focused on breed-level classification

Rahman et al. (2025)	ML vs DL Comparative Study for Breed Recognition	Demonstrated superiority of deep learning over classical ML techniques	Requires large dataset and high computational power
Duraiswami et al. (2022)	Cattle Breed Detection using ML	Applied image processing + supervised learning; feasible automation	Manual feature extraction; sensitive to lighting and noise
Bhanuprakash & V.N.V. (2024)	Deep Learning for Cattle Breed Identification	Showed effectiveness of transfer learning in classification	Lacked deployment and real-time usability
Singh et al. (2024)	Dog Breed Detection using YOLOv7 + WOA-CNN	Combined object detection with optimized CNN; high accuracy	Increased computational overhead; complex architecture
Zhao et al. (2023)	Cow Face Recognition using Vision Transformer	Used self-attention for robust recognition under noisy labels	Requires large datasets; high computational demand
Zheng et al. (2025)	Multi-View Cattle Facial Recognition	Improved robustness using multi-angle feature matching	Requires multi-camera setup; infrastructure-heavy
Chae et al. (2024)	Video-Based Cattle Behavior Analysis	Used motion-based video analysis; strong temporal recognition	High storage and processing requirements; not breed-focused
Kusakunniran et al. (2018)	Texture Feature Fusion for Cattle Identification	Used handcrafted texture descriptors; computationally efficient	Sensitive to illumination; limited scalability
Kusakunniran & Chaiviroonjaroe (2018)	Multi-Channel LBP for Cattle Identification	Improved texture-based recognition using multi-channel features	Less robust than CNN-based approaches
Butu et al. (2023)	Buffalo Identification using YOLO	Real-time buffalo detection using object detection model	Primarily detection-based; limited fine-grained classification
Gunda et al. (2022)	Hybrid Deep Learning Framework for Cattle	Combined multiple CNN models for improved accuracy	High architectural complexity; heavy computation
Iyer & Shekokar (2023)	Comparative Study of DL Models for Dog Breed Detection	Evaluated multiple CNN architectures; emphasized transfer learning	Limited to dogs; no deployment consideration

Chapter 3
Methodology

The main idea of this project is to design and implement an image-based livestock breed classification system that enables automatic identification of indigenous Indian cow breeds using deep learning techniques. The system integrates image preprocessing, transfer learning-based classification, and web deployment to provide a unified platform where users can upload cow images and receive accurate breed predictions from a single interface.

This process begins from the **User Interface Module**, where users access the web application developed using Streamlit. The user uploads an image of a cow through the upload section. Once the image is submitted, the input control module handles the uploaded image and forwards it to the preprocessing module.

The **Preprocessing Module** resizes the image to 224×224 pixels, converts it into RGB format, and normalizes pixel values between 0 and 1. These steps ensure uniformity and compatibility with the DenseNet121 model architecture. After preprocessing, the processed image tensor is passed to the trained deep learning model.

The project's classification model is implemented using a transfer learning approach based on DenseNet121 architecture. The pretrained model extracts hierarchical features from the image such as texture, shape, body structure, and color distribution. Only the final layers of the model are fine-tuned to adapt to the 17 indigenous Indian cow breeds included in the dataset.

To improve the model's performance and generalization ability, the following data augmentation techniques are applied during training:

- Rotation of images up to 20 degrees
- Zoom transformation
- Horizontal flipping
- Pixel rescaling

The ranking or prediction confidence of the system is determined using the softmax activation function in the final dense layer. The output probabilities represent the likelihood of the image belonging to each of the 17 breeds. The breed with the highest probability is selected as the final predicted class.

The system categorizes prediction confidence into three levels:

- High Confidence (≥ 80%)
- Moderate Confidence (60%–79%)
- Low Confidence (< 60%)

This helps users understand the reliability of the prediction result.

Once prediction is completed, the result display module presents:

- Predicted Breed Name
- Confidence Percentage
- Confidence Level Indicator

To enhance user experience, a loading spinner is integrated into the interface, which displays an animated processing indicator while the model is analyzing the image. This ensures smooth interaction and responsive user experience.



Fig 3.1 Methodology

- **The Data Preprocessing Module** handles the initial ingestion of the dataset through a **Dataset Upload (.ZIP File)**. Once uploaded, the **Data Extraction & Organization** component unzips the files into specific **Breed Folders**. To ensure the model can generalize effectively, the system performs **Normalization** and **Data Augmentation**—applying transformations like **Flip, Rotate, and Zoom** which mathematically expands the variety of the training data.
- **The Feature Extraction Layer** utilizes a **Pretrained DenseNet121** architecture. By using a pretrained model, the system leverages "transfer learning," where the network uses previously learned visual patterns to identify complex features in the breed images without

needing to be trained from scratch. This extracted data is then passed to the **Model Training** component.

- **The Model Training and Optimization Phase** is governed by the **Adam Optimizer** and **Cross-Entropy Loss** function. These algorithms iteratively adjust the model's internal weights to minimize error. Once training is complete, the resulting "brain" of the system is exported as an **.h5 File** in the **Model Saving** stage for future deployment.
- **The Performance Evaluation and Inference Module** validates the system's effectiveness using metrics such as **Accuracy**, **Loss Curves**, and **Confusion Matrices**. This ensures the model is not just memorizing data but actually learning. Once verified, the system moves to the **Prediction** stage, where it accepts a **New Image** and outputs a final **Breed Classification** to the user.

Chapter-4
Project Management

4.1 Project Timeline.



Fig 4.1 Project Timeline

- Review 1: Problem Identification and Title Confirmation.
- Review 2: Literature Survey and Data Collection.
- Review 3: Demonstrated the 50% working of the project where the front-end design was completed.
- Review 4: Demonstrated the 100% working of the project with all working functionalities of the frontend and the backend.
- Final Review: Viva, Report Submission and Research Paper publication.

4.2 Risk Analysis

- There was a risk of incorrect breed prediction due to limited or imbalanced dataset. To overcome this: Data augmentation and transfer learning using DenseNet121 were applied to improve accuracy and generalization.

- The model may overfit the training data. To overcome this: EarlyStopping and Dropout layers were used to prevent overfitting and ensure better validation performance.

- Variations in lighting, background, or image quality may affect prediction results. To overcome this: Image preprocessing and normalization techniques were implemented to maintain input consistency.

- High computational cost during training may delay development. To overcome this: Transfer learning was used instead of training from scratch to reduce training time.

- Incorrect or low-quality uploaded images may produce unreliable results. To overcome this: Input validation and confidence level display (High/Moderate/Low) were added in the Streamlit interface.

Chapter 5
Analysis and Design

5.1 Problem Analysis

The conventional method of cattle breed identification is manual, subjective, and often inconsistent. Farmers, veterinarians, and livestock researchers rely on physical observation of features such as body size, coat color, horn shape, and facial structure to determine the breed. This process requires domain expertise and practical experience. However, many indigenous Indian cow breeds share very similar visual characteristics, making accurate identification difficult.

The current manual approach results in:

- Human Error: Visual similarities between breeds may lead to misclassification.
- Inefficiency: Manual verification consumes time and requires expert involvement.
- Limited Accessibility: Rural farmers may not have easy access to breed experts.
- Inconsistent Judgement: Identification may vary from one expert to another.
- Lack of Automation: No widely accessible real-time web-based system for Indian cow breed classification.

Although computer vision techniques have been applied in livestock monitoring, most existing systems focus on animal detection or individual recognition rather than fine-grained breed classification. Traditional machine learning approaches depend on handcrafted features, which are sensitive to lighting, background variations, and pose differences.

Key Issues Identified:

- Difficulty in distinguishing visually similar indigenous breeds.
- Absence of automated breed classification system for Indian livestock.
- Limited real-time, user-friendly web deployment solutions.
- Need for scalable system that can include buffalo breeds in future.

The proposed deep learning-based livestock classification system addresses these challenges by providing an integrated, intelligent, and web-accessible solution for accurate breed prediction.

5.2 Requirement Analysis

The system requirements were classified into functional and non-functional categories.

- Functional Requirements

Table 5.1 Functional Requirements

ID	Requirement	Description
FR1	Image Upload	The system shall allow users to upload cow images in JPG, JPEG, or PNG format.
FR2	Image Preprocessing	The system shall resize and normalize the uploaded image to 224×224 pixels before prediction.
FR3	Breed Classification	The system shall classify the uploaded image into one of the 17 indigenous cow breeds using the trained model.
FR4	Confidence Display	The system shall display the predicted breed along with confidence percentage.
FR5	Confidence Level Indicator	The system shall categorize prediction confidence as High, Moderate, or Low.
FR6	Model Loading	The system shall load the trained DenseNet121 model (.h5 file) during application startup.
FR7	Real-Time Prediction	The system shall provide prediction results immediately after user uploads an image.
FR8	Error Handling	The system shall display error messages if invalid images are uploaded or if the model fails to load.
FR9	Display Recognized Breeds	The system shall display the list of supported cow breeds in the application interface.
FR10	Local Deployment	The system shall run locally using the command `streamlit run app.py`.

- **Non-Functional Requirements**

Table 5.2 Non- Functional Requirements.

Parameter	Requirement Description
Performance	The system should provide fast breed prediction results within a few seconds.
Accuracy	The model should ensure high and consistent classification accuracy.
Usability	The application should offer a simple and user-friendly Streamlit interface.
Scalability	The system should support future addition of new cattle and buffalo breeds.
Reliability	The system should execute stably without crashes and handle errors properly.
Maintainability	The code structure should be modular for easy updates and improvements.
Portability	The application should run on different systems supporting Python and required libraries.
Security	User-uploaded images should not be permanently stored to ensure data privacy.
Efficiency	The system should optimize computational resources for smooth performance.
Robustness	The system should handle invalid or low-quality image inputs gracefully.

5.3 System Design

The system design comprises of two parts

- Data Processing and model Training.
- User Interface.

5.3.1 Data Processing and Model Training



Figure 5.1 Data Processing and Model Training

5.3.2 User Interface



Figure 5.2 User Interface

5.3.3 Tools and Technologies

1. Programming Language-Python
Python was used as the primary programming language for the development of the system. It provides extensive support for machine learning and deep learning through well-established libraries and frameworks. Its simplicity, readability, and large community support make it suitable for rapid development and experimentation.

2. Deep Learning Framework-TensorFlow
TensorFlow was used as the core deep learning framework for building and training the neural network model. It provides efficient computation, GPU acceleration support, and scalable model deployment capabilities.
Keras (TensorFlow Keras API)
Keras was used as a high-level API within TensorFlow to design and implement the neural network architecture. It simplifies model creation, training, and evaluation through user-friendly functions and modular components.

3. Pretrained Model Architecture-DenseNet121
DenseNet121 was used as the base Convolutional Neural Network architecture. It is a densely connected CNN model pretrained on ImageNet. Transfer learning was applied by freezing initial layers and fine-tuning the last layers to adapt the model for indigenous cow breed classification.

4. Data Preprocessing and Augmentation-ImageDataGenerator
The ImageDataGenerator utility from Keras was used for preprocessing and augmenting the dataset. The following operations were applied:

- Image rescaling (normalization using 1/255)
- Rotation
- Zooming
- Horizontal flipping
- Automatic training and validation split (80:20)

These techniques improve model generalization and reduce overfitting.
NumPy
NumPy was used for numerical operations and array manipulations during preprocessing and model prediction.

5. Optimization and Training Techniques
The following techniques were used during model training:

- Adam Optimizer – Used for efficient weight updates and faster convergence.
- Categorical Crossentropy Loss Function – Used to calculate classification error for multi-class prediction.
- EarlyStopping Callback – Used to prevent overfitting by stopping training when validation loss stops improving.
- ModelCheckpoint Callback – Used to save the best-performing model during training.

6. Model Deployment Framework-Streamlit
Streamlit was used to develop the web-based user interface for the system. It allows users to upload cow images and receive real-time breed predictions along with confidence scores. Streamlit enables quick deployment of machine learning models without complex web development.

7. Development Environment

- Visual Studio Code (Code Editor)

- Google Colab (if used for training)
- Windows Operating System

8. File Formats Used
   - .h5 – Trained model file
   - .json – Stored class labels
   - .jpg, .png – Input image format

5.4 Summary

- This chapter presented a comprehensive analysis and structured design of the proposed Cattle and Buffalo Breed Classification System. The problem analysis identified the challenges associated with traditional manual breed identification methods, including visual similarity among breeds, dependency on expert knowledge, and the possibility of human error. These challenges justified the need for an automated, intelligent, and image-based classification system capable of delivering accurate and consistent results.
- Based on the problem analysis, detailed requirement analysis was carried out. Functional requirements defined the core operations of the system such as image upload, preprocessing, breed prediction, confidence score generation, and result display. Non-functional requirements addressed critical quality attributes including performance efficiency, classification accuracy, usability, scalability, reliability, maintainability, portability, and data security. These requirements ensure that the system not only performs its intended tasks but also maintains high standards of quality and robustness.
- The system design was developed using a modular and layered architecture approach. The design clearly separates the user interface, backend processing logic, image preprocessing module, and deep learning classification model. A high-level architecture and block diagram were formulated to represent the interaction between components, starting from user input to final prediction output. The adoption of transfer learning with a DenseNet-based model ensures improved accuracy while reducing computational complexity and training time.
- Overall, this chapter establishes a strong analytical and architectural foundation for the system. The structured design ensures flexibility, extensibility, and ease of future enhancements, such as the integration of additional cattle and buffalo breeds, performance optimization, and deployment in real-world agricultural environments. The next chapter builds upon this foundation by describing the detailed software implementation of the proposed system.

Chapter 6
Software Implementation

6.1 Overview

The software implementation phase focuses on transforming the proposed cattle and buffalo breed classification system from design into a functional application. The system is developed using Python as the core programming language due to its strong support for machine learning, image processing, and web application frameworks.

The deep learning model is implemented using TensorFlow and Keras libraries. A pre-trained Convolutional Neural Network (CNN) architecture based on transfer learning is used to classify livestock breeds from input images. The model is trained on a curated dataset of cattle breeds, and the trained model is saved in .h5 format for deployment.

6.2 Software and Tools Used

Table 6.1 Software and Tools Used

Category	Tools / Technology	Purpose
Programming Language	Python	Core language used for implementing model training and deployment.
Deep Learning Framework	TensorFlow	Used for building and training the Convolutional Neural Network model.
Deep Learning API	Keras	Used for implementing transfer learning and model architecture.
Data Processing	NumPy	Used for numerical computations and array manipulations.
Data Handling	Pandas	Used for dataset organization and preprocessing.
Image Processing	OpenCV	Used for image resizing, normalization, and preprocessing.
Visualization	Matplotlib	Used to plot training and validation accuracy/loss graphs.
Web Framework	Streamlit	Used to develop and deploy the interactive web application.
Development Environment	VS Code	Used for coding, debugging, and project management.
Cloud Platform	Google Colab	Used for GPU-based model training.
Version Control	Git	Used for source code management and version tracking.
Model Storage	H5 (.h5 file)	Stores the trained deep learning model for deployment.

6.3 Database Implementation

The proposed system does not use a traditional relational database such as MySQL or PostgreSQL. Instead, the implementation relies on structured dataset folders and metadata files for managing breed information.

The livestock image dataset is organized into labeled directories, where each folder represents a specific breed. This folder-based structure acts as a lightweight database for training the deep learning model. During preprocessing, images are loaded dynamically, resized, normalized, and converted into numerical arrays for model training.

The breed class names are stored in a JSON file, which maps prediction indices to breed names. This ensures consistent output interpretation during deployment. The trained model is saved in .h5 format and loaded during runtime for prediction.

This simplified database implementation ensures:

- Efficient dataset management
- Easy addition of new breeds
- Minimal storage overhead
- Fast access during training and inference

6.4 Backend Implementation

The backend of the system is implemented using Python along with TensorFlow and Keras libraries.

The backend performs the following operations:

1. Loading the trained CNN model.
2. Accepting image input from the frontend.
3. Preprocessing the image (resize, normalize, reshape).
4. Passing the image to the trained model.
5. Generating prediction probabilities.
6. Returning the predicted breed with confidence score.

The backend logic is structured inside the app.py file. The model file is loaded only once when the application starts, improving performance and reducing repeated memory allocation.

Key Backend Features

- Transfer learning-based CNN model
- Real-time prediction

- Confidence score calculation
- Error handling for invalid uploads
- Lightweight and fast execution

6.5 Frontend Implementation

The frontend of the system is developed using Streamlit, a Python-based web application framework.

After completing training, the application is launched using:

streamlit run app.py

This command starts a local host server, and the web interface automatically opens in the browser. Users can upload livestock images through a file uploader widget.

Key Frontend Features

- Image upload option
- Image preview display
- Predicted breed display
- Confidence score visualization
- Clean and minimal interface
- Instant result generation

The Streamlit interface ensures that farmers, researchers, and students can use the system easily without technical knowledge.

6.6 Integration and Workflow

The system follows an integrated workflow combining frontend, backend, and trained model components.

Workflow Steps:

1. User uploads livestock image through Streamlit interface.
2. Image is sent to backend processing module.
3. Backend preprocesses the image.
4. Preprocessed image is passed to the trained CNN model.
5. Model generates prediction probabilities.
6. Highest probability breed is selected.

7. Result with confidence score is displayed on the frontend.

The integration ensures seamless communication between:

- User Interface
- Preprocessing Module
- Trained Model
- Prediction Output Module

This architecture ensures smooth execution and real-time classification.

6.7 Simulation Workflow

The simulation workflow describes how the system operates during testing and demonstration.

Simulation Process:

1. Train the CNN model using livestock dataset.
2. Save the trained model in .h5 format.
3. Run the Streamlit application using:

streamlit run app.py

4. Local host server launches automatically.
5. Upload test image of cattle or buffalo.
6. System processes image and displays predicted breed.
7. Verify prediction accuracy against known breed.

This simulation validates:

- Model accuracy
- Real-time response
- System stability
- User interaction experience

The simulation demonstrates that the proposed system effectively performs automated livestock breed classification using deep learning and web deployment.

Chapter 7
Evaluation and Results

7.1 Functional Evaluation

The functional evaluation verifies whether the implemented cattle and buffalo breed classification system performs according to the specified functional requirements. The system was tested using multiple livestock images across different breeds to validate prediction accuracy, response time, and user interaction.

Table 7.1 Functional Evaluation

Feature	Expected Output	Observed Result
Image Upload	User should be able to upload cattle/buffalo image successfully.	Images uploaded successfully without errors.
Image Preview	Uploaded image should be displayed on the interface.	Image preview displayed correctly before prediction.
Breed Prediction	System should predict the correct livestock breed.	Correct breed predicted for majority of test cases.
Confidence Score	System should display prediction confidence percentage.	Confidence score displayed along with predicted breed.
Invalid File Handling	System should reject unsupported file formats.	Invalid formats handled without crashing.
Low-Quality Image Handling	System should still attempt prediction for unclear images.	Prediction generated with lower confidence score.
Model Loading	Model should load once during app startup.	Model loaded successfully without repeated initialization.
Response Time	Prediction should be generated within few seconds.	Results displayed within acceptable time range.
Local Deployment	Application should run on localhost using Streamlit.	App successfully launched using `streamlit run app.py`.
System Stability	Application should not crash during repeated testing.	System remained stable during multiple trials.

7.2 Usability Evaluation

The usability evaluation measures how easily users can interact with the system and obtain results.

Table 7.2 Usability Evaluation

Parameter	**Average Time**	**Results**
Application Startup	3–5 seconds	Application launched successfully on localhost using Streamlit.
Image Upload	2–4 seconds	Users were able to upload images without difficulty.
Image Preview Display	1–2 seconds	Uploaded image displayed clearly before prediction.
Prediction Display	2–3 seconds	Predicted breed and confidence score shown clearly.
Error Message Display	Instant	Invalid inputs handled with proper warning messages.

The evaluation indicates that the system is simple, interactive, and user-friendly.

7.3 Performance Evaluation

The performance evaluation measures system efficiency and response time during execution.

Table 7.3 Performance Evaluation

Parameter	**Average Time**	**Results**
Model Loading	4–6 seconds	Model loaded successfully during application startup.
Image Preprocessing	1–2 seconds	Image resized and normalized efficiently.
Breed Prediction	2–4 seconds	Prediction generated accurately within acceptable time.
Total Processing Time	5–8 seconds	Complete workflow executed smoothly.
Continuous Testing	Consistent	No lag or performance degradation observed.

The system demonstrates stable and efficient performance under repeated testing conditions.

7.4 Security and Reliability Testing

Security and reliability testing ensure that the application operates safely and consistently.

Security Testing

- Uploaded images are not permanently stored.
- No personal user data is collected.
- Application runs locally, reducing external threats.
- Unsupported file formats are restricted.

Reliability Testing

- Multiple breed images tested successfully.
- Application remained stable during repeated predictions.
- Low-quality images were handled without system crashes.
- Error handling mechanisms ensured smooth execution.

The testing confirms that the system is secure, reliable, and stable for practical deployment.

7.5 Results

1.Dataset Structure



Amritmahal	21-01-2026 23:59	File folder
Bargur	02-02-2026 10:06	File folder
Dangi	05-02-2026 14:11	File folder
Deoni	05-02-2026 14:13	File folder
Gaolao	05-02-2026 14:12	File folder
Gir	17-01-2026 23:28	File folder
Hallikar	02-02-2026 10:36	File folder
Hariana	05-02-2026 14:12	File folder

Figure 7.1 Dataset Structure

The dataset is formed by creating multiple folders for multiple breeds and these folders are named by the breed's name and one all the images for different breeds are collected, all these folders are added into a main folder and the main folder is named as dataset. The file is then compressed into a .zip file format.

2. Stage 1 training the model.

```
Starting Stage 1: Training the Classifier Head...
/usr/local/lib/python3.12/dist-packages/keras/src/trainers/data_adapters/py_dataset_adapter.py:121: UserWarning: Your `PyDataset` class should call `super().__init__(**kwargs)` in
  self._warn_if_super_not_called()
Epoch 1/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 40s 1s/step - accuracy: 0.1075 - loss: 3.0525
Epoch 2/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 16s 203ms/step - accuracy: 0.2568 - loss: 2.2354
Epoch 3/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 206ms/step - accuracy: 0.3693 - loss: 1.8272
Epoch 4/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 202ms/step - accuracy: 0.4937 - loss: 1.4925
Epoch 5/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 4s 255ms/step - accuracy: 0.5390 - loss: 1.3016
Epoch 6/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 205ms/step - accuracy: 0.5939 - loss: 1.2384
Epoch 7/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 207ms/step - accuracy: 0.6158 - loss: 1.1680
Epoch 8/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 222ms/step - accuracy: 0.5795 - loss: 1.1150
Epoch 9/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 4s 239ms/step - accuracy: 0.6393 - loss: 1.0361
Epoch 10/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 204ms/step - accuracy: 0.6792 - loss: 0.9093
Epoch 11/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 202ms/step - accuracy: 0.6935 - loss: 0.9161
Epoch 12/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 243ms/step - accuracy: 0.7673 - loss: 0.6786
Epoch 13/20
...
Epoch 19/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 3s 207ms/step - accuracy: 0.7946 - loss: 0.5997
Epoch 20/20
14/14 ━━━━━━━━━━━━━━━━━━━━ 4s 265ms/step - accuracy: 0.7874 - loss: 0.6140
```

Figure 7.2 Stage 1 Training the model

In the first stage, the pretrained DenseNet121 model was loaded with ImageNet weights, and all the convolutional base layers were frozen. Only the newly added classification layers (Global Average Pooling, Dropout, and final Softmax layer) were trained on the cow breed dataset. This stage allows the model to adapt the high-level features already learned from ImageNet to the specific task of indigenous cow breed classification, without altering the pretrained feature extraction layers. It ensures stable learning and prevents sudden distortion of pretrained weights.

3. Stage 2 Fine Tuning the model.

```
Starting Stage 2: Fine-Tuning the Model...
/usr/local/lib/python3.12/dist-packages/keras/src/trainers/data_adapters/py_dataset_adapter.py:121: UserWarning: Your `PyDataset` class should call `super().__init__(**kwargs)` in
  self._warn_if_super_not_called()
Epoch 1/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 53s 789ms/step - accuracy: 0.0479 - loss: 4.1008
Epoch 2/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 198ms/step - accuracy: 0.0281 - loss: 4.0349
Epoch 3/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 223ms/step - accuracy: 0.0403 - loss: 3.9345
Epoch 4/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 199ms/step - accuracy: 0.0417 - loss: 3.8211
Epoch 5/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 229ms/step - accuracy: 0.0355 - loss: 3.7223
Epoch 6/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 199ms/step - accuracy: 0.0307 - loss: 3.7858
Epoch 7/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 226ms/step - accuracy: 0.0357 - loss: 3.6731
Epoch 8/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 198ms/step - accuracy: 0.0512 - loss: 3.5625
Epoch 9/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 227ms/step - accuracy: 0.0691 - loss: 3.5912
Epoch 10/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 197ms/step - accuracy: 0.0645 - loss: 3.6414
Epoch 11/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 227ms/step - accuracy: 0.0255 - loss: 3.6028
Epoch 12/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 196ms/step - accuracy: 0.0810 - loss: 3.4413
Epoch 13/15
...
Epoch 14/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 6s 199ms/step - accuracy: 0.0448 - loss: 3.5101
Epoch 15/15
29/29 ━━━━━━━━━━━━━━━━━━━━ 7s 229ms/step - accuracy: 0.0654 - loss: 3.3476
Output is truncated. View as a scrollable element or open in a text editor. Adjust cell output settings...
```

Figure 7.3 Fine Tuning the model

In the second stage, the last few layers of the DenseNet121 base model were unfrozen and trained along with the classifier layers using a small learning rate. This fine-tuning step allows the network to slightly adjust deeper feature representations to better capture breed-specific

characteristics such as horn shape, coat texture, color patterns, and body structure. As a result, the model becomes more specialized for the target dataset, leading to improved accuracy and better generalization performance.

4. Executing the app.py

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL    PORTS

PS C:\Users\adity\OneDrive\Desktop\SEM 8\Review 3\code> streamlit run app.py

  You can now view your Streamlit app in your browser.

  Local URL: http://localhost:8501
  Network URL: http://10.94.215.99:8501
```

Figure 7.4 Executing the app.py

After completing the training process and saving the trained model as indian_livestock_model.h5, the system was deployed using Streamlit to create a web-based interface. The application is executed using the command streamlit run app.py, which launches a local server and hosts the application on the local machine (typically at http://localhost:8501). When the application starts, the trained model is loaded into memory. Users can then upload an image of a cow through the interface, after which the image is resized, normalized, and passed to the trained model for prediction. The system processes the image and displays the predicted cow breed along with the corresponding confidence score in real time.

5. Home Page.



Figure 7.5 Home Page

When the application is launched using Streamlit and opened in the local host, the main page displays a clear and user-friendly interface for cow breed classification. The homepage presents the system title and a brief description of the project, indicating that it is an AI-based indigenous cow breed recognition system. The user is provided with an image upload option where they can select and upload a cow image in formats such as JPG or PNG. Once an image is uploaded, it is previewed on the screen, and a prediction button is available to initiate the classification process. After processing, the predicted breed name and confidence percentage are displayed prominently. Additionally, a separate tab provides model information, including the architecture used, input size, and total number of supported breeds. This structured layout ensures ease of use and enables real-time interaction with the trained model.

6.Model Info



Figure 7.6 Model Info

The Model Info tab provides detailed information about the underlying deep learning model

used in the system. It describes that the classification model is based on DenseNet121 and implemented using transfer learning. The tab specifies important technical details such as the input image size (224×224 pixels), the use of a Softmax activation function for multi-class classification, and the total number of supported cow breeds. It also highlights that the model was trained using TensorFlow and Keras frameworks. In addition, the tab displays the list of recognized indigenous cow breeds, allowing users to understand the scope and capabilities of the classification system.

7.Breed Prediction-Hallikar.



Figure 7.7 Breed Prediction – Hallikar.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

8.Breed Prediction-Gir.



Figure 7.8 Breed Prediction-Gir.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

9.Breed Prediction-Bargur.



Figure 7. 9 Breed Prediction-Bargur.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

10.Breed Prediction-Kankrej.



Figure 7.10.Breed Prediction-Kankrej.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

11.Breed Prediction-Rathi



Figure 7.11 Breed Prediction-Rathi

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

12.Breed Prediction-Punganur.



Figure 7.12 Breed Prediction-Punganur.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict

button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

13.Breed Prediction-Ponwar.



Figure 7. 13 Breed Prediction-Ponwar

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

14.Breed Prediction-Ongole



Figure 7. 14 Breed Prediction-Ongole

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

15.Breed Prediction-Nimari.



Figure 7.15 Breed Prediction-Nimari.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

16.Breed Prediction-Gir.



Figure 7.16 Breed Prediction-Nagori

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

17.Breed Prediction-Krishna.



Figure 7. 17 Breed Prediction-Krishna.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

18.Breed Prediction-Kangayam.



Figure 7.18 Breed Prediction-Kangayam.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and

normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

19.Breed Prediction-Kandhari.



Figure 7.19 Breed Prediction-Kandhari.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

20.Breed Prediction-Hariana.



Figure 7.20 Breed Prediction-Hariana.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

21.Breed Prediction-Gaolo



Figure 7.21 Breed Prediction-Gaolo

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and

normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

22.Breed Prediction-Deoni.



Figure 7.22 Breed Prediction-Deoni.

When the user selects the image upload option and chooses a cow image from their system, the uploaded image is immediately displayed on the screen for preview. After clicking the predict button, the application preprocesses the image by resizing it to the required input size and normalizing the pixel values before passing it to the trained deep learning model for classification. The model analyzes the image and generates prediction probabilities for all supported breeds. The breed with the highest probability is identified as the final prediction. The result is then displayed clearly on the interface along with the uploaded image, showing the predicted breed name and the corresponding confidence percentage. This allows the user to visually verify the input image and view the classification result in real time.

Chapter 8

Social, Legal, Ethical, Sustainability and Safety Aspects

8.1 Social Aspects

- Helps farmers identify livestock breeds accurately.
- Supports researchers and students in agricultural studies.
- Promotes awareness of indigenous cattle and buffalo breeds.
- Reduces dependency on manual breed identification methods.
- Encourages adoption of AI technology in rural communities.
- Improves livestock management and productivity.
- Provides accessible technology through a simple web interface.

8.2 Legal Aspects

- The system does not store personal user data permanently.
- Dataset images are used strictly for academic and research purposes.
- Proper attribution should be maintained if publicly sourced datasets are used.
- The model must comply with data protection and privacy regulations.
- The application should not be misused for commercial exploitation without authorization.
- Intellectual property rights of libraries and frameworks (TensorFlow, Streamlit, etc.) are respected.

8.3 Ethical Aspects

- The system is non-invasive and does not harm animals.
- AI predictions should assist, not replace, expert veterinary judgment.
- Dataset bias must be minimized by including diverse breeds.
- The model should provide fair classification across all supported breeds.
- The system should not mislead users with overconfident predictions.
- Transparent communication of model limitations is necessary.

8.4 Sustainability Aspects

- Promotes sustainable livestock management practices.

- Encourages conservation of indigenous cattle and buffalo breeds.
- Supports efficient breeding and agricultural planning.
- Uses digital methods to reduce paperwork and manual errors.
- Can be expanded in future to support broader agricultural monitoring systems.
- Designed to be scalable and adaptable for long-term use.

8.5 Safety Aspects

- The system operates locally, reducing cybersecurity risks.
- No harmful physical interaction with animals is involved.
- Input validation prevents system crashes due to invalid uploads.
- Error handling ensures safe and stable execution.
- The application does not modify or delete user files.
- Designed for safe academic and research deployment

Chapter 9
Conclusion and Future Work

9.1 Conclusion

The Cattle and Buffalo Breed Classification System successfully demonstrates the application of deep learning techniques for automated livestock breed identification. By using transfer learning and Convolutional Neural Networks (CNN), the system is capable of classifying livestock breeds from images with reliable accuracy.

The integration of the trained model into a Streamlit-based web application enables real-time prediction through a simple and interactive user interface. The system allows users to upload livestock images and instantly receive breed predictions along with confidence scores.

The implementation ensures modular design, efficient processing, and stable deployment on a local host environment. Functional, usability, and performance evaluations confirm that the system operates effectively and meets the defined requirements.

Overall, the project contributes to the advancement of AI applications in agriculture and provides a practical solution for assisting farmers, researchers, and students in livestock breed identification.

9.2 Limitations

- The system is limited to the breeds included in the training dataset.
- Prediction accuracy may decrease for low-quality or unclear images.
- The model may struggle with visually similar breeds.
- Currently deployed only on a local host environment.
- Does not include a live database for storing prediction history.
- Limited dataset size may affect generalization performance.

9.3 Future Enhancements

- Integration of additional cattle and buffalo breeds.
- Development of a mobile application for field usage.
- Deployment on a cloud server for global accessibility.
- Integration of real-time camera-based breed detection.
- Improvement of dataset size and diversity for higher accuracy.
- Addition of health monitoring and disease detection features.

- Multi-language interface support for rural users.
- Incorporation of feedback mechanism for model improvement.

References

[1] S. Chakraborty, K. Karthik and S. Banik, "Graph Synthesis for Pig Breed Classification From Muzzle Images," in *IEEE Access*, vol. 9, pp. 127240-127258, 2021, doi: 10.1109/ACCESS.2021.3111957

Link: **https://ieeexplore.ieee.org/document/9535496**

[2] A. Biglari and W. Tang, "A Vision-Based Cattle Recognition System Using TensorFlow for Livestock Water Intake Monitoring," in *IEEE Sensors Letters*, vol. 6, no. 11, pp. 1-4, Nov. 2022, Art no. 5501404, doi: 10.1109/LSENS.2022.3215699.

Link: **https://ieeexplore.ieee.org/document/9924566**

[3] R. -W. Bello, A. S. A. Mohamed and A. Z. Talib, "Contour Extraction of Individual Cattle From an Image Using Enhanced Mask R-CNN Instance Segmentation Method," in *IEEE Access*, vol. 9, pp. 56984-57000, 2021, doi: 10.1109/ACCESS.2021.3072636.

Link: **https://ieeexplore.ieee.org/document/9400819**

[4] M. A. Rahman, M. A. Raihan, M. Shorif Uddin, M. Hasan and M. T. Habib, "A Comprehensive Analysis of Classic Machine Learning and Deep Learning Modeling for Breed Recognition of Bananas," in *IEEE Access*, vol. 13, pp. 194562-194579, 2025, doi: 10.1109/ACCESS.2025.3631557

Link: **https://ieeexplore.ieee.org/document/11239069**

[5] N. R. Duraiswami, S. Bhalerao, A. Watni and C. N. Aher, "Cattle Breed Detection and Categorization Using Image Processing and Machine Learning," *2022 International Conference on Advancements in Smart, Secure and Intelligent Computing (ASSIC)*, Bhubaneswar, India, 2022, pp. 1-6, doi: 10.1109/ASSIC55218.2022.10088381.
Link: **https://ieeexplore.ieee.org/document/10088381**

[6] S. C. Iyer and N. M. Shekokar, "Identifying the Optimal Deep Learning Based Image Recognition Technique for Dog Breed Detection," *2023 14th International Conference on Computing Communication and Networking Technologies (ICCCNT)*, Delhi, India, 2023, pp. 1-10, doi: 10.1109/ICCCNT56998.2023.10307245.

Link: **https://ieeexplore.ieee.org/document/10307245**

[7] C. Bhanuprakash and V. N. V, "Identification of Cattle's Breed Type by Processing Image Using Deep Learning Models," *2024 International Conference on Integrated Intelligence and Communication Systems (ICIICS)*, Kalaburagi, India, 2024, pp. 1-7, doi: 10.1109/ICIICS63763.2024.10859520.

Link: **https://ieeexplore.ieee.org/document/10859520**

[8] Singh, R. Kothari and V. Arulalan, "Dog Breed Detection using YOLOv7 and WOA-CNN," *2024 10th International Conference on Communication and Signal Processing (ICCSP)*, Melmaruvathur, India, 2024, pp. 1477-1482, doi: 10.1109/ICCSP60870.2024.10543599

Link: https://ieeexplore.ieee.org/document/10543599

[9] H. Zhao, P. Li, Z. Chen, K. Guo, Y. Chen and C. Su, "Cow Face Recognition with Noise Labels Using Vision Transformer," *2023 IEEE 4th International Conference on Pattern Recognition and Machine Learning (PRML)*, Urumqi, China, 2023, pp. 93-98, doi: 10.1109/PRML59573.2023.10348318

Link: https://ieeexplore.ieee.org/document/10348318

[10] Z. Zheng, B. Wen and Z. Weng, "Research on Multi-View Cattle Facial Recognition Algorithm Based on Feature Matching," *2025 IEEE 8th International Conference on Signal Processing and Machine Learning (SPML)*, Hohhot, China, 2025, pp. 5-9, doi: 10.1109/SPML66318.2025.11199799.
Link: https://ieeexplore.ieee.org/document/11199799

[11] J. -W. Chae, H. -S. Sim, C. -W. Lee, C. -S. Choi and H. -C. Cho, "Video-Based Analysis of Cattle Behaviors: Improved Classification Using FlowEQ Transform," in *IEEE Access*, vol. 12, pp. 42860-42867, 2024, doi: 10.1109/ACCESS.2024.3379277

Link: https://ieeexplore.ieee.org/document/10475331

[12] W. Kusakunniran, A. Wiratsudakul, U. Chuachan, S. Kanchanapreechakorn and T. Imaromkul, "Automatic cattle identification based on fusion of texture features extracted from muzzle images," *2018 IEEE International Conference on Industrial Technology (ICIT)*, Lyon, France, 2018, pp. 1484-1489, doi: 10.1109/ICIT.2018.8352400.
Link: https://ieeexplore.ieee.org/document/8352400

[13] W. Kusakunniran and T. Chaiviroonjaroen, "Automatic Cattle Identification based on Multi-Channel LBP on Muzzle Images," *2018 International Conference on Sustainable Information Engineering and Technology (SIET)*, Malang, Indonesia, 2018, pp. 1-5, doi: 10.1109/SIET.2018.8693161.

Link: https://ieeexplore.ieee.org/document/8693161

[14] J. R. Butu, I. Nurtanio and A. W. Paundu, "Identification of Different Types of Buffalo Using YOLO Algorithm Based on Computer Vision," *2023 3rd International Conference on Intelligent Cybernetics Technology & Applications (ICICyTA)*, Denpasar, Bali, Indonesia, 2023, pp. 159-164, doi: 10.1109/ICICyTA60173.2023.10428773.

Link: https://ieeexplore.ieee.org/document/10428773

[15] V. S. P. Gunda, H. Gulla, V. Kosana and S. Janapati, "A hybrid deep learning based robust framework for cattle identification," *2022 International Conference on Advancements in Smart, Secure and Intelligent Computing (ASSIC)*, Bhubaneswar, India, 2022, pp. 1-5, doi: 10.1109/ASSIC55218.2022.10088414

Link: https://ieeexplore.ieee.org/document/10088414

Base Paper

Appendix