# Module – 5: Electrochemical Energy Systems

Brief introduction to conventional primary and secondary batteries; High energy electrochemical energy systems: Lithium batteries – Primary and secondary, its Chemistry, advantages and applications.

Fuel cells – Polymer membrane fuel cells, Solid-oxide fuel cells- working principles, advantages, applications.

27.Li_Battery_Module_5_(I)

Introduction - Electrochemical Cell

Electrolytic Cell
**Chemical reaction by passing electric current**

Electrochemical Cell
Chemical redox reaction is utilized to produce electrical current

| Electrical energy is converted into chemical energy |

| Chemical energy is converted into electrical energy |

Electrochemical cell

Parts of electrochemical cell

- Electrodes
  - i. Anode
  - ii. Cathode
- Electrolyte
- Separator

Oxidation occurs in Anode
Reduction occurs in Cathode

Electrochemical Energy Systems 3

Electrochemical cell – Daniell cell

Anode

Oxidation

$M \rightarrow M^{n+} + ne^-$ (Loss of electron)

$Zn \rightarrow Zn^{2+} + 2e^-$ (Daniell cell)

Cathode

Reduction

$M^{n+} + ne^- \rightarrow M$ (Gain of electron)

$Cu^{2+} + 2e^- \rightarrow Cu$ (Daniell cell)

Representation of Electrochemical cell

- Anode is written on the left hand side, Cathode is on the write right hand side.

- In the anode side, electrode is written on the left.
  In the cathode side, electrode is written on the right

  Anode electrode | Electrolyte||Electrolyte| Cathode electrode

  Zn | Zn^{2+} (1M) || Cu^{2+} (1M) | Cu

- Salt bridge is mentioned as "||"

- Concentration of the electrolyte solution can be mentioned next to the electrolyte

Electrochemical Energy Systems

Battery

- A **battery** is a device consisting of **one or more electrochemical cells** with external connections provided to power electrical devices.

Anode
(Zinc Inner Case)

Cathode
(Graphite Rod)

Paste of MnO_2,
NH_4Cl, and Carbon

- An **electrochemical cell** is a device capable of generating **electrical energy** from **chemical reactions**.
  - e.g. Daniell Cell

Electrochemical Energy Systems

Types of Battery

- ## Primary battery (primary cells)
  - In which the cell reaction is **not reversible**. When all the reactants have been converted to product, no more electricity is produced and the battery is dead.

- ## Secondary battery (secondary cells)
  - In which cell reactions **can be reversed** by passing electric current in the opposite direction. Thus it can be used for a large number of cycles.

- ## Flow battery and Fuel Cell
  - In which materials (reactants, products, electrolytes) pass through the battery, which is simply an electrochemical cell that converts chemical to electrical energy.

Examples

- **Primary batteries**
  - i.   Dry or lachlanche cell
  - ii.   Alkaline battery
  - iii.   Lithium batteries

- **Secondary batteries**
  - i.   Lead acid
  - ii.   Nickel-Cadmium
  - iii.   Nickel Metal hydride
  - iv.   Lithium ion

- **Flow battery and Fuel Cell**
  - i.   Polymer Membrane Fuel Cell
  - ii.   Solid Oxide Fuel Cell

Lithium Primary Cell

- Lithium batteries are different from Lithium ion Batteries (also Known as Li-ion batteries).

- Lithium batteries can not be recharged

- Most of the common lithium batteries contain:

  Anode: **Metallic Li**

  Cathode: **MnO$_2$**

  Electrolyte**: Li salts dissolved in organic solvents such as Acetonitrile (CH$_3$CN), propylene carbonate, ethylene carbonate**

**Electrochemical Energy Systems**

Lithium as a Anode Material

The main attractions of lithium as an anode material is

- It is the most electronegative metal in the electrochemical series

- It has very low density, means, the largest amount of electrical energy per unit weight

10

Lithium Battery

Cell Representation

$$Li \,|\, Li+(\text{non-aqueous}) \,||\, KOH(\text{paste}) \,|\, MnO_2, Mn(OH)_2, C$$

Anode

$$Li \rightarrow Li^+ + e^-$$

Cathode

$$Li^+ + MnO_2 + e^- \rightarrow LiMnO_2$$

Overall Reaction

$$Li + MnO_2 \rightarrow LiMnO_2 + Energy$$

Electrochemical Energy Systems

Different types of Lithium Batteries

S. No.	Anode	Cathode	Characteristics	Applications
1	Li	$SOCl_2$	3.6 V, Long Shelf life, Low to Moderate rate applications	Memory Devices, Standby Electrical devices
2	Li	SO_2	3.0 V, Best low temperature performance	Military and Special Industrial needs
3	Li	MnO_2	3.0 V, Small in size, good low temperature performance, low drain applications	Medical Devices, Memory Circuits

Advantages of Lithium battery

- High electron density
- Long shelf life
- Low self discharge
- Need less maintenance
- Can provide very high current

Electrochemical Energy Systems

13

Li-ion battery (Secondary cell)

Nobel Prize in Chemistry 2019

© Nobel Media. Photo: A. Mahmoud
John B. Goodenough
Prize share: 1/3

© Nobel Media. Photo: A. Mahmoud
M. Stanley Whittingham
Prize share: 1/3

© Nobel Media. Photo: A. Mahmoud
Akira Yoshino
Prize share: 1/3

They created a rechargeable world

The Nobel Prize in Chemistry 2019 rewards the development of the lithium-ion battery. This lightweight, rechargeable and powerful battery is now used in everything from mobile phones to laptops and electric vehicles. It can also store significant amounts of energy from solar and wind power, making possible a fossil fuel-free society

Li-ion battery (Secondary battery)

Li-ion battery (Secondary battery)

Electrochemical Energy Systems 17

Lithium ion batteries

Cathode materials

- The most common compounds used for cathode materials are $LiCoO_2$, $LiNiO_2$ and $LiMn_2O_4$.

- Of these, $LiCoO_2$ has the best performance but is very high in cost, is toxic and has a limited lithium content range over which it is stable.

- $LiNiO_2$ is more stable, however the nickel ions can disorder.

- $LiMn_2O_4$ is generally the best value for money, and is also better for the environment.

Cylindrical lithium-ion battery

Top Cap (Positive Terminal)
Gasket
PTC
Vent
Cathode Tab
Top Insulator
Anode
Steel-Can (Negative Terminal)
Separator
Cathode
Bottom Insulator
Anode Tab

©2006 HowStuffWorks

Lithium ion batteries

Anodic materials

Sony's original lithium-ion battery used **coke as the anode** (coal product), and since 1997 most Li-ion batteries use **graphite to attain a flatter discharge curve**.

Developments also occur on the anode and several additives are being tried, including silicon-based alloys. Silicon achieves a 20 to 30 % increase in specific energy at the cost of lower load currents and reduced cycle life.

Nano-structured *lithium-titanate* as anode additive shows promising cycle life, good load capabilities, excellent low-temperature performance and superior safety, but the specific energy is low.

Lithium ion batteries

Electrolyte

- Since lithium reacts violently with water, and the cell voltage is so high that water would decompose, a non-aqueous electrolyte must be used.

- A typical electrolyte is $LiPF_6$ dissolved in an ethylene carbonate and dimethyl carbonate mixture.

$LiPF_6$

ethylene carbonate

dimethyl carbonate

Discharging

Charging

Anode: lithium ions in the carbon material

Cathode: lithium ions in the layered material (lithium compound)

Anode

$$Li_{1-x}CoO_2 + C_nLi_x \rightarrow LiCoO_2 + C_n$$

Cathode

$$LiCoO_2 + C_n \rightarrow Li_{1-x}CoO_2 + C_nLix$$

The lithium ion moves from the **anode to the cathode during discharge** and **from the cathode to the anode when charging**.

Applications: Laptops, cellular phones, electric vehicles

The chemical reactions for charge and discharge are as shown below:

		Charge / Discharge	
Positive Electrode	$LiCoO_2$	$\rightleftarrows$	$Li_{1-x}\ CoO_2 + xLi^+ + xe^-$
Negative Electrode	$C + xLi^+ + xe^-$	$\rightleftarrows$	CLi_x
Battery as a Whole	$LiCoO_2 + C$	$\rightleftarrows$	$Li_{1-x}\ CoO_2 + CLi_x$

The principle behind the chemical reaction in the lithium ion battery is one where the lithium in the positive electrode lithium cobalt oxide material is ionized during charge, and moves from layer to layer in the negative electrode. During discharge, the ions move to the positive electrode and return to the original compound

22

Lithium Polymer batteries are better than Lithium ion batteries

Exploded laptop

- Li-ion batteries use organic solvents to suspend the lithium ions.

- In situations where the structure of the battery is compromised, that solvent can ignite and vent from the pressurized battery.

- The result is a dangerous explosion

- The main advantage of Li-poly batteries is their reluctance to explode under pressure

Lithium Polymer Battery

• Electrolyte is a polymer

Lithium polymer (Poly-Carbon Monofluoride) batteries

← Charging

- scientists from Stanford University have found a way to use **silicon nanowires** to produces 10 times the amount of electricity of existing lithium-ion, known as Li-ion, batteries that power laptops, iPods, video cameras, cell phones, and countless other devices. **A laptop that now runs on battery for two hours could operate for 20 hours.**

Fuel – Oxidizer reaction

Combustion

Fire
Triangle

Rankine Cycle

RedOx reaction between Fuel and Oxidizer produces thermal energy → converted in to electrical energy by rankine cycle (Thermal energy → Mechanical energy → Electrical energy)

Fuel Cell

Thermal Power Plants→ Fuel is oxidized to produce thermal energy and it is converted in to mechanical and electrical energy

Chemical Energy	**Thermal Energy**	**Mechanical Energy**	**Electrical Energy**

Fuel cell→ Electrochemical redox reaction of Fuel and Oxidant, directly converts chemical energy in to electrical energy

Chemical Energy	Fuel Cell	Electrical Energy

Minimized Interconversion Loss →

Efficient

28

Electrochemical Energy Systems

Fuel Cell

- Electrochemical Cell having a separate fuel-oxidizer system that produces electrical energy by oxidation of Fuel at Anode and the reduction of Oxidizer at Cathode.

- Fuel and Oxidizer are stored outside the battery and supplied as needed.

- Supply of Fuel and Oxidizer → Production of electricity

- High efficiency and Pollution free

- By products are Water and Heat

- Used in NASA Apollo Space Crafts

- e.g. H_2-O_2 Fuel Cell, Solid Oxide Fuel Cell

Fuel Cell Components

- Fuel

- Oxidizer

- Electrodes
  - Anode – Catalyze the oxidation of fuel
  - Cathode – Catalyze the reduction of Oxygen

- Electrolyte
  - Only allows Ions to pass through and blocks electron flow

Fuel

Anode
Electrolyte
Cathode

Oxidizer

Fuel / Electrode // Electrolyte // Electrode / Oxidizer

$H_2 - O_2$ Fuel Cell

- Electrolysis of water → Splitting of water produces H_2 and O_2.

  (Electrolytic cell)

Reverse reaction ??

- Combining H_2 and O_2 to produce H_2O

  (Electrochemical Cell)

- Gas Voltaic Battery

Sir William Grove
(invented - 1839)

Fuel Cell Types

- Based on Electrolyte
  - Alkaline Fuel Cell – **KOH**
  - Polymer Membrane Fuel Cell – Polymer electrolyte – **Nafion**
  - Solid Oxide Fuel cell – Oxide electrolyte – Y doped Thoria, Ceria Stabilize Zirconia

Type of Fuel Cell	Electrolyte type	Electrolyte Example	Ions transported	Water formation in
Alkaline	Alkaline	KOH	OH^-	Anode
Polymer Membrane	Proton conducting Polymer	Nafion	H^+	Cathode
Solid Oxide fuel cell	Metal oxide	Y-doped Thoria	O^{2-}	Anode

Alkaline Fuel cell (or) $H_2 - O_2$ Fuel Cell

- Fuel – Hydrogen

- Oxidizer – Oxygen

- Electrodes

  Anode – Pt (or) Pd electrode

  Cathode – Pt (or) Ag

- Electrolyte

  KOH

33

$H_2 - O_2$ Fuel Cell

H$_2$ – O$_2$ Fuel Cell Reactions

- Anodic reaction

$$2H_2 + 4OH^- \rightarrow 2H_2O + 4e^-$$

- Cathodic Reaction

$$O_2 + 4H_2O + 4e^- \rightarrow 4\ OH^-$$

Net Reaction

$$O_2 + 2H_2 \rightarrow 2H_2O$$

Requirements for Good Fuel Cell

- Electrodes should catalyze the anodic and cathodic

  reactions

- Fuels should be Pure and Cheap - Hydrogen!!

- Oxidizers used Oxygen or Air → Pure oxygen is preferred

Limitations of Fuel Cell

- Pure Hydrogen…

- Electrode and electrolyte contamination/degradation

- Cost of Catalyst – Pt and Pd !!!

- Safety!!

High temperature → Improved kinetics, low risk of contamination

Materials stable at high temperature is needed

Solid Oxide Fuel Cell (SOFC)

Types of Fuel Cell

Based on the operational temperature

- Low Temperature Fuel Cell – Fuel – **Pure Hydrogen** (below 100 ^oC)

- Mid Temperature Fuel Cell – Fuel – **Hydrogen** or **Reformed Hydrocarbons**

  (100-300 ^oC)

- High Temperature Fuel Cell – Fuel – **Hydrocarbons, Electrolytes –**

  solid ceramics (~1000 ^oC)

Solid Oxide Fuel Cell

- $H_2 - O_2$ Fuel Cell

   $H_2 \rightarrow H^+$ diffuses through electrolyte to cathode

- Solid Oxide Fuel Cell

   $O_2 \rightarrow 2O^{2-}$ diffuses through electrolyte to anode

Electrolyte $\rightarrow$ Good oxide ion conductor and poor electron conductor

   - Operates at high temperature so diffusion rate is higher.

   - Electrical insulating oxide with non-stoichiometry

e.g. Yttria Stabilized Zirconia (YSZ), Gadolinium Doped Ceria (GDC)

Solid Oxide Fuel Cell (SOFC)

- Fuel – Hydrogen

- Oxidizer – Oxygen

- Electrodes

  Anode – Mixture of Ni and Yttria Stabilized Zirconia (YSZ)

  Cathode – Sr-doped Lanthanum Manganite ($La_{1-x}Sr_xMnO_3$)

- Electrolyte

  Oxide ion conductors (YSZ, GDC)

Solid Oxide Fuel Cell

Electrochemical Energy Systems 41 **50**

Solid Oxide Fuel Cells - Reactions

- Anode reaction

$$2H_2 + 2O^{2-} \rightarrow 2H_2O + 4e^-$$

- Cathode Reaction

$$O_2 + 4e^- \rightarrow 2O^{2-}$$

- Net reaction

$$2H_2 + O_2 \rightarrow 2H_2O$$

In $H_2 - O_2$ fuel cell water is formed on cathode side
In SOFC water is formed on anode side.

Advantages of Fuel Cell

- Low maintenance cost

- Silent operation

- Produces pure water as a product

- Heat generated during H_2O formation can also be used

- High energy conversion efficiency

- They can be used as auxiliary power units

Electrochemical Energy Systems 43

Spectral Properties of Sunlight

© 2007 Thomson Higher Education

Electrochemical Energy Systems

44

Solar energy conversion devices

```
                    ┌─────────────────────────────────────┐
                    │   Methods of trapping solar energy    │
                    └─────────────────────────────────────┘
```

Photosynthesis	Solar Water heaters	Photovoltaic cells	Chemical routes
Plants (Visible light)	Flat plate, tube (IR radiation)	p/n Si, Si, GaAs (Visible light	

Chemical routes:

Biomimetism	PEC cells
Mimicking Photosynthesis *via* chemicals	Photogalvanic cell

Photoelectrosynthesis cell

Solar Energy Conversion

Photosynthesis

Solar cell

Solar Energy Conversion

Solar heater

Solar Furnace

Module – 5

46

Solar cell

SOLAR CELL

SOLAR CELL

PHOTON

SWITCH OFF

BULB

BATTERY

www.circuiteasy.com

Solar cell is a device that directly converts the **energy of light** into **electrical energy**

Types of solar energy conversion cells

(1) Photovoltaic Cells

- Photovoltaic cell, is an electrical device that converts the energy of light directly into electricity by the photovoltaic effect

(2) Photoelectrochemical cells

- Photoelectrochemical cell is a photocurrent-generated device composed of an electrolyte, a photoactive semiconductor electrode

(3) Dye-sensitized solar cells

- Dye-sensitized solar cells (DSC) is a photoelectrochemical solar cell, consisting of a dye-sensitized semiconducting working electrode (WE), a redox electrolyte and a counter electrode (CE)

(1) Photovoltaic Cells

- **System converts light energy to electricity**

- **Applications in Aerospace & Satellite etc.**

Electrochemical Energy Systems 49

Photovoltaic Cells

❖ A photovoltaic solar cell is a device that converts the energy of sunlight directly into electricity by the photovoltaic effect.

❖ The photovoltaic effect involves creation of a voltage (or a corresponding electric current) in a material upon exposure to electro-magnetic radiation.

❖ Though the photovoltaic effect is directly related to the photoelectric effect, the two processes are different.

❖ In the photoelectric effect electrons are ejected from a material's surface upon exposure to radiation of sufficient energy.

50
Electrochemical Energy Systems

Why Silicon?

Silicon

| atomic number | 14 | 28.086 | atomic weight |

Si

[Ne]$3s^23p^2$

silicon

- acid-base properties of higher-valence oxides
- crystal structure
- physical state at 20 ºC (68 ºF)

symbol

electron configuration

name

o Silicon is a very common element abundant in nature. It is the main element in sand and quartz.

o Silicon is considered as the most suitable material for solar energy conversion because of

1) Most abundance (~28% by mass) after oxygen

2) Optimum band gap of 1.23 eV at 300 K

3) Cost effectiveness

4) Interestingly, silicon has a greater density in a liquid state than a solid state.

Electrochemical Energy Systems

51

Structure of Silicon

The crystal structure, or atomic arrangement, of any material has a great deal to do with its electrical properties.

Allotropes of silicon

Single crystal silicon

Polycrystalline silicon

Amorphous silicon

Types of silicon

❖ **Single crystal silicon -** In its crystalline form, a material is characterized by an ordered array of component atoms. This array is repetitive with displacement through the material sample.

❖ **Polycrystalline silicon -** Where a polycrystalline material is concerned, the object is composed of a number of sub-sections, each of which is crystalline in form. These subsections, however, are independently oriented so that at their interfaces the atomic order and regularity undergo sharp discontinuities.

❖ **Amorphous silicon (non-crystalline for higher light absorption) -** The final category, the amorphous material, displays no atomic regularity of arrangement on any macroscopic scale.

Electrochemical Energy Systems
53

(2) Photoelectrochemical cells

Electrochemical Energy Systems

54

Types of Photoelectrochemical cells

Photo-electrochemical cells are classified into two types according to their application

1. Liquid Junction Solar Cell (LJSC) –
   • This cell is used to convert solar energy into electrical energy

2. Photo-electrosynthesis (PES) cells –
   • In this class of cells, solar energy is converted into chemical energy in the form of fuels.

Electrochemical Energy Systems 55

Conditions for Efficient Solar Energy Conversion – Electrodes

The requirements for the electrode materials are:

1) Band gap (E_g) should be optimum

2) The doping level should be optimum, so that there will be a good spatial separation of the photo-generated carriers and hence, high quantum efficiency.

3) Should have large values of absorption co-efficient (α). This is usually found for direct band gap SC's.

Electrochemical Energy Systems

56

(3) Dye-sensitized solar cells - Grätzel cell

Dye-sensitized solar cells - Grätzel cell

1. Sunlight energy (photon of light) passes through the titanium dioxide layer and strikes electrons within the adsorbed dye molecules. Electrons gain this energy and become excited because they have the extra energy.

2. The excited electrons escape the dye molecules and become free electrons. These free electrons move through the titanium dioxide and accumulate at the -ve plate (dyed TiO_2 plate).

3. The free electrons then start to flow through the external circuit to produce an electric current. This electric current powers the light bulb.

4. To complete the circuit, the dye is regenerated. The dye regains its lost electrons from the iodide electrolyte. Iodide (I^-) ions are oxidized (loss of 2 electrons) to tri-iodide (I_3^-). The free electrons on the graphite plate then reduce the tri-iodide molecules back to their iodide state. The dye molecules are then ready for the next *excitation/oxid/red* cycle.

Dye-sensitized solar cells - Grätzel cell

Prepared Grätzel cell

Upper Plate :
Dye coated TiO_2 Plate (-Ve)

Lower Plate :
Graphite coated conductor (+Ve)

By Hermetic sealing

Electrochemical Energy Systems

59

Applications of solar cell

Solar cells are used in a wide variety of applications

- ❖ Toys, watches, calculators
- ❖ Electric fences
- ❖ Remote lighting systems
- ❖ Water pumping
- ❖ Water treatment
- ❖ Emergency power
- ❖ Portable power supplies
- ❖ Satillites

Module – 6: Fuels and Combustion

- Calorific value - Definition of LCV, HCV. Measurement of calorific value using bomb calorimeter and Boy's calorimeter including numerical problems.

- Controlled combustion of fuels - Air fuel ratio - minimum quantity of air by volume and by weight - Numerical problems

- Three way catalytic converter - selective catalytic reduction of NO_X

- Knocking in IC engines - Octane and Cetane number - Anti-knocking agents.

Fuel

- **Fuel:** Anything which burn to give heat in presence of oxygen

$$\text{Fuel} + O_2 \rightarrow \text{Product} + \text{Heat}$$

- **Combustion:** The process of burning fuel. In other words, combustion involves oxidation of fuels to CO_2 and H_2O.

$$H_2 + O_2 \rightarrow H_2O + \textbf{Heat}$$
$$C + O_2 \rightarrow CO_2 + \textbf{Heat}$$
$$CH_4 + O_2 \rightarrow CO_2 + H_2O + \textbf{Heat}$$

- During this fuel combustion process large amount of heat energy is liberated which can be utilized.

Classification of Fuel


```
Classification of Fuels
    │
    ├── Based on Physical state
    │       ├── Solid fuel (e.g. Wood, Coal)
    │       ├── Liquid fuel (e.g. Crude petroleum)
    │       └── Gaseous fuel (e.g. Natural gas)
    │
    └── Based on Occurrence
            ├── Primary or natural fuel (e.g. Wood, Coal)
            └── Secondary or prepared fuel (e.g. Charcoal)
```

Characteristic of good fuel

1. It should **ignite easily**

2. It should give out a **lot of heat (High calorific value)**

3. It should have **low smoke** and **low combustible matter** such as ash

4. It should be **inexpensive** and **readily available**

5. It should be **easy to store and transport**

6. It should have **low ash content**

Calorific value of fuels

- **Calorific value:** The total quantity of heat liberated when a unit mass or volume of the fuel is burnt completely **(capacity to supply heat)**.

- **Units:** cal/g (or) kJ/kg.

- **Calorie:** The amount of heat required to raise the temperature of one gram of water through one degree centigrade.

Fuel	Calorific Value (kJ/kg)
Cow dung cake	6000-8000
Wood	17000-22000
Coal	25000-33000
Petrol	45000
Kerosene	45000
Diesel	45000
Methane	50000
CNG	50000
LPG	55000
Biogas	35000-40000
Hydrogen	150000

Calorific Value   = Heat produced on burning of 1 kg of fuel

Types of calorific value

Calorific value

Higher or Gross Calorific Value

- HCV or GCV

Lower or Net Calorific Value

- LCV or NCV

Determination of Calorific Value

Bomb Calorimeter

- HCV (or) GCV

Boy's Calorimeter

- Gaseous (or) Liquid fuels

Fuels and Combustion 66

Higher or Gross Calorific Value (HCV or GCV)

It is defined as

The total amount of heat liberated, when a unit mass of fuel is burnt completely and the products of the combustion are cooled down to room temperature

- Usually, all fuels contain some hydrogen
- When the calorific value of hydrogen containing fuel is determined experimentally, the hydrogen is converted to steam.
- If the products of combustion are condensed to room temperature (25°C), the steam gets condensed into water and latent heat is evolved.
- The latent heat of condensation of steam also gets included in the measured heat.
- A good fuel posses HCV

Lower or Net Calorific Value

It is defined as

The net heat produced when unit mass / volume of the fuel is burnt completely and the products are permitted to escape

- In actual use of fuel, the water vapour and moisture *etc.* are not condensed and escapes as such along with hot combustion gases. Hence a lesser amount of heat is available.

- Net or lower calorific value can be found from GCV value

  NCV   =   GCV - Latent heat of water vapour formed

  =   GCV - Mass of hydrogen x 9 x latent heat of steam

- 1 part by mass of hydrogen produces 9 parts by mass of water. The latent heat of steam is 587 kcal/kg formed at room temperature. (i.e. 25°C).

Latent heat of water vapour formed

Latent heat of water vapours is 587 kcal/kg

Hydrogen in the fuel reacts with oxygen to give water

$$H_2 + 1/2\ O_2 \rightarrow H_2O$$

$$2H = 1/2O_2 = H_2O$$

$$2 parts = 16 parts = 18 parts$$

$$1 parts = 8 parts = 9 parts$$

Thus,

$$NCV = GCV - 0.09H*587$$

Note:

If H is the percentage of hydrogen in fuel,

the mass of water produced from 1 g of fuel = (9/100)×H

= 0.09 H

Determination of Calorific Value

Bomb calorimeter

oxygen supply
thermometer
stirrer
ignition wires
magnifying eyepiece
insulating jacket
water
air space
bucket
heater
ignition coil
steel bomb
sample
crucible

Stirrer
Electric heater to ignite sample.
Temp C

Bomb calorimeter

Calculation for HCV

$$HCV = \frac{(W+w)(t_2-t_1) \times \text{Specific heat of water}}{m} \quad cal/g$$

m   =   mass of fuel pellet (g)

W   =   mass of water in the calorimeter (g)

w   =   water equivalent of calorimeter (g)

t_1 =   initial temperature of calorimeter

t_2 =   final temperature of calorimeter

HCV   =   Higher/gross calorific value of fuel

Specific heat of water = 1 cal/g °C

$$HCV = \frac{(W+w)(t_2-t_1)}{m} \quad cal/g$$

Numerical

0.72 g of a fuel containing 80% carbon, when burnt in a bomb calorimeter, increased the temperature of water from 27.3 ºC to 29.1 ºC. If the calorimeter contains 250 g of water and its water equivalents is 150 g, calculate the HCV of the fuel. Give your answer in kJ/kg.

Solution:

Here, m = 0.72 g; W = 250 g; w = 150 g; t_1 = 27.3 ºC and t_2 = 29.1 ºC.

$$\text{HCV of fuel (L)} = \frac{(W+w)(t_2-t_1)}{m} \ cal/g$$

1 cal/g = 4.2 kJ/kg

$$= \frac{(250+150)(29.1-27.3)}{0.72} = 1000 \ cal/g$$

$$= 1000 \times 4.2 = \textbf{4,200 kJ/kg}$$

72

13

Calculation for LCV

Water Equivalent of the calorimeter

- It is determined by burning a fuel of known calorific value Benzoic acid (HCV = 6,325 kcal/kg) and naphthalene (HCV = 9,688 kcal/kg)

If H is the percentage of hydrogen in fuel,
the mass of water produced from 1 g of fuel = (9/100)×H
$$= 0.09\ H$$

Heat taken by water in forming steam = 0.09 H× 587 cal

(latent heat of steam = 587 cal/kg)

LCV = HCV − Latent heat of water formed

LCV = [HCV − (0.09 H x 587)] kcal/kg

Numerical - Problem

On burning 0.83 g of a solid fuel in a bomb calorimeter, the temperature of 3,500 g of water increased from 26.5 ⁰C to 29.2 ⁰C. Water equivalent of calorimeter and latent heat of steam are 385.0 g of and 587.0 cal/g, respectively. If the fuel contains 0.7% hydrogen, calculate its gross and net calorific value.

Weight of fuel	=	m	= ?	0.83 g
Weight of water	=	W	= ?	3,500 g
Water equivalent of calorimeter	=	w	= ?	385 g
Final temperature	=	t_2	= ?	29.2 °C
Initial temperature	=	t_1	= ?	26.5 °C
Percentage of hydrogen	=	H	= ?	0.7%
Latent heat of steam	=		= ?	587 cal/g

Numerical

$$\text{HCV of fuel (L)} = \frac{(W+w)(t_2 - t_1)}{m} \; \text{cal/g}$$

$$= \frac{(3500 + 385)(29.2 - 26.5)}{0.83}$$

$$= 12,638 \; \text{cal/g}$$

NCV   = [GCV − 0.09 H × 587]

        = (12,63 8 − 0.09 × 0.7 × 587) cal/g

        = (12,638 − 37) cal/g

        = 12,601 cal/g

Corrections

Corrections

- For accurate results the following corrections are also incorporated

1 Fuse wire correction

2 Acid correction

3 Cooling correction

Fuels and Combustion 76

1. Fuse wire correction

Fuse wire correction:

Heat liberated during sparking should be subtracted from calorific value

Fuse wire correction:

1) **As Mg wire is used for ignition, the heat generated by burning of Mg wire is also included in the gross calorific value.**

2) **Hence, this amount of heat has to be subtracted from the total value.**

2. Acid correction

Acid correction:

Fuels containing Sulphur and Nitrogen if oxidized, the heats of formation of H_2SO_4 and HNO_3 should be subtracted (as the acid formations are exothermic reactions)

Acid correction:

During combustion, sulphur and nitrogen present in the fuel are oxidized to their corresponding acids under high pressure and temperature condition.

$S + O_2 \quad\quad\quad\quad \rightarrow \quad SO_2$

$2SO_2 + O_2 + 2H_2O \quad \rightarrow \quad 2H_2SO_4 \quad\quad \Delta H = -144{,}000 \text{ cal}$

$2N_2 + 5O_2 + 2H_2O \quad \rightarrow \quad 4HNO_3 \quad\quad \Delta H = -57{,}160{,}000 \text{ cal}$

2. Acid correction (Cont.)

- The corrections must be made for the heat liberated in the 'bomb calorimeter' by the formation of H_2SO_4 and HNO_3.

- The amount of H_2SO_4 and HNO_3 is analyzed by washings of the calorimeter.

  - ➢ For each mL of 0.1 N H_2SO_4 formed, 3.6 calories should be subtracted.

  - ➢ For each mL of 0.01N HNO_3 formed, 1.43 calories should be subtracted.

3. Cooling correction:

Cooling correction:

   The rate of cooling of the calorimeter from maximum temperature to room temperature is noted. From this rate of cooling [*i.e.* dt (°C/min)] and the actual time taken for cooling (X min) then correction (dt × X) is called cooling correction and is added to the $(t_2 - t_1)$ term.

If the time taken for the water in the calorimeter **to cool down from the maximum temperature** **attained to the room temperature**	**= "X" minutes**
Rate of cooling	**= dt (°C/min)**
Cooling correction	**= X $\times$ dt**

This should be added to the observed rise in temperature

Calculation after correction

- ## HCV - Before corrections

$$\text{HCV} = \frac{(W+w)(t_2 - t_1)}{m} \text{ cal/g}$$

- ## HCV – After corrections

$$\text{HCV} = \frac{(W+w)[(t_2 - t_1) + \text{Cooling correction}] - (\text{Acid correction} + \text{Fuse correction})}{m} \text{ cal/g}$$

Fuels and Combustion 81

Numerical - Problem

A sample of coal contains C = 93%; H = 6% and ash = 1%. The following data were obtained when the above coal was tested in bomb calorimeter.

Weight of coal burnt	=	0.92 g
Weight of water taken	=	550 g
Water equivalent of calorimeter	=	2,200 g
Rise in temperature	=	2.42 °C
Fuse wire correction	=	10.0 cal
Acid correction	=	50.0 cal

Calculate gross and net calorific value of the coal, assuming the latent heat of condensation of steam as 580 cal/g.

Numerical - Solution

Weight of coal burnt	=	m	=	**0.92 g**
Weight of water taken	=	W	=	**550 g**
Water equivalent of calorimeter	=	w	=	**2,200 g**
Rise in temperature	=	(t_2-t_1)	=	**2.42 °C**
Fuse wire correction	=		=	**10.0 cal**
Acid correction	=		=	**50.0 cal**
Latent heat of steam	=		=	**580 cal**
Percentage of hydrogen	=	H	=	**6%**

Numerical – Solution (Cont.)

(a)

$$GCV = \frac{(W+w)(t_2 - t1) - (Acid\ correction + Fuse\ correction)}{m}\ cal/g$$

$$= \frac{(550+2{,}200) \times (2.42) - (50+10)}{0.92}\ cal/g$$

$$= 7{,}168.5\ cal/g$$

(b)

NCV $= [GCV - 0.09 \times H \times latent\ heat\ steam]$

$= (7168.5 - 0.09 \times 6 \times 580)\ cal/g$

$= 6855.3\ cal/g$

Boy's Calorimeter - Principle

It is used for measuring the calorific value of gaseous (or) liquid fuels.

Principle

➢ A known volume of gaseous fuel sample is burnt in the combustion chamber of a Boy's calorimeter.

➢ The released heat is quantitatively absorbed by cooling water, circulated through copper coils surrounding the combustion chamber.

➢ The mass of cooling water and its rise in temperature are noted.

➢ The mass of water produced by condensation of steam is calculated.

➢ The calorific value of the fuel sample is then calculated from these data.

Boy's Calorimeter

Boy's gas calorimeter

Fuels and Combustion 86

Boy's Calorimeter - Construction

Construction

Boy's calorimeter consists of a combustion chamber surrounded by water tube with two thermometers T_1 and T_2 attached. There is a burner in the chamber, which is connected to a gas tube.

Working

➢ A known volume of water is passed through the tubes.

➢ The initial temperature is noted when the two thermometers show the same constant temperature.

➢ A known volume of the gas (measured using a meter) is passed through the tube and burnt in the combustion chamber.

➢ The heat liberated is absorbed by the water in the tubes.

➢ The final temperature of water is noted.

➢ The gaseous products are cooled and condensed into a measuring jar.

Boy's Calorimeter - Calculation

32.Boy's Calorimeter_Module_6_(II)

$$\text{HCV (or) GCV} = W \times S \times \frac{(T_2 \quad T1)}{V}$$

$$\text{LCV (or) NCV} = \left(GCV - \frac{m \times 587}{V} \right)$$

V = Volume of the gas burns at STP in certain time (t)

W = Mass of the cooling water used in time (t)

T_1 = Temperature of inlet water

T_2 = Temperature of outgoing water

m = Amount of water collected from condensation in time (t)

S = Specific heat of water   Specific heat of water = 1 cal/g °C

Module – 6   88   Fuels and Combustion   30

Determination of calorific value

Determination of calorific value

❖ **Experimental methods**
1. Bomb calorimeter
2. Boy's calorimeter

❖ **Theoretical method**
➢ Dulong's formula
(or)
➢ I.A. Davies formula

• The calorific value of fuels (e.g. Coal) is determined theoretically by Dulong's formula or I.A. Davies formula

Dulong's Formula

- The approximate calorific value of a fuel can be determined by knowing the amount of constituents present:

- Gross or higher calorific value (HCV) from elemental constituents of a fuel.

    H = 34500 kcal/kg; C = 8080 kcal/kg; S = 2240 kcal/kg

- Oxygen present in the fuel is assumed to be present as water (fixed hydrogen).

    Available Hydrogen   = Total hydrogen - Fixed hydrogen

                               = Total hydrogen - 1/8 mass of oxygen in fuel

- Dulong's formula for calorific value from the chemical composition of fuel is,

$$\text{HCV} = \frac{1}{100}\left[8080\,\text{C} + 34500\left(\text{H} - \frac{\text{O}}{8}\right) + 2240\,\text{S}\right] \text{ kcal/kg}$$

Combustion of Fuel

Fuels and Combustion

Combustion

- **Combustion** is a process in which oxygen from the air reacts with the elements or compounds to give heat.

```
                                    ┌─────────────────────────────┐
                                    │    Ignition temperature     │
                                    └─────────────────────────────┘
                                    ┌─────────────────────────────┐
                                    │       Explosive range       │
                                    └─────────────────────────────┘
          ┌───────────┐             ┌─────────────────────────────┐
          │ Concepts  │─────────────│            Flame            │
          └───────────┘             └─────────────────────────────┘
                                    ┌─────────────────────────────┐
                                    │      Surface combustion     │
                                    └─────────────────────────────┘
                                    ┌─────────────────────────────┐
                                    │      Primary combustion     │
                                    └─────────────────────────────┘
```

Combustion

- As the elements or compounds combine in definite proportions with oxygen, we need to calculate what is **minimum oxygen or air required** for the complete combustion of compounds.

- The commonly involved combustion reactions are;

$$i) \quad C \quad + \quad O_2 \quad \rightarrow \quad CO_2$$

$$ii) \quad 2H_2 \quad + \quad O_2 \quad \rightarrow \quad 2H_2O$$

$$iii) \quad S \quad + \quad O_2 \quad \rightarrow \quad SO_2$$

$$iv) \quad 2CO \quad + \quad O_2 \quad \rightarrow \quad 2CO_2$$

$$v) \quad CH_4 \quad + \quad 2O_2 \quad \rightarrow \quad CO_2 + 2H_2O$$

$$vi) \quad 2C_2H_6 \quad + \quad 7O_2 \quad \rightarrow \quad 4CO_2 + 6H_2O$$

$$vii) \quad 2C_2H_2 \quad + \quad 5O_2 \quad \rightarrow \quad 4CO_2 + 2H_2O$$

Combustion – Calculation of air quantities

✓ Substances always combine in definite proportions.

C (s)	+	O_2 (g)	→	CO_2 (g)
12		32		44

✓ Air contains 21% of oxygen by volume & 23% of oxygen by mass.

$1\ kg$ of oxygen is supplied by $\dfrac{1 \times 100}{23}$ = 4.35 kg of air

$1\ m^3$ of oxygen is supplied by $\dfrac{1 \times 100}{21}$ = 4.76 m^3 of air

✓ 28.94 g/mol is taken as the molecular mass of air

- Since air has 23% by weight or 21% by volume of oxygen

- Minimum weight of air needed for complete combustion = Net O_2 x 100/23 g
- Minimum volume of air needed for complete combustion = Net O_2 x 100/21 g

Combustion calculation procedure

Combustion equation	Wt. of Oxygen needed	Vol. Of Oxygen needed
C + O₂ → CO₂ "x" g or m³	$x \times 1 \times \frac{32}{12}$	$x \times 1$
H₂ + 0.5 O₂ → H₂O "y" g or m³	$y \times 0.5 \times \frac{32}{2}$	$y \times 0.5$
CO + 0.5 O₂ → CO₂ "z" g or m³	$z \times 0.5 \times \frac{32}{28}$	$z \times 0.5$
S + O₂ → SO₂ "p" g or m³	$p \times 1 \times \frac{32}{32}$	$p \times 1$
CH₄ + 2 O₂ → CO₂ + 2H₂O "q" g or m³	$q \times 2 \times \frac{32}{16}$	$q \times 2$
C₂H₆ + 3.5 O₂ → 2CO₂ + 3H₂O "r" g or m³	$r \times 3.5 \times \frac{32}{30}$	$r \times 3.5$

Combustion- Numerical problem

Question: How much air is required to burn 1 kg of pure carbon?

Solution: M. Wt. of O_2 = 32

This reacts with C, M. Wt. = 12

C (s)	+	O_2 (g)	$\rightarrow$	CO_2 (g)
12		32		44
x = 1000 g		m_{Oxygen} = ?		

Wt. of Oxygen needed = m_{Oxygen} = $x \times 1 \times \dfrac{32}{12}$

$$m_{Oxygen} = 1000 \times 1 \times \dfrac{32}{12}$$
$$= 2667 \text{ g (or) } 2.667 \text{ kg of } O_2$$

But, air contains only 23% of O_2 by weight

Mass of air required to burn 1 kg of pure carbon = $\dfrac{100 \times 2.667}{23}$ = 11.59 kg

Knocking

IC engine

An **internal combustion engine** (ICE) is a heat **engine** in which the **combustion** of a fuel occurs with an oxidizer (usually air) in a **combustion** chamber that is an integral part of the working fluid flow circuit

IC engine

> In an internal combustion engine, a mixture of gasoline vapour and air is used as a fuel.

> After the initiation of the combustion reaction by spark in the cylinder, the flame should spread rapidly and smoothly through the gaseous mixture, thereby the expanding gas drives the piston down the cylinder.

IC engine – Compression ratio

- **The ratio of the gaseous volume in the cylinder (V_1) at the end of the suction stroke to the volume (V_2) at the end of compression-stroke of the piston is known as the 'compression ratio'.**

V_1 **being greater than** V_2**, the CR is > 1**

- The CR indicates the extent of compression of the fuel-air-mixture by the piston.

- Efficiency of IC engine increases with compression ratio.

IC engine – Knocking

- In certain circumstances, due to the presence of some constituents in the gasoline used, the rate of oxidation becomes so great that the last portion of the fuel-air mixture gets ignited instantaneously producing an explosive violence, known as '**knocking**'.

Knocking – Rattling noise or sharp metallic noise produced by internal combustion engine
– Loss of energy and engine lifetime

Knocking in IC engine

Fuels and Combustion

Knocking – Reasons and Effects

Reasons

- If the IC Engine chamber is not getting the appropriate mixture of air and fuel combining together for combustion, then it will result in inconsistent fuel burn.

Chemical structure and Knocking

- The tendency of fuel constituents to knock is in the following order;

Straight chain paraffins > **Branched chain paraffins (iso-paraffin)** > **Olefins** > **Cyclo paraffins (naphthenes)** > **Aromatics**

Effects

- **The knocking results in loss of efficiency, since this ultimately decreases the compression ratio.**

- **The cylinder wall and piston get damaged.**

Knocking – Gasoline & Diesel fuel

Octane Number Vs Cetane Number

|	
Octane number is a measure of the performance of a fuel	Cetane number is the measure of the delay of the ignition of a fuel
Important for predicting the knocking of an engine	Important for predicting the ignition of an engine
Given for gasoline	Given for diesel
Octane rating is done considering the octane number of isooctane as 100	Cetane rating is done considering the ignition of cetane

Visit www.pediaa.com

Octane Number

- The most common way of expressing the **knocking characteristics of a combustion engine fuel is by 'octane number'**, introduced by Edger.

- A measure of the resistance of petrol and other fuels to autoignition n-heptane, knocks very badly and hence, its anti-knock value has arbitrarily been given zero.

- Isooctane (2, 2, 4-trimethyl pentane) gives very little knocking , so its anti-knock value has been fixed as 100.

- Octane number is defined as the % of isooctane in a mixture of n-heptane and isooctane which has the same knocking characteristics of the petrol under the same set of conditions.


n-Heptane

Isooctane

Greater the octane number, greater is the resistance of knocking

Cetane Number

- **The suitability of a diesel fuel is determined by its cetane value**, which is the percentage of hexadecane in a mixture of hexadecane and 2-methyl naphthalene, which has the same ignition characteristics as the diesel fuel sample, under the same set of conditions.

n-hexadecane (cetane No.=100)   2-Methyl naphthalene (cetane No.=0)

The cetane number of a diesel fuel can be raised by the addition of small quantity of certain "pre-ignition dopes" like alkyl nitrites such as ethyl nitrite, iso-amyl nitrite, acetone peroxide.

Anti-knocking Agents

Improvement of anti-knock characteristics of a fuel

- The octane number of poor fuels can be raised by the addition of tetra ethyl lead $(C_2H_5)_4Pb$ or TEL and diethyl telluride $(C_2H_5)_2Te$.

- TEL is converted into a cloud of finely divided lead and **lead oxide** (litharge) particles in the cylinder, thereby reducing the oxidation.

- Deposit of lead oxide is harmful to the engine life, **ethylene dibromide** is added to remove the lead oxide formed as lead bromide along with exhaust gases.

- **Emission of Lead: Damages the environment**

Unleaded petrol: Alternative methods

- Addition of high octane compounds like isopentane, isooctane, ethyl benzene, isopropyl benzene, **methyl tertiary butyl ether** (MTBE). Among these MTBE is more preferred because it contains oxygen in the form of ether group and supplies oxygen for the combustion of petrol in internal combustion engines there by reducing the extent of peroxy compound formation.

106 **Fuels and Combustion** **51**

Three-way catalytic converter

**Fuels and Combustion** 107

Three-way catalytic converter

Fuels and Combustion

108

Components

- The current three-way catalyst is generally a multicomponent material, containing the precious metals rhodium, platinum and (to a lesser extent) palladium, ceria (CeO_2), γ-alumina (Al_2O_3), and other metal oxides.

- It typically consists of a ceramic monolith of cordierite ($2Mg \cdot 2Al_2O_3 \cdot 5SiO_2$) with strong porous walls enclosing an array of parallel channels.

- For example, Cordierite is used because it can withstand the high temperatures in the exhaust, and the high rate of thermal expansion encountered when the engine first starts – typically, the exhaust gas temperature can reach several hundred degrees in less than a minute.

- The reduction catalyst is made of platinum and rhodium while the oxidation catalyst is made of platinum and palladium. Both the catalysts have a ceramic honeycomb structure.

Working of Three-way catalytic converter

- A three-way catalytic converter makes use of two catalysts to convert harmful gases to harmless gases.

- They are: **Reduction Catalyst** & **Oxidation Catalyst**

Exhaust gases with HC, NO_x and CO

3-way Catalytic Converter

Reduction Catalyst

Removal of NO_x

Oxidation Catalyst

N_2, CO_2 and H_2O

Ceramic Honeycomb Structured Catalyst

Function of Three-way catalytic converter

Stage 1 – Reduction Catalyst:

• The exhaust gases are first sent over the reduction catalyst (which is made of platinum and rhodium). It converts oxides of nitrogen (NO_x) to nitrogen (N_2) and oxygen (O_2).

$$2NO \quad \rightarrow \quad N_2 \quad + \quad O_2$$

$$2NO_2 \quad \rightarrow \quad N_2 \quad + \quad O_2$$

Stage 2 – Oxidation Catalyst:

• Exhaust gases that are free of oxides of nitrogen (NO_x) are then sent over the oxidation catalyst (made of platinum and palladium). The oxidation catalyst coverts carbon-monoxide (CO) and hydrocarbons (HC) in the gases into carbon-di-oxide (CO_2) and water (H_2O).

$$2CO \quad + \quad O_2 \quad \rightarrow \quad 2CO_2$$

$$HC \quad + \quad O_2 \quad \rightarrow \quad CO_2 \quad + \quad H_2O$$