

Q.No :6

Problem Description:

Good news! Suresh get to go to America on a class trip! Bad news, he don't know how to use the Dollar which is the name of the American cash system. America uses coins for cash a lot more than the Kuwait does. Dollar comes in coins for values of: 1, 2, 10, 50, 100, & 500 To practice your Dollar skills, suresh have selected random items from Amazon.co.us and put them into a list along with their prices in Dollar. Suresh now want to create a program to check suresh Dollar math.

Suresh goal is to maximize your buying power to buy AS MANY items as you can with your available Dollar.

Input Format:

File listing 2 to 6 items in the format of:

ITEM DDDDD

ITEM = the name of the item you want to buy

DDDDD = the price of the item (in Dollar)

Output Format:

Print the output in a separate lines contains, List the items suresh can afford to buy. Each item on its own line. Suresh goal is to buy as many items as possible. If suresh can only afford the one expensive item, or 2 less expensive items on a list, but not all three, then list the less expensive items as affordable. If suresh cannot afford anything in the list, output "I need more Dollar!" after the items. The final line you output should be the remaining Dollar he will have left over after make purchases.

Logical Test Cases

Test Case 1	Test Case 2
INPUT (STDIN) 6000 3 Phone-case 1486 Candybar 863 Sunglasses 5529 EXPECTED OUTPUT I can afford Phone-case I can afford Candybar I can't afford Sunglasses 3651	INPUT (STDIN) 2100 3 Camera 69555 TV 76439 iPhone 90000 EXPECTED OUTPUT I can't afford Camera I can't afford TV I can't afford iPhone I need more Dollar!

Mandatory Test Cases

Test Case 1	Test Case 2	Test Case 3
KEYWORD char name[MAX][LEN];	KEYWORD int price[MAX]	KEYWORD afford[MAX]

Code:

```
#include <stdio.h>
#include <string.h>

#define MAX 10
#define LEN 100

int main()
{
    char name[MAX][LEN];
    int price[MAX];
    int afford[MAX] = {0};
```

```

int dollar;
int items;
int i, j;
int tempPrice;
char tempName[LEN];

printf("Input value:\n");

scanf("%d %d", &dollar, &items);

for(i = 0; i < items; i++)
{
scanf("%s %d", name[i], &price[i]);
}
for(i = 0; i < items - 1; i++)
{
for(j = i + 1; j < items; j++)
{
if(price[i] > price[j])
{
tempPrice = price[i];
price[i] = price[j];
price[j] = tempPrice;

strcpy(tempName, name[i]);
strcpy(name[i], name[j]);
strcpy(name[j], tempName);
}
}
}
int money = dollar;

for(i = 0; i < items; i++)
{
if(money >= price[i])
{
afford[i] = 1;
money = money - price[i];
}
}

printf("\nOutput:\n");

for(i = 0; i < items; i++)
{
if(afford[i] == 1)
{
printf("I can afford %s\n", name[i]);
}
else
{
printf("I can't afford %s\n", name[i]);
}
}

```

```
if(money == dollar)
{
printf("I need more Dollar!\n");
}
else
{
printf("%d\n", money);
}

return 0;
}
```

Output:

Test_case 1:

```
Input value:
6000 3
phone-case 1486
candybar 863
sunglassess 5529
Output:
I can afford phone-case
I can afford candybar
I can't afford sunglassess
3651
```

Test_case 2:

```
● addityajaiswal@Addityas-MacBook-Air:~$ ./a.out
Input value:
2100 3
Camera 69555
Tv 76439
iphone 90000
Output:
I can't afford Camera
I can't afford Tv
I can't afford iphone
I need more Dollar!
```

x