

QNo:9

DS	Session	Arrays	Question Information	Level 1	Challenge 29
Problem Description: Tina has given a boolean matrix <code>mat[P][Q]</code> of size <code>P X Q</code> to Laaysa, She wants to modify it such that if a matrix cell <code>mat[m][n]</code> is 1 (or true) then make all the cells of <code>m</code>_th row and <code>n</code>th column as 1. Can you help Laaysa? Constraints: <code>1 <= p, q <= 1000</code> Input Format: First line of the input is the how many rows and columns in Laaysa matrix. After that, each line will represent each row and Laaysa need to enter numbers. Output Format: Print the resultant matrix output in a separate lines.					
✓ Logical Test Cases Test Case 1 INPUT (STDIN) <pre>2 2 1 0 0 1</pre> EXPECTED OUTPUT <pre>1 1 1 1</pre> Test Case 2 INPUT (STDIN) <pre>3 3 0 0 0 0 1 0 0 0 1</pre> EXPECTED OUTPUT <pre>0 1 1 1 1 1 1 1 1</pre> ✓ Mandatory Test Cases Test Case 1 KEYWORD <pre>int arr[r][c];</pre> Test Case 2 KEYWORD <pre>arrTemp[r][c]</pre> Test Case 3 KEYWORD <pre>for(m=0;m<r;m++)</pre>					

Code:

```
#include <stdio.h>

int main()
{
    int r, c;

    printf("Input value:\n");
    scanf("%d %d", &r, &c);

    int arr[r][c];
    int arrTemp[r][c];

    int i, j;

    for(i = 0; i < r; i++)
    {
        for(j = 0; j < c; j++)
        {
            scanf("%d", &arr[i][j]);
            arrTemp[i][j] = arr[i][j];
        }
    }
}
```

```

for(i = 0; i < r; i++)
{
for(j = 0; j < c; j++)
{
if(arr[i][j] == 1)
{
int k;

for(k = 0; k < c; k++)
arrTemp[i][k] = 1;

for(k = 0; k < r; k++)
arrTemp[k][j] = 1;
}
}
}

printf("\nOutput:\n");

for(i = 0; i < r; i++)
{
for(j = 0; j < c; j++)
{
printf("%d", arrTemp[i][j]);

if(j < c - 1)
printf(" ");
}

printf("\n");
}

return 0;
}

```

Output:

```

Test_case 1:
additya@addityas-Mac:~$ ./15
Input value:
2 2
1 0
0 1

Output:
1 1
1 1

Test_case 2:

```

Input value:

3 3

0 0 0

0 1 0

0 0 1

Output:

0 1 1

1 1 1

1 1 1