

DAY -3 : CONFIGURING BASIC NETWORK THEORY

1. Router Login Page

← → ↻ ⚠ Not secure 192.168.1.1

ZTE [中文](#) | [English](#)

Home Internet Local Network VoIP Management & Diagnosis

Welcome to F670L. Please login.

Username

Password

Login

©2008-2023 ZTE Corporation. All rights reserved | F670L

2. Current Network Configuration

- IPv4 Address : 192.168.1.8
- Subnet Mask : 255.255.255.0
- Default Gateway : 192.168.1.1

3. Static IP Configuration & Internet Access Test

Steps Taken:

Navigated to **Network Settings** → **Change Adapter Options** → **Wi-Fi Properties** → **Internet Protocol Version 4 (TCP/IPv4)**.

Switched from **Obtain an IP address automatically** to **Use the following IP address**.

Entered the manual settings:

IP Address: 192.168.1.50

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.1.1

Saved the configuration and tested connectivity by opening a browser and searching on Google.

Test Result:

Status: Successful. The device retained full internet access because 192.168.1.50 lies within the valid subnet range of the router and does not conflict with existing connected devices.

After successful : Settings were successfully reverted back to **DHCP (Obtain IP automatically)** to avoid future address conflicts.