Lead Drop API (New ERP)

ERP System — API Documentation

Table of Contents

Lead Drop API (New ERP) 1

1. Endpoint 1
2. Authentication 2
3. Request Body 2
4. Response 5
5. Behaviour Notes 7
6. Common Error Messages 7
7. cURL 8
8. Migration Notes (Old ERP → New ERP) 8

Lead Drop API (New ERP)

Public / external-client API to capture a lead ("drop a lead") from a website, landing page, or ad platform into the new ERP. This replaces the legacy `onecrm.co.in/api/student/store` endpoint.

---

1. Endpoint

Method	`POST`
Path	`/api/v1/leads/drop`
Content-Type	`application/json`
Accept	`*/*`

Base URLs

Environment	Base URL
QA / Testing	https://erp-system.talentedge.dev

Environment	Base URL
Production	'https://api.onecrm.co.in/api/v1/leads/drop'

Full QA URL: https://erp-system.talentedge.dev`/api/v1/leads/drop`

---

2. Authentication

The endpoint is restricted to authenticated **external clients**. Authentication is done with two request **headers** — a logical client id and a shared secret token. The token is sent in plaintext over TLS and is compared server-side against a stored BCrypt hash.

Header	Required	Description	Example
`X-Client-Id`	Yes	Logical client id issued by the ERP team. For website drops use `WEBSITE`.	`WEBSITE`
`X-Token`	Yes	Shared secret token for that client.	`6c5b4441b2c13156a87cbd9uvbsd87vgsd8vsiduv35148760b5711cff0b` `(This is only dev token, contact tech team for actual production token)`

Tokens are environment-specific. Use the QA token in QA and the production token in production.

Requests with a missing or invalid client id/token are rejected before reaching the handler (`401 Unauthorized`).

---

3. Request Body

The request is a single JSON object. **String keys such as source / media / campaign are matched exactly (case-insensitive) against ERP master data** — the value must already exist in the ERP for that master.

3.1 Mandatory fields

Field	Type	Description
`subEntityCode`	string	Matched to `SubEntity.shortCode`. University / sub-entity short code from ERP.
`source`	string	Matched to Source master (`source_name`). Must exist in ERP.
`media`	string	Matched to Media master (`media_name`). Must exist in ERP.
`campaign`	string	Matched to Campaign master (`campaign_name`). Must exist in ERP.
`firstName`	string	First name of the lead. Cannot be blank.

Conditionally mandatory: `email` and/or `mobileNumber` may be required depending on the sub-entity's **lead-uniqueness configuration**. If the config marks a field as a uniqueness key, that field must be present (see §5). At minimum, supply enough identity to satisfy that config.

3.2 Optional fields

Field	Type	Description
`middleName`	string	Middle name.
`lastName`	string	Last name.
`dateOfBirth`	long (epoch seconds)	Date of birth as a Unix timestamp.
`gender`	enum	One of `MALE`, `FEMALE`, `OTHERS`.
`email`	string	Valid email id. Validated for format.
`alternateEmail`	string	Valid alternate email id. Validated for format.
`mobileNumber`	string	Valid mobile number — international (e.g. `+919876543210`) or national format.
`alternateMobileNumber`	string	Valid alternate mobile number. Must differ from `mobileNumber`.
`courseNameOrCode`	string	Course `short_code` **or** name under the sub-entity. Short code is tried first.

Field	Type	Description
		Unknown value does not block the drop (course left unset).
`specializationNameOrCode`	string	Specialization `short_code` or name under the resolved course. Short code first.
`batchNameOrCode`	string	Batch `short_code` or name. Short code first.
`studentCategory`	string	`Domestic` or `International/NRI`.
`countryNameOrCode`	string	Country `short_code` or name.
`stateNameOrCode`	string	State `short_code` or name within the country.
`cityNameOrCode`	string	City `short_code` or name within the state.
`pincode`	string	Free-text postal code, stored as-is. Max 10 chars; letters, digits and spaces only.
`firstReferrerUrl`	string	First referrer URL (attribution).
`landingPageUrl`	string	Landing page URL (attribution).
`platformUrl`	string	Platform URL (attribution).
`extraFields`	JSON	Arbitrary JSON object of custom key/values, stored on the UTM log.
`clickId`	string	Ad-platform click id (attribution).

Non-blocking resolution: optional lookups (course, specialization, batch, student category, country/state/city) never fail the request. If a value can't be matched to ERP master data, the lead is still created and that field is simply left unset. Location resolves top-down — an unresolved country leaves state/city unset.

3.3 Minimal request example

```
{
  "subEntityCode": "BDU",
  "source": "BDU",
  "media": "Direct",
  "campaign": "Whatsapp",
  "firstName": "yogendra ",
  "email": "yogendra@example.com",
  "mobileNumber": "9039507777"
}
```

3.4 Full request example

```
{
  "subEntityCode": "BDU",
  "source": "BDU",
  "media": "Direct",
  "campaign": "Whatsapp",
  "firstName": "Yogendra",
  "middleName": "K",
  "lastName": "Mahajan",
  "dateOfBirth": 631152000,
  "gender": "MALE",
  "email": "yogendra@example.com",
  "alternateEmail": "yogendra.alt@example.com",
  "mobileNumber": "9039507777",
  "alternateMobileNumber": "+919812345678",
  "courseNameOrCode": "MBA",
  "specializationNameOrCode": "FIN",
  "batchNameOrCode": "2026-JAN",
  "studentCategory": "Domestic",
  "countryNameOrCode": "IN",
  "stateNameOrCode": "MH",
  "cityNameOrCode": "Pune",
  "pincode": "411001",
  "firstReferrerUrl": "https://google.com",
  "landingPageUrl": "https://site.com/mba",
  "platformUrl": "https://site.com",
  "clickId": "gclid_abc123",
  "extraFields": { "utm_term": "mba online", "adgroup": "brand" }
}
```

---

4. Response

All responses use the standard ERP envelope:

```
{
  "message": "string",
  "status": "SUCCESS | FAILURE",
  "data": { ... }
}
```

4.1 Success — `201 Created`

`message` is always `"Lead captured successfully"` and `status` is `"SUCCESS"` for both new and existing leads.

`data` fields

Field	Type	Description
`leadId`	long	ID of the created or matched lead.
`opportunityId`	long	ID of the created / updated opportunity.
`isNewLead`	boolean	`true` when a brand-new lead was created; `false` when an existing lead was matched (re-enquiry or additional opportunity).
`utmLogRecorded`	boolean	Always `true` — every drop appends an `opportunity_utm_logs` row with this request's attribution and optional URL / click fields.

New lead created


```
{
  "message": "Lead captured successfully",
  "status": "SUCCESS",
  "data": {
    "leadId": 176,
    "opportunityId": 176,
    "isNewLead": true,
    "utmLogRecorded": true
  }
}
```


Existing lead (re-enquiry / additional opportunity)


```
{
  "message": "Lead captured successfully",
  "status": "SUCCESS",
  "data": {
    "leadId": 176,
    "opportunityId": 176,
    "isNewLead": false,
    "utmLogRecorded": true
  }
}
```


4.2 Failure

Validation and lookup failures return the same envelope with `status: "FAILURE"` and a human-readable `message` (HTTP `400 Bad Request` for validation / invalid-request errors, `401` for auth). Example:


```
{
  "message": "We could not find this source. Please check the name with your
administrator.",
  "status": "FAILURE",
```

```
  "data": null
}
```

---

5. Behaviour Notes

- **New vs. Re-Enquired.** The system sets the opportunity's primary (call) status automatically:
  - New lead → **"New Lead"**.
  - Existing lead with an existing opportunity → **"Re-Enquired"** (a re-enquiry). The re-enquiry updates course details and sets the re-enquire date.
- **One opportunity per lead** (scoped by sub-entity when the uniqueness config uses `SUB_ENTITY` scope). The `source` / `media` / `campaign` stored on the opportunity row are **first-touch** and are not overwritten on re-enquiry.
- **Terminal statuses protected.** If the matched opportunity's call status is already **"Registered"** or **"Enrolled"**, a re-enquiry drop records the UTM attribution **only** — it does not change the opportunity's status or data.
- **Uniqueness matching** uses the sub-entity's `LeadUniquenessConfig` (mobile and/or email, at GLOBAL or SUB_ENTITY scope). This decides whether `mobileNumber` / `email` are required and how an existing lead is matched.
- **Attribution log.** Every successful drop appends an `opportunity_utm_logs` row carrying `source`, `media`, `campaign`, `firstReferrerUrl`, `landingPageUrl`, `platformUrl`, `clickId`, and `extraFields`.

---

6. Common Error Messages

Message	Cause
`First name cannot be empty`	`firstName` present but blank.
`We could not find this sub entity. Please check and try again.`	`subEntityCode` does not match any active `SubEntity.shortCode`.
`We could not find this source. Please check the name with your administrator.`	`source` not found in Source master.
`We could not find this media. Please check the name with your administrator.`	`media` not found in Media master.
`We could not find this campaign. Please check the name with your administrator.`	`campaign` not found in Campaign master.

Message	Cause
`Mobile number is required as per uniqueness configuration`	Uniqueness config requires mobile, but none supplied.
`Email is required as per uniqueness configuration`	Uniqueness config requires email, but none supplied.
`Sub entity ID is required when uniqueness scope is SUB_ENTITY`	Sub-entity could not be resolved under SUB_ENTITY scope.
`Primary and alternate mobile number must differ`	`mobileNumber` and `alternateMobileNumber` normalise to the same number.
`A lead with this mobile number already exists`	GLOBAL-scope uniqueness on mobile violated.
`A lead with this email already exists`	GLOBAL-scope uniqueness on email violated.
`Invalid email ID passed` / `Invalid alternate email ID passed`	Email format invalid.
`Mobile number must be a valid international number (e.g. +919876543210) or national number`	Mobile format invalid.
`Pincode must not exceed 10 characters` / `Pincode may contain only letters, digits and spaces`	`pincode` fails validation.

---

7. cURL

```
curl --location 'https://qa-erp-system.talentedge.dev/api/v1/leads/drop' \
  --header 'accept: */*' \
  --header 'Content-Type: application/json' \
  --header 'X-Client-Id: WEBSITE' \
  --header 'X-Token:
6c5b4441b2c13156a87cbd9bc4f30b60178e587f801f3235148760b5711cff0b' \
  --data-raw '{
    "subEntityCode": "BDU",
    "source": "BDU",
    "media": "Direct",
    "campaign": "Whatsapp",
    "firstName": "yogendra ",
    "email": "yogendra@example.com",
    "mobileNumber": "9039507777"
  }'
```

8. Migration Notes (Old ERP → New ERP)

Old ERP (`/api/student/store`)	New ERP (`/api/v1/leads/drop`)
Auth: `token` header	Auth: `X-Client-Id` + `X-Token` headers
`first_name`	`firstName`
`last_name`	`lastName` (old "middle name" note no longer applies)
`contact_no`	`mobileNumber`
`email_id`	`email`
`gender` (string)	`gender` (enum: `MALE` / `FEMALE` / `OTHERS`)
`city` / `state` / `country` (names)	`cityNameOrCode` / `stateNameOrCode` / `countryNameOrCode`
`course`	`courseNameOrCode`
`source` / `media` / `campaign`	same (matched to ERP master)
`highest_qualification`	*not in this API*
`c1`–`c5` (custom values)	`extraFields` (JSON object)
`uni_code` (university short code)	`subEntityCode`
`ref_url`	`firstReferrerUrl` (also `landingPageUrl`, `platformUrl`, `clickId`)
Response: `status: true/false`, `code`, `message`, `data.lead_id`	Response: `status: SUCCESS/FAILURE`, `message`, `data.leadId` + `opportunityId` + `isNewLead` + `utmLogRecorded`
Duplicate → `"Re-Enquired"` in `message`	Duplicate → `status: SUCCESS`, `data.isNewLead: false`; status set to "Re-Enquired" internally