

# CORVUS LED

## Adjustable Square LED Downlight



<b>Type:</b>	A range of square adjustable LED downlights for accent lighting applications.
<b>Specification:</b>	Aluminium faceted reflector with tempered glass. Light beam 60°. Body in cast aluminium in white finish. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
<b>Application:</b>	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corvus LED1x1600 D326 T840 CLR	145x145(138x138)x115	50000	1597	14	80+	4000	2,00
Corvus LED1x2300 D327 T840 CLR	145x145(138x138)x115	50000	2216	21	80+	4000	2,00
Corvus LED1x3000 D328 T840 CLR	145x145(138x138)x115	50000	2990	28	80+	4000	2,00

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
CLR-	Clear glass
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
RAL-	RAL colours

### CORVUS LED1X3000 D328 T840 CLR

