

JETTA R

Recessed Indirect Luminaire



Type:	Modern design indirect LED or compact fluorescent luminaire with light source hidden under a perforated diffuser. The light is reflected across two parabolic reflectors to allow a comfortable and glare-free lighting effect.
Specification:	White painted perforated diffuser with UV stable opal film to give soft light distribution. Two parabolic reflectors. Fully enclosed white steel body. Luminaire is plastic-wrapped and boxed individually.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm.
Application:	Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output ⁺ , lm Ta=25°C	System power ⁺ , W	CRI (Ra)	CCT, K	Weight, kg
Jetta R LED1x3500 D081 T840	595x595x100	50000	3466	39	80+	4000	4,00
Jetta R LED1x4900 D082 T840	595x595x100	50000	4865	57	80+	4000	4,00

* Tolerance range for optical and electrical data: ±10 %

Type	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Jetta 236 C49	2x36 (2G11)	595x595x100	4	84
Jetta 240 B44	2x40 (2G11)	595x595x100	4	84
Jetta 255 B40	2x55 (2G11)	595x595x100	4	118

Options available on request:

HF-	High Frequency control gear
DIM-	Dimmable ballast 1-10V
SDIM-	Switch-control/dimming
DALI-	DALI driver
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
WIE-	3-pole Wieland or similar connector
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

JETTA R LED1X3500 D081 T840

