

LEVANTO

T8 Recessed Luminaire with Opal Diffuser



Type:	Traditional recessed luminaire with opal diffuser for the majority of applications.
Specification:	UV stable opal diffuser. Fully enclosed white steel body. Luminaire is plastic-wrapped and packed in twin boxes.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm.
Application:	Indoor. Office buildings, shops and other commercial environments.

Type	Description	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Levanto 218 H61	IP20	2x18 (G13)	595x295x85	2,4	42
Levanto 318 L51	IP20	3x18 (G13)	595x595x72	3,7	63
Levanto 418 B07	IP20	4x18 (G13)	595x595x72	3,7	84
Levanto 236 H62	IP20	2x36 (G13)	1195x295x85	3,9	84
Levanto 336 L53	IP20	3x36 (G13)	1195x595x85	7,2	126
Levanto 436 H63	IP20	4x36 (G13)	1195x595x85	7,2	168

- Options available on request:**
- HF- High Frequency control gear
 - DIM- Dimmable ballast 1-10V
 - SDIM- Switch-control/dimming
 - DALI- DALI ballast
 - EMG- Emergency version 1 hour
 - EM3- Emergency version 3 hours
 - 5TB- 5 way terminal block for loop feed and ease of wiring
 - WIE- 3-pole Wieland or similar connector (subject to minimum quantity)
 - NCP- Low Power Factor
 - LT80- Opal diffuser with 80% light transmission

