

# AURIGA C LED

## Recessed LED Downlight with Deep Glass Cover



<b>Type:</b>	A unique LED downlight with deep diffuser for most applications.
<b>Specification:</b>	Faceted aluminium reflector with white powder coated aluminium ring. Deep clear glass cover. Light beam 40°. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
<b>Application:</b>	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Auriga C LED1x1600 D336 T840 CLR	ø195(176)x140	50000	1597	14	80+	4000	0,80
Auriga C LED1x2300 D337 T840 CLR	ø195(176)x140	50000	2216	21	80+	4000	0,80
Auriga C LED1x3000 D338 T840 CLR	ø195(176)x140	50000	2990	28	80+	4000	0,80

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
CLR-	Clear glass
OP-	Opal diffuser
MPRZ-	Microprismatic diffuser
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

### AURIGA C LED1X2300 D337 T840 CLR

