

MONSOON

T8 Surface Luminaire with Glossy Parabolic Louvre and Ribbed Cross Blades



MONSOON 236 D16 HF

Type:	Traditional surface mounted T8 luminaire with a modern low profile body. Premium quality at competitive prices.
Specification:	Shiny parabolic louvre with ribbed cross blades. Louvre is fitted into the body with a locking safety clip for maximum stability. Nylon retainers enable louvre to swing down for maintenance and tube replacement. Number of cross blades is optional from 5 to 11 for a better glare protection. Fully enclosed painted steel body, wiring is concealed and not visible from ground level. Luminaire is plastic-wrapped and packed in twin boxes.
Installation:	Surface luminaire designed to be fixed to ceiling of any type.
Application:	Indoor. Office buildings, shops and other commercial environments.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Monsoon 218 D15	2x18 (G13)	635x360x66	2,4	42
Monsoon 418 B08 STD	4x18 (G13)	635x635x66	3,6	84
Monsoon 418 B08 STD 7CR	4x18 (G13)	635x635x66	3,6	84
Monsoon 418 B08 STD 9CR	4x18 (G13)	635x635x66	3,6	84
Monsoon 418 B08 STD 11CR	4x18 (G13)	635x635x66	3,6	84
Monsoon 236 D16	2x36 (G13)	1245x360x66	4	84
Monsoon 258 O44	2x58 (G13)	1545x635x66	5,5	134
Monsoon 436 G77	4x36 (G13)	1245x635x66	7	168

Options available on request:

HF-	High Frequency control gear	5TB-	5 way terminal block for loop feed and ease of wiring
DIM-	Dimmable ballast	MAT-	Matted reflector
SDIM-	Switch-control/dimming	7CR-	Louvre with 7 cross blades
DALI-	DALI ballast	9CR-	Louvre with 9 cross blades
EMG-	Emergency version 1 hour	11CR-	Louvre with 11 cross blades
EM3-	Emergency version 3 hours	NCP-	Low Power Factor