

DUBHE S&M

Wall Mounted Bulkhead



DUBHE M LED1x500 D053 T840 LOUVER

Type: A non-corrosive durable luminaire. IP54 - water and dust protection for use in adverse conditions.

Specification: The diffuser is made of polycarbonate.
Die-cast aluminium in dark grey finish.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for surface mounting on walls or ceiling.

Application: Outdoor. Building exteriors and other areas.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Dubhe S 1E27 C420	E27 (max. 40W)	Ø190x60	1,10	-
Dubhe S 1E27 C420 LOUVER	E27 (max. 40W)	Ø190x65	1,20	-
Dubhe M 1E27 C423	E27 (max. 60W)	Ø270x80	1,30	-
Dubhe M 1E27 C423 LOUVER	E27 (max. 60W)	Ø270x85	1,50	-

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Dubhe S LED1x300 C421 T830	Ø190x60	50000	215	4	80+	3000	1,20
Dubhe S LED1x300 C421 T830 LOUVER	Ø190x65	50000	132	4	80+	3000	1,30
Dubhe M LED1x500 C424 T830	Ø270x80	50000	423	8	80+	3000	1,40
Dubhe M LED1x900 D052 T840	Ø270x80	50000	835	10	80+	4000	1,40
Dubhe M LED1x400 C425 T830 LOUVER	Ø270x85	50000	325	8	80+	3000	1,60
Dubhe M LED1x500 D053 T840 LOUVER	Ø270x85	50000	451	7	80+	4000	1,60

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

T830- Colour temperature 3000K

T840- Colour temperature 4000K