

AURIGA LED

Recessed LED Downlight with Clear Glass Cover



Type: Traditional LED downlight with clear diffuser for most applications.

Specification: Faceted aluminium reflector with white powder coated aluminium ring. Clear glass cover. Light beam 60°. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for plasterboard or similar types of ceiling, requires a cut-out.

Application: Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Auriga LED1x1600 D329 T840 CLR	ø195(165)x100	50000	1597	14	80+	4000	0,80
Auriga LED1x2300 D330 T840 CLR	ø195(165)x100	50000	2216	21	80+	4000	0,80
Auriga LED1x3000 D331 T840 CLR	ø195(165)x100	50000	2990	28	80+	4000	0,80

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
CLR-	Clear glass
OP-	Opal diffuser
MPRZ-	Microprismatic diffuser
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

AURIGA LED1X2300 D330 T840 CLR

