

CETUS OP/CLR

IP44 Rounded Profile Luminaire



CETUS 1E27 J46 CLR

Type:	Surface-mounted fluorescent luminaire with rounded profile.
Specification:	Transparent or frosted glass IP44 diffuser with quick fix lock. White thermoplastic body with reflector. Luminaire is packed 5 pcs/box.
Installation:	Designed to be fixed onto ceiling or walls of any type, including flammable surfaces.
Application:	Indoor. Ideal for common areas in hospitals, colleges and other similar institutions.

Name	Lamp (W) and holder	IP level	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Cetus 1E27 J46 CLR	max. 100W (E27)	IP44	Ø245x85	0,75	-
Cetus 209 M21 CLR	2x9 (TC-S, G23)	IP44	Ø245x85	1,15	32
Cetus 113 J52 CLR	1x13 (G24d-1)	IP44	Ø245x85	1,15	19
Cetus 118 J47 CLR	1x18 (G24d-2)	IP44	Ø245x85	1,2	26
Cetus 126 J48 CLR	1x26 (G24d-3)	IP44	Ø245x85	1,25	34
Cetus 116 P84 CLR HF	1x16 (GR10Q)	IP44	Ø245x85	1,2	17

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Cetus LED1x500 C441 T830 OP ECO	Ø245x85	50000	434	8	80+	3000	1,10

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

HF-	High Frequency control gear
DIM-	Dimmable ballast
DALI-	DALI ballast
OP-	Frosted glass diffuser
CLR-	Clear glass diffuser
MW-	MW sensor
5TB-	5 way terminal block for loop feed and ease of wiring
NCP-	Low Power Factor
T830-	Colour temperature 3000K

CETUS LED1X500 C441 T830 OP ECO

