

BOREAS CL

Discharge Floodlight with Clips and Asymmetric Reflector



Type:	A range of discharge floodlights with asymmetric reflector and aluminium clips. IP65 - water and dust protection for use in adverse conditions.
Specification:	Faceted asymmetric reflector in anodized aluminium. Clear glass diffuser with aluminium clips. Body in aluminium in dark grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for any horizontal and/or vertical surfaces.
Application:	Outdoor. Efficient floodlight for building facades and perimeters, billboards, displays, car parks, etc.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Boreas 170 K52 CL HI	1x70 W(RX7s)	445x275x130	3,6	83,5
Boreas 1150 K53 CL HI	1x150 W(RX7s)	445x275x130	4,5	168
Boreas 170 K52 CL HS	1x70 W(RX7s)	445x275x130	3,6	83,5
Boreas 1150 K53 CL HS	1x150 W(RX7s)	445x275x130	4,5	168

- Options available on request:**
- HF- High Frequency control gear
 - TIM- Timed ignitor
 - HI- For metal halide lamp
 - HS- For high pressure sodium lamp

BOREAS 1150 K53 CL HI

