

LEVANTO & MARENCO

T5 Surface Luminaire with framed Opal or Prismatic Diffuser



MARENCO 414 S59

Type:	Traditional surface T5 luminaire with opal or prismatic diffuser for most applications.
Specification:	UV stable opal (Levanto) or prismatic (Marenco) diffuser fitted to the body with a steel frame. Fully enclosed white steel body. Luminaire is plastic-wrapped and packed in twin boxes.
Installation:	Surface luminaire designed to be fixed to ceiling of any type or suspended.
Application:	Indoor. Office buildings, shops and other commercial environments.

Name	Description	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Marenco 214 S55	IP40, framed	2x14 (G5)	595x295x57	1,2	31
Marenco 224 S56	IP40, framed	2x24 (G5)	595x295x57	1,2	49
Marenco 314 S57	IP40, framed	3x14 (G5)	595x595x57	2	47
Marenco 324 S58	IP40, framed	3x24 (G5)	595x595x57	2	74
Marenco 414 S59	IP40, framed	4x14 (G5)	595x595x57	2	62
Marenco 424 S60	IP40, framed	4x24 (G5)	595x595x57	2	98
Marenco 128 S61	IP40, framed	1x28 (G5)	1210x143x57	1,6	30,5
Marenco 154 S62	IP40, framed	1x54 (G5)	1210x143x57	1,6	58
Marenco 228 S63	IP40, framed	2x28 (G5)	1210x143x57	1,6	60
Marenco 254 S64	IP40, framed	2x54 (G5)	1210x143x57	1,6	115
Marenco 228 S65	IP40, framed	2x28 (G5)	1210x295x57	2,6	60
Marenco 254 S66	IP40, framed	2x54 (G5)	1210x295x57	2,6	115
Marenco 328 S67	IP40, framed	3x28 (G5)	1210x295x57	3	90,5
Marenco 354 S68	IP40, framed	3x54 (G5)	1210x295x57	3	173

Name	Description	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Levanto 214 S69	IP40, framed	2x14 (G5)	595x295x57	1,2	31
Levanto 224 S70	IP40, framed	2x24 (G5)	595x295x57	1,2	49
Levanto 314 S71	IP40, framed	3x14 (G5)	595x595x57	2	47
Levanto 324 S72	IP40, framed	3x24 (G5)	595x595x57	2	74
Levanto 414 S73	IP40, framed	4x14 (G5)	595x595x57	2	62
Levanto 424 S74	IP40, framed	4x24 (G5)	595x595x57	2	98
Levanto 128 S75	IP40, framed	1x28 (G5)	1210x143x57	1,6	30,5
Levanto 154 S76	IP40, framed	1x54 (G5)	1210x143x57	1,6	58
Levanto 228 S77	IP40, framed	2x28 (G5)	1210x143x57	1,6	60
Levanto 254 S78	IP40, framed	2x54 (G5)	1210x143x57	1,6	115
Levanto 228 S79	IP40, framed	2x28 (G5)	1210x295x57	2,6	60
Levanto 254 S80	IP40, framed	2x54 (G5)	1210x295x57	2,6	115
Levanto 328 S81	IP40, framed	3x28 (G5)	1210x295x57	3	90,5
Levanto 354 S82	IP40, framed	3x54 (G5)	1210x295x57	3	173

Options available on request:

DIM-	Dimmable ballast 1-10V
SDIM-	Switch-control/dimming
DALI-	DALI ballast
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
5TB-	5 way terminal block with two holes (for in and out going cable)
MPRZ-	Microprismatic diffuser
LT80-	Opal diffuser with 80% light transmission

LEVANTO 228 S79

