

PERSEUS C LED

Recessed LED Downlight with IP65 Ingress Protection



Type:	A recessed LED downlight for maximum protection and use in adverse conditions.
Specification:	Faceted aluminium reflector with clear glass cover. White aluminium body. Silicon gasket. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Dust and moisture proof luminaire, ideal for environments subject to humidity and excessive dust.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Perseus C LED1x2300 D028 T840 CLR	Ø225(205)x125	50000	2224	20	80+	4000	1,20
Perseus C LED1x3100 D029 T840 CLR	Ø225(205)x125	50000	3037	29	80+	4000	1,20
Perseus C LED1x4400 D348 T840 CLR	Ø225(205)x125	50000	4373	42	80+	4000	1,20

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
CLR-	Clear glass
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
RAL-	RAL colours

PERSEUS C LED1X3100 D029 T840 CLR

