CETUS P LED

IP65 Rounded Profile LED Luminaire with Opal Diffuser





| Type: | A surface-mounted LED luminaire with rounded profile and high impact resistance. | | | | | | |
|----------------|---|--|--|--|--|--|--|
| Specification: | Opal polycarbonate diffuser with screw fixing. Sealed to IP65. | | | | | | |
| | White aluminium body. High impact resistance. | | | | | | |
| | Luminaire is plastic-wrapped and boxed individually. | | | | | | |
| Installation: | Designed to be fixed onto ceiling or walls of any type, including flammable surfaces. | | | | | | |
| Application: | Ideal for corridors, hospitals, colleges and other similar institutions. | | | | | | |

| Name | Overall dimensions (LxWxH), mm | Lifetime | Luminaire output*, lm Ta=25°C | System power*, W | CRI (Ra) | сст, к | Weight, kg |
|-------------------------------|--------------------------------------|----------|-------------------------------------|---------------------|-------------|--------|---------------|
| Cetus P LED1x800 C139 T730 OP | Ø192x75 | 40000 | 800 | 10 | 70+ | 3000 | 0.90 |

 $^{^{\}ast}$ Tolerance range for optical and electrical data: $\pm 10~\%$

Options available on request:
OP- Opal diffuser
T730- Colour temperature 300 Colour temperature 3000K

CETUS P LED1X800 C139 T730 OP

