## TAURUS Deluxe LED Emergency Exit Sign





Surface/suspended double-sided LED exit sign for both mains and emergency operations. One or three hour operation with a recharge time of 24 hours.

Ambient temperature: 0°C to +40°C.
Recognition distance 30 m.

Specification:

Durable transparent PMMA diffuser.
Extruded aluminium silver body with LED status indicator. High-temperature nickel-cadmium batteries.
Luminaire is plastic-wrapped and boxed individually.

Installation: Designed to be fixed onto ceiling/walls of any type, including flammable surfaces, or suspended.

Application: For informational purposes when electricity supply fails. Suitable for escape routes and open areas.

<sup>\*</sup>Supplied with legend kit ("Exit", "Left" and "Right")

Name	Lamp type	Operating time, hours	IP level	Illumination modes	Overall dimensions (LxWxH), mm	Weight, kg
TAURUS 1H G05 Deluxe	1,2W LED	1	IP41	Non-maintained	315x48x243	1,25
TAURUS 3H G07 Deluxe	1,2W LED	3	IP41	Non-maintained	315x48x243	1,30
TAURUS 1P G08 Deluxe	1,2W LED	1	IP41	Maintained	315x48x243	1,20
TAURUS 3P G10 Deluxe	1,2W LED	3	IP41	Maintained	315x48x243	1,25
TAURUS CEBLED C339 Deluxe	1.2W I FD	X	IP41	Central battery	315x48x243	1.25

## Options available on request:

TEST- Manual test button

AUT- The fitting is equipped with an autonomous testing system

CEB- The fitting is equipped with electronic AC/DC ballast compatible with any central battery system

CLV- Fitting to low voltage central battery system CEBLV

EMS- The emergency monitoring system