

BREEZE DPAR

T5 & T8 Surface Luminaire with Double Parabolic Louvre



| | |
|----------------|---|
| Type: | Surface mounted T5 or T8 luminaire with a double parabolic louvre. |
| Specification: | Shiny double parabolic louvre with 5 cross blades. Louvre is fitted into the body with locking safety clips for maximum stability. Fully enclosed painted steel body, wiring is concealed and not visible from ground level. Luminaire is plastic-wrapped and packed in twin boxes. |
| Installation: | Surface luminaire designed to be fixed to ceiling of any type. |
| Application: | Indoor. Office buildings, shops and other commercial environments. |

| Name | Lamp (W) and holder | Overall dimensions (LxWxH), mm | Weight, kg | Total wattage, W |
|----------------|---------------------|--------------------------------|------------|------------------|
| Breeze 418 H16 | 4x18 (G13) | 635x635x66 | 3,6 | 84 |
| Breeze 236 N24 | 2x36 (G13) | 1245x360x66 | 3,6 | 84 |
| Breeze 414 N25 | 4x14 (G5) | 635x635x66 | 2,8 | 62 |
| Breeze 424 N26 | 4x24 (G5) | 635x635x66 | 2,8 | 98 |
| Breeze 228 N27 | 2x28 (G5) | 1245x360x66 | 2,8 | 60 |
| Breeze 254 N28 | 2x54 (G5) | 1245x360x66 | 2,8 | 116 |

| | |
|-------------------------------|---|
| Options available on request: | |
| HF- | High Frequency control gear |
| DIM- | Dimmable ballast 1-10V |
| SDIM- | Switch-control/dimming |
| DALI- | DALI ballast |
| EMG- | Emergency version 1 hour |
| EM3- | Emergency version 3 hour |
| 5TB- | 5 way terminal block for loop feed and ease of wiring |
| MAT- | Matted reflector |
| NCP- | Low Power Factor |

