

LYRA R LED

Decorative LED Luminaire



Type: A decorative and modern LED luminaire in four sizes to fit wide range of applications.

Specification: Opal acrylic diffuser.
White powder coated body and recessed mounting frame with quick lock system.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for plasterboard or similar type of ceiling, requires a cut-out.

Application: Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Lyra R LED1x1800 D083 T840 OP LT80	Ø320x180	50000	1798	19	80+	4000	4,00
Lyra R LED1x2600 D084 T840 OP LT80	Ø320x180	50000	2526	27	80+	4000	4,00
Lyra R LED1x3300 D085 T840 OP LT80	Ø470x180	50000	3251	31	80+	4000	6,80
Lyra R LED1x4500 D086 T840 OP LT80	Ø470x180	50000	4493	44	80+	4000	6,80
Lyra R LED1x5900 D087 T840 OP LT80	Ø620x190	50000	5849	55	80+	4000	10,00
Lyra R LED1x7000 D088 T840 OP LT80	Ø620x190	50000	6985	67	80+	4000	10,00
Lyra R LED1x8400 D089 T840 OP LT80	Ø920x210	50000	8332	80	80+	4000	14,00
Lyra R LED1x10200 D090 T840 OP LT80	Ø920x210	50000	10116	100	80+	4000	14,00

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
TW-	Tunable white
BLT-	Bluetooth unit (for wireless control via mobile device)
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
OP LT80-	Opal diffuser with 80% light transmission
STB-	5 way terminal block with two holes (for in and out going cable)
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

LYRA R LED1X4500 D086 T840 OP LT80

