

# KAPPA

## A Miniature Floodlight for Halogen Lamps



**KAPPA 1GU10 Q88 LONG**

**Type:** A range of miniature wall mounted luminaires with IP65 protection.

**Specification:** Tempered glass diffuser.  
Die-cast aluminium body in dark grey finish.  
Luminaire is plastic-wrapped and boxed individually.

**Installation:** Suitable for surface mounting on walls or ceiling.

**Application:** Outdoor. Building exteriors and other areas.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
KAPPA 1GU10 Q87	max 1x50W (GU10)	Ø70x150x210	0,7	-
KAPPA 1GU10 Q88 LONG	max 1x50W (GU10)	Ø70x150x605	1,2	-

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Kappa LED1x400 B678 T840	Ø70x150x210	30000	350	5	80+	4000	1,40
Kappa LED1x400 B678 T840 L90	Ø70x150x210	30000	350	5	80+	4000	1,40
Kappa LED1x400 B678 T840 L30	Ø70x150x210	30000	350	5	80+	4000	1,40
Kappa LED1x400 B679 LONG T840	Ø70x150x605	30000	350	5	80+	4000	1,40
Kappa LED1x400 B679 LONG T840 L90	Ø70x150x605	30000	350	5	80+	4000	1,40
Kappa LED1x400 B679 LONG T840 L30	Ø70x150x605	30000	350	5	80+	4000	1,40

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

T830- Colour temperature 3000K  
T840- Colour temperature 4000K  
L30- LED tube with 30° beam angle  
L90- LED tube with 90° beam angle