

# ARCTURUS LED

## Vandal Resistant LED Bulkhead for Wall Mounting



Type:	A range of vandal resistant LED bulkheads for outdoor wall applications. Designed to spread light sideways and sealed to IP65.
Specification:	The opal diffuser is made of impact resistant UV stable polycarbonate. Body in die-cast aluminium in dark grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for surface mounting on the walls.
Application:	Outdoor. Building exteriors and other areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Arcturus LED1x2800 E054 T850 OP	308x264x182	50 000	2759	27	80+	5000	2,40
Arcturus LED1x4000 E055 T850 OP	308x264x182	50 000	4020	41	80+	5000	2,40

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

DALI-	DALI driver
SDIM-	Switch-control/dimming
MW-	MW sensor
T830-	Colour temperature 3000K (subject to min. quantity)
T840-	Colour temperature 4000K
T850-	Colour temperature 5000K

### ARCTURUS LED1X2800 E054 T850 OP

