

# MARENCO

## T8 Recessed Luminaire with Prismatic Diffuser



Type:	Traditional recessed luminaire with prismatic diffuser for the majority of applications.
Specification:	UV stable prismatic diffuser. Fully enclosed white steel body. Luminaire is plastic-wrapped and packed in twin boxes.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm.
Application:	Indoor. Office buildings, shops and other commercial environments.

Type	Description	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Marenco 218 I33	IP20	2x18 (G13)	595x295x85	2,4	42
Marenco 318 L60	IP20	3x18 (G13)	595x595x72	3,7	63
Marenco 418 D09	IP20	4x18 (G13)	595x595x72	3,7	84
Marenco 236 K25	IP20	2x36 (G13)	1195x295x85	3,9	84
Marenco 336 L62	IP20	3x36 (G13)	1195x595x85	7,2	126
Marenco 436 K26	IP20	4x36 (G13)	1195x595x85	7,2	168

- Options available on request:**
- HF- High Frequency control gear
  - DIM- Dimmable ballast 1-10V
  - SDIM- Switch-control/dimming
  - DALI- DALI ballast
  - EMG- Emergency version 1 hour
  - EM3- Emergency version 3 hours
  - 5TB- 5 way terminal block for loop feed and ease of wiring
  - WIE- 3-pole Wieland or similar connector (subject to minimum quantity)
  - MPRZ- Microprismatic diffuser
  - NCP- Low Power Factor

