

ROUND LED

Recessed LED Downlight with Low Height Body



Type:	A low height LED downlight with opal diffuser to allow installation into low and restricted ceiling voids.
Specification:	Opal diffuser. Body in aluminium in white finish. Tool free spring clip installation. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output ⁺ , lm Ta=25°C	System power ⁺ , W	CRI (Ra)	CCT, K	Weight, kg
Round LED1x500 C218 T840 OP	Ø120(100)x12	30000	450	6	80+	4000	0,28
Round LED1x700 C219 T840 OP	Ø145(128)x12	30000	676	9	80+	4000	0,30
Round LED1x1000 C220 T840 OP	Ø170(150)x12	30000	917	12	80+	4000	0,32
Round LED1x1200 C221 T840 OP	Ø200(175)x12	30000	1125	15	80+	4000	0,46
Round LED1x1400 C222 T840 OP	Ø225(200)x12	30000	1351	18	80+	4000	0,54
Round LED1x1800 C223 T840 OP	Ø240(225)x12	30000	1800	24	80+	4000	0,60

⁺ Tolerance range for optical and electrical data: ±10 %

- Options available on request:**
- SDIM- Switch-control/dimming
 - DALI- DALI driver
 - EMG- Emergency version 1 hour
 - EM3- Emergency version 3 hours
 - OP- Opal diffuser
 - T830- Colour temperature 3000K
 - T840- Colour temperature 4000K

ROUND LED1X1200 C221 T840 OP

