

TUBE B & M

Wall Mounted Luminaire for Decorative Lighting



TUBE M SR LED1X1500 D049 T750 L45

TUBE M UP LED1X1500 D046 T750 L45

Type: A range of wall mounted luminaires with pleasing direct/indirect light distribution.

Specification: Tempered glass diffuser.
Die-cast aluminium body in dark grey finish.
Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for wall mounting on any vertical surface. TUBE SR version designed for mounting on ceiling.

Application: Outdoor. Ideal for numerous indoor and outdoor applications.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Tube B 270 R05	2x70 W(Rx7s)	Ø180x500	3,4	160
Tube B 2150 R06	2x150 W(Rx7s)	Ø180x500	3,9	340
Tube B SR 170 R08	1x70 W(Rx7s)	Ø180x220	2,2	80
Tube B SR 1150 R09	1x150 W(Rx7s)	Ø180x220	2,6	170
Tube M 235 R10	2x35 W(G12)	Ø155x460	2,8	88
Tube M UP 135 R12	1x35 W(G12)	Ø155x250	1,8	44
Tube M UP 170 R14	1x70 W(G12)	Ø155x250	2,2	80

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Tube M LED2x1100 D042 T750 L45	Ø155x464	50000	2271	21	70+	5000	3,20
Tube M LED2x1500 D043 T750 L45	Ø155x464	50000	3052	29	70+	5000	3,20
Tube M LED2x2000 D044 T750 L45	Ø155x464	50000	4111	43	70+	5000	3,20
Tube M LED2x1100 D042 T750 L60	Ø155x464	50000	2271	21	70+	5000	3,20
Tube M LED2x1500 D043 T750 L60	Ø155x464	50000	3052	29	70+	5000	3,20
Tube M LED2x2000 D044 T750 L60	Ø155x464	50000	4111	43	70+	5000	3,20
Tube M UP LED1x1100 D045 T750 L45	Ø155x250	50000	1136	11	70+	5000	2,20
Tube M UP LED1x1500 D046 T750 L45	Ø155x250	50000	1526	15	70+	5000	2,20
Tube M UP LED1x2000 D047 T750 L45	Ø155x250	50000	2055	23	70+	5000	2,20
Tube M UP LED1x1100 D045 T750 L60	Ø155x250	50000	1136	11	70+	5000	2,20
Tube M UP LED1x1500 D046 T750 L60	Ø155x250	50000	1526	15	70+	5000	2,20
Tube M UP LED1x2000 D047 T750 L60	Ø155x250	50000	2055	23	70+	5000	2,20
Tube M SR LED1x1100 D048 T750 L45	Ø155x250	50000	1136	11	70+	5000	2,20
Tube M SR LED1x1500 D049 T750 L45	Ø155x250	50000	1526	15	70+	5000	2,20
Tube M SR LED1x2000 D050 T750 L45	Ø155x250	50000	2055	23	70+	5000	2,20
Tube M SR LED1x1100 D048 T750 L60	Ø155x250	50000	1136	11	70+	5000	2,20
Tube M SR LED1x1500 D049 T750 L60	Ø155x250	50000	1526	15	70+	5000	2,20
Tube M SR LED1x2000 D050 T750 L60	Ø155x250	50000	2055	23	70+	5000	2,20

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

TIM-	Timed ignitor
HI-	For metal halide lamps
HF-	High Frequency control gear
DIM-	Dimmable ballast / driver 1-10V
DALI-	DALI ballast / driver
SDIM-	Switch-control/dimming
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
T750-	Colour temperature 5000K
L45-	45° beam angle
L60-	60° beam angle

TUBE M LED2X1500 D043 T750 L45

