

LEVANTO

T5 & T8 Surface Luminaire with Opal Diffuser



LEVANTO 236 A41

Type: Economical surface mounted T5/T8 luminaire with a modern low profile body and opal diffuser.

Specification: UV stable Opal diffuser is fitted to the body with a steel frame.
Fully enclosed painted steel body.
Luminaire is plastic-wrapped and packed in twin boxes.

Installation: Surface luminaire designed to be fixed to ceiling of any type.

Application: Indoor. Office buildings, shops, sport halls and other commercial environments.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Levanto 118 J95	1x18 (G13)	635x220x66	1,8	22
Levanto 218 J96	2x18 (G13)	635x220x66	2,2	42
Levanto 218 H75	2x18 (G13)	635x360x66	2,4	42
Levanto 318 L05	3x18 (G13)	635x360x66	2,8	64
Levanto 318 L06	3x18 (G13)	635x635x66	4	64
Levanto 418 A40	4x18 (G13)	635x635x66	4,2	84
Levanto 136 J97	1x36 (G13)	1245x220x66	3,2	42
Levanto 236 A41	2x36 (G13)	1245x220x66	3,8	84
Levanto 236 L27	2x36 (G13)	1245x360x66	4	84
Levanto 336 L03	3x36 (G13)	1245x360x66	4,6	126

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Levanto 114 L07	1x14 (G5)	635x220x66	1,4	16
Levanto 124 L08	1x24 (G5)	635x220x66	1,4	25
Levanto 214 L09	2x14 (G5)	635x220x66	1,5	31
Levanto 224 L10	2x24 (G5)	635x220x66	1,5	49
Levanto 214 L11	2x14 (G5)	635x360x66	2,2	31
Levanto 224 L12	2x24 (G5)	635x360x66	2,2	49
Levanto 314 L13	3x14 (G5)	635x360x66	2,3	46
Levanto 324 L14	3x24 (G5)	635x360x66	2,3	73
Levanto 314 L15	3x14 (G5)	635x635x66	3,1	46
Levanto 324 L16	3x24 (G5)	635x635x66	3,1	73
Levanto 414 L17	4x14 (G5)	635x635x66	3,2	62
Levanto 424 L18	4x24 (G5)	635x635x66	3,2	98
Levanto 128 L19	1x28 (G5)	1245x220x66	2,5	30
Levanto 154 L20	1x54 (G5)	1245x220x66	2,5	58
Levanto 228 L21	2x28 (G5)	1245x220x66	2,6	60
Levanto 254 L22	2x54 (G5)	1245x220x66	2,6	116
Levanto 228 L23	2x28 (G5)	1245x360x66	3,3	60
Levanto 254 L24	2x54 (G5)	1245x360x66	3,3	116
Levanto 328 L25	3x28 (G5)	1245x360x66	3,7	90
Levanto 354 L26	3x54 (G5)	1245x360x66	3,7	174

Options available on request:

- HF- High Frequency control gear
- DIM- Dimmable ballast
- SDIM- Switch-control/dimming
- DALI- DALI ballast
- EMG- Emergency version 1 hour
- EM3- Emergency version 3 hours
- 5TB- 5 way terminal block for loop feed and ease of wiring
- NCP- Low Power Factor
- OP LT80- Opal diffuser with 80% light transmission

LEVANTO 418 A40 HF

