## **BOREAS**

## **Asymmetric Floodlight for Discharge Lamps**







| Type:          | A high power asymmetric floodlight for discharge lamps. IP65 - water and dust protection for use in adverse conditions. |  |  |  |  |
|----------------|---|--|--|--|--|
| Specification: | Faceted asymmetric reflector in anodized aluminium. Tempered glass cover.   |  |  |  |  |
|                | Body in aluminium in dark grey finish.  |  |  |  |  |
|                | Luminaire is plastic-wrapped and boxed individually.  |  |  |  |  |
| Installation:  | Suitable for any horizontal and/or vertical surfaces.   |  |  |  |  |
| Application:   | Outdoor. Efficient floodlight for building facades and perimeters, billboards, displays, car parks, etc.                |  |  |  |  |

| Name                   | Lamp (W) and<br>holder | Overall dimensions (LxWxH), mm | Weight, kg | Total wattage,<br>W |
|------------------------|------------------------|--------------------------------|------------|---------------------|
| Boreas 11000 R71 AS HI | 1x1000 (E40)           | 530x500x195                    | 19,8       | 1075                |
| Boreas 11000 R71 AS HS | 1x1000 (E40)           | 530x500x195                    | 19,8       | 1075                |

## **Options available on request:**

TIM- Timed ignitor
HI- For metal halide lamp
HS- For high pressure sodium lamp
AS- Asymmetric reflector