

# OVAL

## Vandal Resistant Bulkhead



### OVAL B LED1X500 D056 T840 LOUVER

<b>Type:</b>	A non-corrosive vandal resistant luminaire. IP54 - water and dust protection for use in adverse conditions.
<b>Specification:</b>	The diffuser is made of impact resistant UV stable polycarbonate. Die-cast aluminium in dark grey finish. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Suitable for surface mounting on walls or ceiling.
<b>Application:</b>	Outdoor. Building exteriors and other areas.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
OVAL B 1E27 Q83	1x60W (max) (E27)	280x185x95	1,20	-
OVAL B 118 Q84	1x18W (G24d-2)	280x185x95	1,50	26
OVAL B 126 Q85	1x26W (G24d-3)	280x185x95	1,60	34
OVAL B 1E27 Q83 LOUVER	1x60W (max) (E27)	280x185x95	1,30	-
OVAL B 118 Q84 LOUVER	1x18W (G24d-2)	280x185x95	1,60	26
OVAL B 126 Q85 LOUVER	1x26W (G24d-3)	280x185x95	1,70	34
Oval S 1E27 C428	1x25W (max) (E27)	220x135x70	1,00	-
Oval S 1E27 C428 LOUVER	1x25W (max) (E27)	220x135x70	1,10	-

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Oval B LED1x500 C426 T830	280x185x95	50000	429	8	80+	3000	1,40
Oval B LED1x700 D054 T840	280x185x95	50000	603	7	80+	3000	1,50
Oval B LED1x900 D055 T840	280x185x95	50000	835	10	80+	4000	1,50
Oval B LED1x400 C427 T830 LOUVER	280x185x95	50000	330	8	80+	3000	1,50
Oval B LED1x500 D056 T840 LOUVER	280x185x95	50000	451	7	80+	4000	1,60
Oval S LED1x500 D473 T840	220x135x70	50000	436	5	80+	4000	1,10
Oval S LED1x500 D473 T840 LOUVER	220x135x70	50000	268	5	80+	4000	1,20

\* Tolerance range for optical and electrical data: ±10 %

#### Options available on request:

HF-	High Frequency control gear
IP65-	Water and dust protection IP65
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K