

CORONA M LED

Recessed LED Luminaire with Rectangular Diffuser



Type:	A recessed mounted LED luminaire with rectangular opal diffuser for most commercial lighting applications.
Specification:	Diffuser: high transmission opal (OP LT80). Fully enclosed white steel body. Luminaire is plastic-wrapped and boxed individually.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm.
Application:	Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corona M LED1x4000 D075 T840 OP LT80	595x595x75	50000	3996	40	80+	4000	3,00

* Tolerance range for optical and electrical data: ±10 %

- Options available on request:**
- SDIM- Switch-control/dimming
 - DALI- DALI driver
 - BLT- Bluetooth unit (for wireless control via mobile device)
 - EMG- Emergency version 1 hour
 - EM3- Emergency version 3 hours
 - OP LT80- Opal diffuser with 80% light transmission
 - W625- To fit 625x625 suspended ceiling (subject to minimum quantity)
 - IP44- IP44 protection degree
 - RAL- RAL colours
 - T830- Colour temperature 3000K
 - T840- Colour temperature 4000K

CORONA M LED1X4000 D075 T840 OP LT80

