

# LODOS S LED

## Decorative LED Luminaire



<b>Type:</b>	A decorative and modern LED luminaire in four sizes to fit wide range of applications.
<b>Specification:</b>	Opal acrylic diffuser. White powder coated body and gear tray with quick lock system. Luminaire is boxed individually.
<b>Installation:</b>	Surface luminaire is designed to be fixed to ceiling of any type or suspended. Wire suspension set is ordered separately.
<b>Application:</b>	Indoor. Office buildings, shops and other commercial environments.



Wire suspension set (Lodos S suspension KIT) is available on request.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Lodos S LED1x1800 D361 T840 OP LT80	Ø300x125	50000	1798	19	80+	4000	2,50
Lodos S LED1x2600 D362 T840 OP LT80	Ø300x125	50000	2526	27	80+	4000	2,50
Lodos S LED1x3300 D363 T840 OP LT80	Ø450x125	50000	3251	31	80+	4000	4,80
Lodos S LED1x4500 D364 T840 OP LT80	Ø450x125	50000	4493	44	80+	4000	4,80
Lodos S LED1x5900 D365 T840 OP LT80	Ø600x135	50000	5849	55	80+	4000	7,50
Lodos S LED1x7000 D366 T840 OP LT80	Ø600x135	50000	6985	67	80+	4000	7,50
Lodos S LED1x8400 D367 T840 OP LT80	Ø900x150	50000	8332	80	80+	4000	10,50
Lodos S LED1x10200 D368 T840 OP LT80	Ø900x150	50000	10116	100	80+	4000	10,50

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
TW-	Tunable white
BLT-	Bluetooth unit (for wireless control via mobile device)
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
OP LT80-	Opal diffuser with 80% light transmission
5TB-	5 way terminal block with two holes (for in and out going cable)
RAL-	RAL colours
SUS-	Suspended version
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

### LODOS S LED1X5900 D365 T840 OP

