

CRUX LED

Recessed LED Downlight with Opal Diffuser



Type:	Recessed LED downlight with opal diffuser for installations with minimum ceiling void.
Specification:	Aluminium reflector with white coated ring. Opal diffuser. Body in aluminium in white finish. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Crux LED1x1100 E307 T840 OP	ø200(185)x90	50000	1053	10	80+	4000	0,80
Crux LED1x1500 E308 T840 OP	ø200(185)x90	50000	1479	13	80+	4000	0,80
Crux LED1x2100 E309 T840 OP	ø200(185)x90	50000	2035	19	80+	4000	0,80
Crux LED1x1400 E310 T840 OP	ø235(220)x90	50000	1321	12	80+	4000	0,90
Crux LED1x1900 E311 T840 OP	ø235(220)x90	50000	1858	16	80+	4000	0,90
Crux LED1x2600 E312 T840 OP	ø235(220)x90	50000	2575	23	80+	4000	0,90

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
OP-	Opal diffuser
MPRZ-	Microprismatic diffuser
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

CRUX LED1X1500 E308 T840 OP

