

# CORONA Q LED

## Recessed LED Luminaire with Square Diffuser



**Type:** A recessed mounted LED luminaire with square opal diffuser for most commercial lighting applications.

**Specification:** Diffuser: high transmission opal (OP LT80).  
Fully enclosed white steel body.  
Luminaire is plastic-wrapped and boxed individually.

**Installation:** Fits 15-24mm exposed T-Bar ceiling 600x600mm.

**Application:** Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corona Q LED1x3200 E394 T840 OP LT80	595x595x70	50000	3144	31	80+	4000	5,00
Corona Q LED1x4500 E395 T840 OP LT80	595x595x70	50000	4416	45	80+	4000	5,00
Corona Q LED1x6400 E396 T840 OP LT80	595x595x70	50000	6311	61	80+	4000	5,00

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
TW-	Tunable white
BLT-	Bluetooth unit (for wireless control via mobile device)
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
OP LT80-	Opal diffuser with 80% light transmission
W625-	To fit 625x625 suspended ceiling (subject to minimum quantity)
IP44-	IP44 protection degree
RAL-	RAL colours
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

### CORONA Q LED1X4500 E395 T840 OP LT80

