

PRIZMA LED

High-Bay LED Luminaire with Prismatic Reflector



| | |
|-----------------------|--|
| Type: | Luminaire for high mounting applications with transparent prismatic reflector. |
| Specification: | Prismatic polycarbonate reflector. Protective cover can be supplied on request. Body in die-cast aluminium in dark grey finish. Luminaire is plastic-wrapped and boxed individually. |
| Installation: | Supplied with suspension hook for easy mounting. |
| Application: | Indoor. For use in halls, factories, shops and many other commercial applications. |



Protective cover (**COVER**) for glare control available on request. For more information check option list.

| Name | Overall dimensions (LxWxH), mm | Lifetime | Luminaire output*, lm Ta=25°C | System power*, W | CRI (Ra) | CCT, K | Weight, kg |
|-----------------------------|--------------------------------|----------|----------------------------------|------------------|----------|--------|------------|
| Prizma LED1x4100 D434 T840 | Ø410x425 | 50000 | 4088 | 34 | 80+ | 4000 | 3,50 |
| Prizma LED1x5800 D435 T840 | Ø410x425 | 50000 | 5718 | 51 | 80+ | 4000 | 3,50 |
| Prizma LED1x9000 D436 T840 | Ø510x540 | 50000 | 8915 | 84 | 80+ | 4000 | 5,80 |
| Prizma LED1x10900 D437 T840 | Ø510x540 | 50000 | 10851 | 107 | 80+ | 4000 | 5,80 |

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

| | |
|--------|--------------------------|
| SDIM- | Switch-control/dimming |
| DALI- | DALI driver |
| COVER- | Protective PC cover |
| T830- | Colour temperature 3000K |
| T840- | Colour temperature 4000K |
| T850- | Colour temperature 5000K |

PRIZMA LED1X5800 D435 T840

