

CASTLE

IP54 Classic-Shaped Park Lights



Type: A range of classic shaped park lights with a low light pollution.

Specification: Flat tempered glass diffuser with a clear top cap part made of UV stable PC material. Canopy in aluminium in dark grey finish. Gear tray is made of zinc plated steel. Luminaire is plastic-wrapped and boxed individually.

Installation: Post top installation with three screws on poles Ø60mm. Suggested mounting height from 3 to 5 meters. Suspended mounting versions are available on request.

Application: Outdoor. Suitable for many applications including parks, old cities path walks and public places.

| Name | Lamp (W) and holder | Overall dimensions (LxWxH), mm | Weight, kg | Total wattage, W |
|-----------------|---------------------|--------------------------------|------------|------------------|
| Castle 1E27 N73 | E27 (max.100 W) | 430x430x900 | 8,2 | |
| Castle 150 N74 | 1x50 (E27) | 430x430x900 | 9,6 | 62 |
| Castle 170 N75 | 1x70 (E27) | 430x430x900 | 9,6 | 85 |
| Castle 1100 N76 | 1x100 (E27) | 430x430x900 | 9,6 | 116 |
| Castle 1150 N77 | 1x150 (E27) | 430x430x900 | 10,2 | 168 |

Options available on request:

- HF- High Frequency control gear
- HS- For high pressure sodium lamps
- HM- For high pressure mercury lamps
- HI- For metal halide lamps