

# LEVANTO PLN LED

## Slim Profile LED Panel



Type:	A slim profile LED panel with opal diffuser to create an attractive environment and a sense of natural light.
Specification:	UV stable opal diffuser. Fully enclosed white aluminium body. Luminaire is plastic-wrapped and packed individually.
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm. Suspension brackets included. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use Levanto PLN LED recessed mounting kit (to be ordered separately).
Application:	Indoor. Office buildings, shops and other commercial environments.



Surface mounting box for Levanto PLN LED available on request. For more information check product list.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Levanto PLN LED1x3400 C169 T830 OP	596x596x11	36000	3314	40	80+	3000	3,40
Levanto PLN LED1x3400 C169 T840 OP	596x596x11	36000	3400	40	80+	4000	3,40
Levanto PLN LED Surface MTG KIT (600x600)	605x605x50						1,5
Levanto PLN LED Recessed MTG KIT (620x620)	620x620x35						0,5

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
IP44-	IP44 protection degree (for recessed version)
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

### LEVANTO PLN LED1X3400 C169 T840 OP

