BLADE ECO

Industrial Luminaire with a Choice from Narrow to Wide Beam Distribution





Type:	An industrial luminaire with a choice of narrow, middle or wide beam lamp holder position.
Specification:	High efficiency MIRO aluminium reflector with multi-position lamp holders mounting system.
	IP23 rated body is made of galvanised steel.
	Luminaire is plastic-wrapped and packed in single boxes.
Installation:	Surface luminaire is designed to be fixed to ceiling of any type or suspended.
Application:	Indoor. For use in warehouse, production facilities, halls, logistics centers, shops and sports facilities.



The industrial luminaire with changing lamp holders place allows to choose three different light beam distributions: narrow, middle or wide.

Name	Overall dimensions (LxWxH), mm	Lamp (W) and socket	System power, W	Weight, kg
Blade ECO 128 U46 MTO	1250x158x114	1x28 (G5)	30	3
Blade ECO 154 U47 MTO	1250x158x114	1x54 (G5)	58	3
Blade ECO 228 U48 MTO	1250x158x114	2x28 (G5)	60	3
Blade ECO 254 U49 MTO	1250x158x114	2x54 (G5)	116	3
Blade ECO 328 U50 MTO	1250x158x114	3x28 (G5)	90	3.2
Blade ECO 354 U51 MTO	1250x158x114	3x54 (G5)	174	3.2
Blade ECO 135 U52 MTO	1550x158x114	1x35 (G5)	38	3.6
Blade ECO 149 U53 MTO	1550x158x114	1x49 (G5)	53	3.6
Blade ECO 180 U54 MTO	1550x158x114	1x80 (G5)	85	3.6
Blade ECO 235 U55 MTO	1550x158x114	2x35 (G5)	75	3.6
Blade ECO 249 U56 MTO	1550x158x114	2x49 (G5)	104	3.6
Blade ECO 280 U57 MTO	1550x158x114	2x80 (G5)	170	3.6
Blade ECO 335 U58 MTO	1550x158x114	3x35 (G5)	113	3.8
Blade ECO 349 U59 MTO	1550x158x114	3x49 (G5)	157	3.8
Blade ECO 380 U60 MTO	1550x158x114	3x80 (G5)	255	3.8

Name	Overall dimensions (LxWxH), mm	Lamp (W) and socket	System power, W	Weight, kg
Blade ECO 158 U83 MTO HF *	1600x158x114	1x58 (G13)	54	3.6
Blade ECO 258 U84 MTO HF *	1600x158x114	2x58 (G13)	107	3.7
Blade ECO 358 U75 MTO HF *	1600x158x114	3x58 (G13)	161	3.9

^{*-} Blade ECO with T8 tubes is subject to minimum quantity


Options available on request:DIM- Dimmable ballast Deluxe- MIRO4 reflector SDIM-Switch-control/dimming MTO-MIRO5 reflector

DALI-DALI ballast


NAR-Lamp holders in narrow beam position Emergency version 1 hour Emergency version 3 hours Lamp holders in middle beam position Lamp holders in wide beam position EMG-MID-WID-EM3-

5TB-5 way terminal block with two holes (for in and out going cable)

BLADE ECO 249 U56 MTO NAR



BLADE ECO 249 U56 MTO MID



BLADE ECO 249 U56 MTO WID

