

CYGNI

Aluminium IP65 Luminaire



CYGNI 128 Q99

Type:	Dust and moisture proof IP65 fixture is made of aluminium profile.
Specification:	Tempered safety glass is fixed to the body. Glossy aluminium reflector. The body is made of extruded aluminium profile, dark grey finished. Silicone rubber sealing provides reliable IP protection. Luminaire is plastic-wrapped and boxed individually.
Installation:	Surface mounted luminaire is designed to be fixed to walls of any type.
Application:	Outdoor. Dust and moisture proof luminaire, efficient floodlight for building facades and bridges.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Cygni 114 Q97	1x14 (G5)	630x62x63	2,1	16
Cygni 124 Q98	1x24 (G5)	630x62x63	2,1	25
Cygni 128 Q99	1x28 (G5)	1200x62x63	4,1	30
Cygni 154 R01	1x54 (G5)	1200x62x63	4,1	58

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Cygni LED1x1200 E257 T830	630x62x63	50000	1106	10	80+	3000	2,10
Cygni LED1x2500 E258 T830	1200x62x63	50000	2335	21	80+	3000	4,10
Cygni LED1x1200 E257 T840	630x62x63	50000	1123	10	80+	4000	2,10
Cygni LED1x2500 E258 T840	1200x62x63	50000	2438	21	80+	4000	4,10

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

DIM-	Dimmable ballast / driver 1-10V
DALI-	DALI ballast / driver
SDIM-	Switch-control/dimming
OP-	Opal diffuser
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K

CYIGNI LED1X2500 E258 T840

