

Ursa

Recessed Downlight with Vertical Lamp Position



Ursa 118 I22 SOP



Ursa 118 I22

Type:	Recessed downlight with vertical lamp position for compact fluorescent lamps.
Specification:	Glossy aluminium reflector with white powder coated steel ring. Body in steel in white finish, gearbox in grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Lamp (W) and holder	Overall dimensions (cut-out), mm	Weight, kg	Total wattage, W
Ursa 1E27 I20 FCT	40W (E27)	ø180(155)x205	0,8	-
Ursa 113 I21 FCT	1x13W (G24d-1)	ø180(155)x205	1,1	19
Ursa 118 I22 FCT	1x18W (G24d-2)	ø180(155)x205	1,1	26
Ursa 1E27 I20 SOP	40W (E27)	ø180(155)x185	1,0	-
Ursa 113 I21 SOP	1x13W (G24d-1)	ø180(155)x185	1,2	19
Ursa 118 I22 SOP	1x18W (G24d-2)	ø180(155)x185	1,2	26

Options available on request:

HF-	High Frequency control gear
DIM-	Dimmable ballast
SDIM-	Switch-control/dimming
DALI-	DALI ballast
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
FCT-	Faceted reflector
SOP-	Surface frosted glass cover (IP44)
RAL-	RAL colours