

Negara

IP65 Batten for Humid&Dusty Rooms



NEGARA 158 H05

Type:	Water and dust resistant IP 65 batten type luminaire for use in adverse conditions.
Specification:	Injection moulded glass fiber reinforced housing and cover with quick locking system. Grey finished. Luminaire can be fitted with white painted steel reflector and protective tubes on request (see Option list). Starters are accessible from outside. Luminaire is plastic wrapped and boxed individually.
Installation:	Surface luminaire designed to be fixed to ceiling of any type or suspended.
Application:	Indoor. Suitable for production halls, workshops and car parks with dusty, humid environment.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Negara 118 H01	1x18 (G13)	661x66x115	1,25	26
Negara 136 H03	1x36 (G13)	1271x66x115	1,8	42
Negara 158 H05	1x58 (G13)	1571x66x115	2,3	67
Negara 218 H02	2x18 (G13)	661x117x115	1,35	42
Negara 236 H04	2x36 (G13)	1271x117x115	2,6	84
Negara 258 H06	2x58 (G13)	1571x117x115	3,35	134

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Negara 114 L82	1x14 (G5)	661x66x115	1	15
Negara 124 L83	1x24 (G5)	661x66x115	1	25
Negara 128 L84	1x28 (G5)	1271x66x115	1,7	30
Negara 154 L87	1x54 (G5)	1271x66x115	1,7	58
Negara 135 L85	1x35 (G5)	1571x66x115	2,1	38
Negara 149 L86	1x49 (G5)	1571x66x115	2,1	53
Negara 180 L88	1x80 (G5)	1571x66x115	2,1	85
Negara 214 L89	2x14 (G5)	661x117x115	1,1	31
Negara 224 L90	2x24 (G5)	661x117x115	1,1	50
Negara 228 L91	2x28 (G5)	1271x117x115	1,8	60
Negara 254 L94	2x54 (G5)	1271x117x115	1,8	116
Negara 235 L92	2x35 (G5)	1571x117x115	2,2	75
Negara 249 L93	2x49 (G5)	1571x117x115	2,2	104
Negara 280 L95	2x80 (G5)	1571x117x115	2,2	170

Options available on request:

HF- High Frequency control gear
 DALI- DALI ballast
 SDIM- Switch-control/dimming
 DIM- Dimmable ballast
 EMG- Emergency version 1 hour
 EM3- Emergency version 3 hours
 TUBE- PMMA protective tube
 RFL- White symmetric reflector
 SPORT- White painted protective grid
 Deluxe- Symmetric aluminium reflector

5TB- 5 way terminal block with two holes
 1LIN- Through wiring 3x1.5 mm² with two push-in terminals
 3LIN- Through wiring 5x1.5 mm² with two push-in terminals
 1LIN2,5- Through wiring 3x2.5 mm² with two push-in terminals
 3LIN2,5- Through wiring 5x2.5 mm² with two push-in terminals
 CBF3x1,5- Outgoing flexcable 3x1,5mm² ready for connection (-length, m)
 CBF5x1,5- Outgoing flexcable 5x1,5mm² ready for connection (-length, m)
 CBF3x2,5- Outgoing flexcable 3x2,5mm² ready for connection (-length, m)
 CBF5x2,5- Outgoing flexcable 5x2,5mm² ready for connection (-length, m)

NEGARA 236 H04 HF

