

BREEZE DPAR

T5 & T8 Recessed Luminaire with Double Parabolic Louvre



BREEZE 414 M70

Type:	A recessed T5/T8 luminaire with a double parabolic louvre.
Specification:	<p>A glossy double parabolic reflector with glossy cross blades. Louvre is fitted into the body with locking safety clips for maximum stability.</p> <p>Fully enclosed painted steel body, wiring is concealed and not visible from ground level.</p> <p>Luminaire is plastic-wrapped and packed in twin boxes.</p>
Installation:	Fits 15-24mm exposed T-Bar ceiling 600x600mm. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use recessed mounting kit S620x620 (to be ordered separately).
Application:	Indoor. Office buildings, shops and other commercial environments.

Type	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Breeze 418 I92	4x18 (G13)	595x595x72	3,7	84
Breeze 414 M70	4x14 (G5)	595x595x72	2,9	62
Breeze 424 M71	4x24 (G5)	595x595x72	2,9	98

2 or 3 Tube (2/3x18/14W) versions are available on request

Options available on request:

HF-	High Frequency control gear
DIM-	Dimmable ballast 1-10V
SDIM-	Switch-control/dimming
DALI-	DALI ballast
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
5TB-	5 way terminal block for loop feed and ease of wiring
MAT-	Matted reflector (subject to minimum quantity)
WIE-	3-pole Wieland or similar connector (subject to minimum quantity)
QCK-	Quick connection version, includes tubes.