

# AQUARIUS LED

## Adjustable Circular LED Downlight



<b>Type:</b>	A range of round adjustable circular LED downlights for accent lighting applications.
<b>Specification:</b>	Aluminium faceted reflector with tempered glass. Light beam 60°. Body in cast aluminium in white finish. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
<b>Application:</b>	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Aquarius LED1x1600 D323 T840 CLR	Ø185(177)x150	50000	1597	14	80+	4000	2,50
Aquarius LED1x2300 D324 T840 CLR	Ø185(177)x150	50000	2216	21	80+	4000	2,50
Aquarius LED1x3000 D325 T840 CLR	Ø185(177)x150	50000	2990	28	80+	4000	2,50

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

SDIM-	Switch-control/dimming
DALI-	DALI driver
CLR-	Clear glass
R36-	Reflector with 36° light beam angle (subject to minimum quantity)
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
RAL-	RAL colours

### AQUARIUS LED1X3000 D325 T840 CLR

