NORTE

Low-Bay Luminaire











NORTE 1250 G96 HI GRID

NORTE 1250 G96 HI FRAME

NORTE LED1X10800 D439 T750 L60

Type: Luminaire for high mounting applications for metal halide lamps. High performance, ideal for high mounting applications.

Parabolic symmetric reflector in faceted aluminium. Tempered glass cover.

Light grey painted steel body.

Luminaire is plastic-wrapped and packed individually.

Installation: Suitable for surface mounting on ceiling.

Application: Indoor. For use in factories, warehouses, garages, halls and many others commercial applications.

| Name | Description | Lamp (W) and holder | Overall dimensions (LxWxH), mm | Weight, kg | Total wattage, W | |
|-------------------|-------------|---------------------|-----------------------------------|------------|---------------------|--|
| Norte 1150 G95 HI | HI | 1x150 (E27) | 490x365x175 | 7,5 | 170 | |
| Norte 1250 G96 HI | HI | 1x250 (E40) | 490x365x175 | 7,9 | 280 | |
| Norte 1400 G97 HI | HI | 1x400 (E40) | 490x365x175 | 8,4 | 440 | |
| Norte 1150 G98 HS | HS | 1x150 (E40) | 490x365x175 | 7,5 | 170 | |
| Norte 1250 G96 HS | HS | 1x250 (E40) | 490x365x175 | 7,9 | 280 | |
| Norte 1400 G97 HS | HS | 1x400 (E40) | 490x365x175 | 8,4 | 440 | |

| Name | Overall dimensions (LxWxH), mm | Lifetime | Luminaire output*, lm Ta=25°C | System power*, W | CRI (Ra) | сст, к | Weight, kg |
|------------------------------------|--------------------------------------|----------|-------------------------------------|------------------------|-------------|--------|---------------|
| Norte LED1x8600 D438 T750 L45 | 490x365x175 | 50000 | 9085 | 80 | 70+ | 5000 | 8,50 |
| Norte LED1x10800 D439 T750 L45 | 490x365x175 | 50000 | 11356 | 99 | 70+ | 5000 | 8,50 |
| Norte LED1x8600 D438 T750 L60 | 490x365x175 | 50000 | 9085 | 80 | 70+ | 5000 | 8,50 |
| Norte LED1x10800 D439 T750 L60 | 490x365x175 | 50000 | 11356 | 99 | 70+ | 5000 | 8,50 |
| Norte LED1x8600 D438 T750 L60x120 | 490x365x175 | 50000 | 9085 | 80 | 70+ | 5000 | 8,50 |
| Norte LED1x10800 D439 T750 L60x120 | 490x365x175 | 50000 | 11356 | 99 | 70+ | 5000 | 8,50 |

 $^{^{\}ast}$ Tolerance range for optical and electrical data: $\pm 10~\%$

Options available on request:

DIM-Dimmable ballast / driver Switch-control/dimming
DALI ballast / driver
For high pressure sodium lamp
Protective grid SDIM-DALI-

HS-


GRID-

FRAME-Frame for recessed mounting


IP65-IP65 version Asymmetric reflector AS-Colour temperature 3000K T830-Colour temperature 4000K Colour temperature 5000K T840-T850-

Lens 45° L45-Lens 60° L60-L60x120- Lens 60x120°

NORTE LED1X10800 D439 T750 L45



NORTE LED1X10800 D439 T750 L60



NORTE LED1X10800 D439 T750 L60X120

