

ORION

Recessed Downlight for Compact Fluorescent Lamp



ORION 226 B28 GLR



ORION 226 B28 OGL

Type:	Recessed downlight with horizontal lamp position for compact fluorescent lamps.
Specification:	Gloss aluminium reflector with white powder coated steel ring. Body in steel in white finish, gearbox in grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Lamp (W) and holder	Overall dimensions (cut-out), mm	Weight, kg	Total wattage, W
Orion 113 D45	1x13W (G24d-1)	ø193(165)x100	1,3	19
Orion 213 D46	2x13W (G24d-1)	ø193(165)x100	1,7	38
Orion 118 E60	1x18W (G24d-2)	ø193(165)x100	1,4	26
Orion 218 B27	2x18W (G24d-2)	ø193(165)x100	1,8	52
Orion 126 I95	1x26W (G24d-3)	ø193(165)x100	1,5	34
Orion 226 I96	2x26W (G24d-3)	ø193(165)x100	1,9	68
Orion 126 D47	1x26W (G24d-3)	ø235(210)x126	1,6	34
Orion 226 B28	2x26W (G24d-3)	ø235(210)x126	2,1	68
Orion 132 J40 HF	1x32W (Gx24q-3)	ø235(210)x126	1,2	32
Orion 142 J41 HF	1x42W (Gx24q-4)	ø235(210)x126	1,2	44
Orion 132 J38 HF	1x32W (Gx24q-3)	ø265(235)x178	1,7	32
Orion 232 K28 HF	2x32W (Gx24q-3)	ø265(235)x178	1,8	64
Orion 142 J39 HF	1x42W (Gx24q-4)	ø265(235)x178	1,7	44
Orion 242 K29 HF	2x42W (Gx24q-4)	ø265(235)x178	1,8	85



Steel ring can be optional: RAL powder coated, chrome or gold plated (see option list)

Options available on request:

HF-	High Frequency control gear
DIM-	Dimmable ballast
SDIM-	Switch-control/dimming
DALI-	DALI ballast
EMG-	Emergency version 1 hour
EM3-	Emergency version 3 hours
5TB-	5 way terminal block for loop feed and ease of wiring
MAT-	Matted reflector
FCT-	Faceted reflector
OGL-	Decorative glass outside (in middle frosted)
GLR-	Decorative frosted ring outside
RAL-	RAL colours
CR-	Chrome plated ring
GOLD-	Gold plated ring

