


## Barat PAR

### IP66 for High Mounting Applications



**BARAT 249 I71 PC/PC PAR**



**BARAT 236 I17 PC/PMMA PAR IC**



**BARAT 236 I17 PC/PMMA PAR IC**

<b>Type:</b>	Dust and moisture proof IP66 fixture for high mounting applications. High performance.
<b>Specification:</b>	Luminaires are available with injection moulded UV stabilized IK08 polycarbonate (or IK03 PMMA) diffuser for high impact resistance. Specular aluminium parabolic reflector. Injection moulded polycarbonate canopy, grey finished. Diffuser retaining clips and sealing washers from the end of the body for easy maintenance. Luminaire is plastic-wrapped and boxed individually.
<b>Installation:</b>	Surface mounted luminaire is designed to be fixed to ceiling of any type or suspended. Supplied with two fixing brackets for easy installation, sealing washer and accessories for chain and wire suspension.
<b>Application:</b>	Indoor. Dust and moisture proof luminaire, ideal for installations higher than 5 meters. For use in factories, warehouses, garages, halls and many others commercial applications.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Barat 136 I16 PC/PMMA PAR	1x36 (G13)	1272x96x111	2,6	42
Barat 236 I17 PC/PMMA PAR	2x36 (G13)	1272x146x111	3,9	84
Barat 158 I18 PC/PMMA PAR	1x58 (G13)	1572x96x111	3,3	67
Barat 258 I19 PC/PMMA PAR	2x58 (G13)	1572x146x111	5,1	134
Barat 136 I16 PC/PC PAR	1x36 (G13)	1272x96x111	2,6	42
Barat 236 I17 PC/PC PAR	2x36 (G13)	1272x146x111	3,9	84
Barat 158 I18 PC/PC PAR	1x58 (G13)	1572x96x111	3,3	67
Barat 258 I19 PC/PC PAR	2x58 (G13)	1572x146x111	5,1	134

