

BOREAS

Discharge Floodlight for Metal Halide Lamps with Symmetric Reflector



Type:	A range of discharge floodlights with symmetric reflector for metal halide lamps. IP65 - water and dust protection for use in adverse conditions.
Specification:	Faceted symmetric reflector in anodized aluminium. Tempered glass diffuser. Body in aluminium in dark grey finish. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for any horizontal and/or vertical surfaces.
Application:	Outdoor. Efficient floodlight for building facades and perimeters, billboards, displays, car parks, etc.

Name	Lamp (W) and holder	Overall dimensions (LxWxH), mm	Weight, kg	Total wattage, W
Boreas 1150 I79 HI	1x150 (E27)	514x420x146	7,2	168
Boreas 1250 E77 HI	1x250 (E40)	514x420x146	8,2	280
Boreas 1400 E78 HI	1x400 (E40)	514x420x146	9	440
Boreas 1150 I79 HS	1x150 (E27)	514x420x146	7,2	168
Boreas 1250 E77 HS	1x250 (E40)	514x420x146	8,2	280
Boreas 1400 E78 HS	1x400 (E40)	514x420x146	9	440

Options available on request:

HF-	High Frequency control gear
TIM-	Timed ignitor
HI-	For metal halide lamp
HS-	For high pressure sodium lamp

BOREAS 1250 E77 HI

