

BENTU LED

Luminaire for Use in Logistics Centers



Type:	Luminaire for high mounting applications between shelves or open areas.
Specification:	IP65 version is made with clear polycarbonate diffuser for protection from splinklers water jet. Optics: 45°, 60° or 120x60° beam. Three versions: without sensor, with PIR sensor or with PIR&DAYLIGHT sensor. Light grey aluminium body. Luminaire is plastic-wrapped and packed individually.
Installation:	Surface mounted luminaire is designed to be fixed to ceiling of any type or suspended.
Application:	Indoor. For use in warehouse, production facilities, halls and logistics centers with ceiling heights of 10-12 meters and higher.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Bentu LED1x8600 D443 T750 L45	1200x100x76	50000	9085	80	70+	5000	7,00
Bentu LED1x10800 D444 T750 L45	1200x100x76	50000	11356	99	70+	5000	7,20
Bentu LED1x12900 D445 T750 L45	1200x100x76	50000	13627	119	70+	5000	7,20
Bentu LED1x15000 D446 T750 L45	1500x100x76	50000	15898	139	70+	5000	8,90
Bentu LED1x17200 D447 T750 L45	1500x100x76	50000	18170	159	70+	5000	8,90
Bentu LED1x8600 D443 T750 L60	1200x100x76	50000	9085	80	70+	5000	7,00
Bentu LED1x10800 D444 T750 L60	1200x100x76	50000	11356	99	70+	5000	7,20
Bentu LED1x12900 D445 T750 L60	1200x100x76	50000	13627	119	70+	5000	7,20
Bentu LED1x15000 D446 T750 L60	1500x100x76	50000	15898	139	70+	5000	8,90
Bentu LED1x17200 D447 T750 L60	1500x100x76	50000	18170	159	70+	5000	8,90

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

DIM-	Dimmable driver 1-10V
SDIM-	Switch-control/dimming
DALI-	DALI driver
T830-	Colour temperature 3000K
T840-	Colour temperature 4000K
T750-	Colour temperature 5000K
L45-	Lens 45°
L60-	Lens 60°

BENTU LED1x12900 D445 T750 L60

